
Inductive proximity sensors

XS range

Catalogue



Simply easy!™



Telemecanique
Sensors

Inductive proximity sensors

XS range

Selection guidepage 2

- Generalpage 12
- Flush mountability using teach mode:
Simplicity through innovationpage 70

XS range, general purpose

- Cylindrical type
 - Standard range, flush mountablepage 22
 - Increased range, flush mountablepage 32
 - Increased range, non flush mountablepage 40
- Block type
 - Standard range, flush mountablepage 46
- Cubic type
 - 40 x 40 x 70 mm format, flush or non flush mountablepage 50
 - 40 x 40 x 117 mm format, flush or non flush mountablepage 52
- Multivoltage sensors with short-circuit protectionpage 54
- Sensors with 2 complementary outputs
 - Solid-state PNP or NPN, NO + NC outputspage 56
 - Solid-state PNP + NPN, NO or NC programmable outputspage 62
- Plastic case sensorspage 64
(for chemical processing, marine applications)
- Quasi flush mountable sensors, increased rangepage 66
- Miniature sensorspage 68

XS range, Application

- Adjustable range sensorspage 72
- Sensors for rotation monitoringpage 77
- Sensors with analogue outputpage 81
- Sensors for food/beverage and pharmaceutical applications
 - Cubic, plasticpage 88
 - Cylindrical, stainless steelpages 92 and 94
 - Cylindrical, plasticpages 96 and 98
 - Cylindrical, stainless steel, for harsh industrial environmentspage 100
- Sensors for assembly, packaging and light material handling applications
 - 12 x 26 x 40 mm formatpage 102
 - 80 x 80 x 40 mm formatpage 106
- Sensors for welding machine applicationspages 108 to 110
- Selective detection of ferrous and non ferrous materialspage 112
- Accessoriespage 118
- Detection curvespage 122
- Substitution tablepage 126
- Product reference indexpage 132

Inductive proximity sensors
XS range
General purpose

Cylindrical type		Standard range				
		Flush mountable				
						
Sensing distance Sn (mm)		1.5	2	5	10	
Diameter		Ø 6.5 plain and M8	M12	M18	M30	
Short case	Supply	Page 22				
	3-wire ⋯ (PNP/NPN)	Page 26				
	2-wire ⋯					
Long case	Supply	Page 23				
	3-wire ⋯ (PNP/NPN)	Page 27				
	2-wire ⋯					
	2-wire ⋈	Page 30				
Function	NO	•	•	•	•	
	NC	•	•	•	•	
Connection	Pre-cabled (L = 2 m) (1)	•	•	•	•	
	M8 connector, 3-pin (3-wire ⋯)	•	–	–	–	
	M12 connector	•	•	•	•	
	1/2"-20UNF connector	–	•	•	•	
	Remote connector	Remote connectors available: M8, M12, M18, screw terminal, 7/8", DIN: please consult our Customer Care Centre				
Degree of protection		IP 65 and IP 67, IP 68 for pre-cabled version, IP 69K for diameters 12 to 30				
Special temperatures	– 40 °C, + 70 °C	Add the suffix TF to the end of the reference (2)				
	– 25 °C, + 85° C	Add the suffix TT to the end of the reference (2)				
Type reference		XS506	XS508	XS512	XS518	XS530
Pages		22 to 31				

(1) Also available in lengths of 5 and 10 m, depending on model
(2) Product availability depending on model: please consult our Customer Care Centre.

Increased range										
Flush mountable				Non flush mountable						
										
2.5	4	8	15	4	7	8	12	16	22	30
Ø 6.5 plain and M8	M12	M18	M30	M8	M12		M18		M30	
Pages 32 and 33				–	–	Page 42	–	Page 42	–	–
Page 36				–	–	–	–	–	–	–
Page 34				Page 40	Page 40	–	Page 40	–	–	Page 40
Page 36				–	–	–	–	–	–	–
–	Page 38			–	–	–	Page 44	–	Page 44	–
•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•
•	–	–	–	•	–	–	–	–	–	–
•	•	•	•	–	•	•	•	•	•	•
–	•	•	•	–	–	–	•	–	•	–
Remote connectors available: M8, M12, M18, screw terminal, 7/8", DIN: please consult our Customer Care Centre										
IP 65 and IP 67, IP 68 for pre-cabled version, IP 69K for diameters 12 to 30				IP 65 and IP 67, IP 68 for pre-cabled version, IP 69K for diameters 12 to 30						
Add the suffix TF to the end of the reference (2)										
Add the suffix TT to the end of the reference (2)										
XS106 XS606	XS112 XS612	XS118 XS618	XS130 XS630	XS608	XS612	XS212	XS618	XS218	XS630	
XS108 XS608										
32 to 39				40 to 45						

Inductive proximity sensors
XS range
General purpose

Block type		Standard range				
		Flush mountable				
						
Sensing distance Sn (mm)		2.5	5	10	15	40
Dimensions (W x H x D)		8 x 22 x 8	15 x 32 x 8	26 x 26 x 13	40 x 40 x 15	80 x 80 x 26
Supply	3-wire --- (PNP/NPN)	Page 46	Page 46	Page 48	Page 48	Page 48
	2-wire ---	Page 46	Page 46	Page 48	Page 48	Page 48
	~	–	–	–	–	–
Function	NO	•	•	•	•	•
	NC	•	•	•	•	•
	NO + NC	–	–	–	–	–
	NO/NC	–	–	–	–	–
Connection	Pre-cabled (L = 2 m) (1)	•	•	•	•	•
	M8 connector, 3-pin (3-wire ---)	–	–	•	•	–
	M12 connector	–	–	–	–	•
	1/2"-20UNF connector	–	–	–	–	–
	Screw terminals	–	–	–	–	–
	Remote connector	•	•	–	–	–
				–	–	–
				•	•	–
	Other remote connectors available	–	–	–	–	–
Degree of protection		IP 67				
		IP 67, double insulation ☐ or IP 68, double insulation ☐, depending on model				
Special temperatures		Add the suffix TF to the end of the reference (2)				
		Add the suffix TT to the end of the reference (2)				
Type reference		XS7J	XS7F	XS7E	XS7C	XS7D
Pages		46		48		

(1) Also available in lengths of 5 and 10 m, depending on model.
(2) Product availability depending on model: please consult our Customer Care Centre.

Standard and increased ranges		
Flush mountable		Non flush mountable
		
15	20	40
40 x 40 x 70 and 40 x 40 x 117		
Pages 50 and 52		
Pages 50 and 52		
Pages 50 and 52		
•	•	•
•	•	•
–	•	•
•	•	•
–	–	–
–	–	–
•	•	•
•	•	•
•	•	•
–	–	–
–	–	–
–	–	–
–	–	–
IP 65, IP 67 and IP 69K		
Add the suffix TF to the end of the reference (2)		
Add the suffix TT to the end of the reference (2)		
XS7C2, XS7C4, XS8C2 and XS8C4		
50 and 52		


Inductive proximity sensors
XS range
General purpose

Sensor type: flush and non flush mountable		Multivoltage sensors	Sensors with 2 complementary outputs	
		With short-circuit protection	Solid-state PNP or NPN NO + NC outputs	Solid-state PNP + NPN, NO or NC programmable outputs
				
Sensing distance Sn (mm)	Flush mountable Non flush mountable	2 ... 10 4 ... 15	1.5 ... 15 2.5 ... 15	2 ... 10 4 ... 15
Diameter		Threaded: M12, M18, M30	Plain: Ø 6.5 Threaded: M8, M12, M18, M30	Threaded: M12, M18, M30
Case material		Nickel plated brass	Nickel plated brass or stainless steel or plastic	Nickel plated brass or plastic
Supply	— ~ ~	— — •	• — —	• — —
Function	NO NC NO + NC NO/NC	• • — —	— — • —	— — — • programmable
Connection	Pre-cabled (L = 2 m) (1) M8 connector, 3-pin (3-wire ---) M12 connector 1/2"-20UNF connector Remote connector	• — — •	• — • —	• — • —
Degree of protection		Remote connectors available: M8, M12, M18, screw terminal, 7/8", DIN: please consult our Customer Care Centre		
Special temperatures	- 40 °C, + 70 °C - 25 °C, + 85 °C	IP 67, IP 68 or IP 69K depending on model		
Type reference		Add the suffix TF to the end of the reference (2) Add the suffix TT to the end of the reference (2)		
Pages		XS1M XS2M 54	XS1●●●C410 XS4P●●●C410 XS1●●B3PC● 56 and 60	XS1M●●KP340 XS2M●●KP340 XS4P●●KP340 62

(1) Also available in lengths of 5 and 10 m, depending on model.
(2) Product availability depending on model: please consult our Customer Care Centre.

Plastic case sensors	Basic sensors	Almost flush mountable sensors	Miniature sensors	
For chemical processing, marine applications	For repetitive machines			For robotic, transfer machine, assembly line applications
				
— 2.5 ... 15	1.5 ... 10 2.5 ... 15	2.5 ... 15 —	— 2.5 ... 20	1 —
Threaded: M8, M12, M18, M30	Threaded: M8, M12, M18, M30	Threaded: M8, M12, M18, M30	Plain: Ø 4 Threaded: M5	
Plastic	Nickel plated brass	Nickel plated brass	Nickel plated brass or stainless steel	
• — •	• — —	• — —	• — —	• — —
— • — —	• • — —	• • — —	• • — —	• • — —
• — — •	• • • —	• • • —	• • • —	• • • —
Remote connectors available: M8, M12, M18, screw terminal, 7/8", DIN: please consult our Customer Care Centre				
IP 67 or IP 68 depending on model	IP 67	IP 65 or IP 67	IP 67 or IP 68 IP 69K depending on model	IP 67
Add the suffix TF to the end of the reference (2) Add the suffix TT to the end of the reference (2)				
XS4P	XS1●●BL● XS2●●BL●	XS1●●BH●	XS1N●●349	XS1L XS2L XS1N
64	Please refer to our catalogue Inductive proximity sensors XS range. Basics line		66	68

Applications



Conveying

Sensor type: flush and non flush mountable


Adjustable range sensors

Developed in accordance with the needs expressed by our customers, these sensors provide a complete solution for specific application functions: rotation monitoring, selective detection, analogue control, etc.




Sensing dist. Sn (mm)	Flush mountable Non flush mountable	3...11 (1) 5...18 (1)	15	25	60
Form	Cylindrical	M12 x 54 M18 x 67 M30 x 71	–	–	–
	Block (W x H x D) dimensions in mm	–	26 x 26 x 13	40 x 40 x15	80 x 80 x 26
Case material		Nickel plated brass	PBT	PBT	PBT
Supply		●	●	●	●
		–	–	–	–
		–	●	●	●
Function	NO	●	●	●	●
	NC	●	●	●	●
	NO + NC	–	–	–	–
	NO/NC	–	–	–	–
Connection	Pre-cabled (L = 2 m) (2)	–	●	●	●
	M8 connector, 3-pin (--- 3-wire)	–	●	●	–
	M12 connector	–	–	–	●
	1/2"-20UNF connector	–	–	–	●
	Remote connector	●	●	●	●
	Screw terminals	–	–	–	–
Degree of protection		IP 67, double insulation 	IP 67, double insulation  or IP 68, double insulation  , depending on model.		
Special temperatures	– 40 °C, + 70 °C	Add the suffix TF to the end of the reference (3)			
	– 25 °C, + 85 °C	Add the suffix TT to the end of the reference (3)			
Type reference		XS612B2 XS618 B2 XS630 B2	XS8E	XS8C	XS8D
Pages		72	74		


(1) Depending on model.
(2) Also available in lengths of 5 and 10 m, depending on model.
(3) Product availability depending on model: please consult our Customer Care Centre.



Detection of underspeed, shaft overload



Position, displacement and deformation control/monitoring



Machine with stainless steel housing

Sensors for rotation monitoring


Sensors with analogue output
0 ... 10 V or 4 ... 20 mA

Sensors for food/beverage and pharmaceutical applications
Cylindrical, stainless steel 316 L
Cylindrical, plastic



10	10...15 (1)	0.2...10 (1)	5...40 (1)	—	—	6,10 or 20 (1)	—	—
10	10...15 (1)	0.4...15 (1)	5...40 (1)	2...25	2...25	10, 20 or 40 (1)	7...22 (1)	7...22 (1)
M30 x 81	—	Threaded: M12, M18, M30	—	—	—	Threaded: M12, M18, M30	Plain: Ø 18 Threaded: M12, M18, M30	Threaded: M12, M18, M30
—	26 x 26 x 13 40 x 40 x 15	—	32 x 15 x 8 26 x 26 x 13 40 x 40 x 15 80 x 80 x 26	40 x 40 x 70	40 x 40 x 117	—	—	—
Metal	PBT	Metal or plastic	PBT	PBT	PBT	Stainless steel, 316 L	Stainless steel, 316 L	Plastic, PPS
●	●	●	●	●	●	●	●	●
—	—	—	—	—	—	—	—	—
●	●	—	—	—	—	—	●	●
—	—	—	—	—	—	●	●	●
●	●	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—
●	—	●	●	—	—	—	●	●
—	—	—	—	—	—	—	—	—
—	—	—	●	●	—	●	●	●
—	—	—	—	—	—	—	●	●
—	●	—	●	—	—	—	—	—
—	—	—	—	—	●	—	—	—
IP 67	IP 67, double insulation ☐	IP 67	IP 67 or IP 68 (pre-cabled version)	IP 65, IP 67 IP 69K	IP 65, IP 67 IP 69K	IP 68, IP 69K	IP 68 (pre-cabled version), double insulation ☐ IP 69K conforming to DIN 40050	
Add the suffix TF to the end of the reference (3)								
Add the suffix TT to the end of the reference (3)								
XSAV	XS9●11R	XS1M●●●AB1 XS4P●●AB1	XS9●●●●A	XS9C2	XS9C4	XS9●●S●	XS2●●SA	XS2●●AA
77	79	81	85 and 87	88	88	90	92 and 94	96 and 98

Applications



Conveying

Sensor type: flush and non flush mountable

Developed in accordance with the needs expressed by our customers, these sensors provide a complete solution for specific application functions: rotation monitoring, selective detection, analogue control, etc.


Sensors for conveying and material handling applications		
Cylindrical, stainless steel 303	12 x 40 x 26 format	80 x 80 x 40 format, increased range



Sensing dist. Sn (mm)	Flush mountable
	Non flush mountable
Form	Cylindrical
	Block (W x H x D) dimensions in mm
Case material	
Supply	11
	2
	2
Function	NO
	NC
	NO + NC
	NO/NC
Connection	Pre-cabled (L = 2 m) (2)
	M8 connector, 3-pin (--- 3-wire)
	M12 connector
	1/2"-20UNF connector
	Remote connector
	Screw terminals
Degree of protection	
Special temperatures	- 40 °C, + 70 °C
	- 25 °C, + 85 °C
Type reference	
Pages	

3, 6, 10 or 20 (1)	2	50
6, 10, 20 or 40 (1)	4	42
Threaded: M8, M12, M18, M30	–	–
–	12 x 40 x 26	80 x 80 x 40
Stainless steel 303	Plastic	Plastic
•	•	•
–	–	–
–	•	–
•	•	•
–	•	–
–	•	–
–	–	–
–	•	–
–	•	–
•	–	•
–	–	–
–	–	–
–	–	–
–	–	–
IP 67 and IP 69K	IP 67	IP 67, double insulation ☐
Add the suffix TF to the end of the reference (3)		
Add the suffix TT to the end of the reference (3)		
XS9●●R●	XS7G XS8G	XS7D
100	102	106

(1) Depending on model.
(2) Also available in lengths of 5 and 10 m, depending on model.
(3) Product availability depending on model: please consult our Customer Care Centre.



Robotics

Assembly machines, conveyor systems, material handling

Sensors for welding machine applications	Factor 1 (Fe/Nfe) sensors for ferrous and non ferrous materials			Selective detection sensors for ferrous materials only or non ferrous materials only
Cylindrical, stainless steel 303	Cylindrical	Cubic	Rectangular	Cylindrical




6 or 10 (1)	5, 10 or 15 (1)	20	20	5
–	–	–	–	–
Threaded: M12, M18	Threaded: M18, M30	–	–	Threaded: M18
–	–	40 x 40 x 70	40 x 40 x 117	–
Stainless steel 303	Metal	PBT	PBT	Metal
●	●	●	●	●
–	–	–	–	–
–	–	–	–	–
●	–	–	–	●
–	–	–	–	–
–	–	●	●	–
–	●	–	–	–
–	●	–	–	●
–	–	–	–	–
●	●	●	–	–
–	–	–	–	–
–	●	–	–	–
–	–	–	●	–
IP 68 and IP 69K	IP 68	IP 65, IP 67 and IP 69K		IP 68
Add the suffix TF to the end of the reference (3)				
Add the suffix TT to the end of the reference (3)				
XS9●●RW XSLC	XS1M●●●KP	XS9C2	XS9C4	XS1M18PA
108 and 110	112	114	114	116

Inductive proximity sensors


XS range, general purpose

Cylindrical, standard range, flush mountable

Three-wire DC, solid-state output




XS506B1●●L2




XS508B1●●L2




XS512B1●●M12




XS518B1●●M12



XS518B1●●L2



XS530B1●●L2



XSZB1●●

Sensors, 3-wire 12-24 V, short case model

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 6.5, plain					
1.5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS506B1PAL2	0.035
			M8 connector	XS506B1PAM8	0.025
			M12 connector	XS506B1PAM12	0.025
		NPN	Pre-cabled (L = 2 m) (1)	XS506B1NAL2	0.035
			M8 connector	XS506B1NAM8	0.025
			NC	PNP	Pre-cabled (L = 2 m) (1)
	M8 connector	XS506B1PBM8			0.025
	NPN	Pre-cabled (L = 2 m) (1)		XS506B1NBL2	0.035
		M8 connector	XS506B1NBM8	0.025	
Ø 8, threaded M8 x 1					
1.5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS508B1PAL2	0.035
			M8 connector	XS508B1PAM8	0.025
			M12 connector	XS508B1PAM12	0.025
		NPN	Pre-cabled (L = 2 m) (1)	XS508B1NAL2	0.035
			M8 connector	XS508B1NAM8	0.025
			M12 connector	XS508B1NAM12	0.025
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS508B1PBL2	0.035
			M8 connector	XS508B1PBM8	0.025
			M12 connector	XS508B1PBM12	0.025
		NPN	Pre-cabled (L = 2 m) (1)	XS508B1NBL2	0.035
			M8 connector	XS508B1NBM8	0.025
			M12 connector	XS508B1NBM12	0.025
Ø 12, threaded M12 x 1					
2	NO	PNP	Pre-cabled (L = 2 m) (1)	XS512B1PAL2	0.075
			M12 connector	XS512B1PAM12	0.035
		NPN	Pre-cabled (L = 2 m) (1)	XS512B1NAL2	0.075
			M12 connector	XS512B1NAM12	0.035
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS512B1PBL2	0.075
			M12 connector	XS512B1PBM12	0.035
		NPN	Pre-cabled (L = 2 m) (1)	XS512B1NBL2	0.075
			M12 connector	XS512B1NBM12	0.035
Ø 18, threaded M18 x 1					
5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS518B1PAL2	0.120
			M12 connector	XS518B1PAM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	XS518B1NAL2	0.120
			M12 connector	XS518B1NAM12	0.060
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS518B1PBL2	0.120
			M12 connector	XS518B1PBM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	XS518B1NBL2	0.120
			M12 connector	XS518B1NBM12	0.060
Ø 30, threaded M30 x 1.5					
10	NO	PNP	Pre-cabled (L = 2 m) (1)	XS530B1PAL2	0.205
			M12 connector	XS530B1PAM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS530B1NAL2	0.205
			M12 connector	XS530B1NAM12	0.145
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS530B1PBL2	0.205
			M12 connector	XS530B1PBM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS530B1NBL2	0.205
			M12 connector	XS530B1NBM12	0.145

Accessories (2)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 6.5 (plain)	XSZB165	0.005
	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: XS508B1PAL2 becomes XS508B1PAL5 with a 5 m cable.


(2) For more information, see page 118.

Inductive proximity sensors


XS range, general purpose

Cylindrical, standard range, flush mountable


Three-wire DC, solid-state output



XS500BL00L2



XS500BL00M12



XS530BL00L2

Sensors, 3-wire 12-48 V, long case model

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1					
1.5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS508BLPAL2	0.035
			M12 connector	XS508BLPAM12	0.025
	NPN		Pre-cabled (L = 2 m) (1)	XS508BLNAL2	0.035
			M12 connector	XS508BLNAM12	0.025
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS508BLPBL2	0.035
			M12 connector	XS508BLPBM12	0.025
		NPN	Pre-cabled (L = 2 m) (1)	XS508BLNBL2	0.035
			M12 connector	XS508BLNBM12	0.025

Ø 12, threaded M12 x 1

2	NO	PNP	Pre-cabled (L = 2 m) (1)	XS512BLPAL2	0.075
			M12 connector	XS512BLPAM12	0.035
	NPN		Pre-cabled (L = 2 m) (1)	XS512BLNAL2	0.075
			M12 connector	XS512BLNAM12	0.035
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS512BLPBL2	0.075
			M12 connector	XS512BLPBM12	0.035
		NPN	Pre-cabled (L = 2 m) (1)	XS512BLNBL2	0.075
			M12 connector	XS512BLNBM12	0.035

Ø 18, threaded M18 x 1

5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS518BLPAL2	0.120
			M12 connector	XS518BLPAM12	0.060
	NPN		Pre-cabled (L = 2 m) (1)	XS518BLNAL2	0.120
			M12 connector	XS518BLNAM12	0.060
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS518BLPBL2	0.120
			M12 connector	XS518BLPBM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	XS518BLNBL2	0.120
			M12 connector	XS518BLNBM12	0.060

Ø 30, threaded M30 x 1.5

10	NO	PNP	Pre-cabled (L = 2 m) (1)	XS530BLPAL2	0.205
			M12 connector	XS530BLPAM12	0.145
	NPN		Pre-cabled (L = 2 m) (1)	XS530BLNAL2	0.205
			M12 connector	XS530BLNAM12	0.145
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS530BLPBL2	0.205
			M12 connector	XS530BLPBM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS530BLNBL2	0.205
			M12 connector	XS530BLNBM12	0.145

Accessories (2)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 6.5 (plain)	XSZB165	0.005
	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: XS508BLPAL2 becomes XS508BLPAL5 with a 5 m cable.

(2) For more information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, standard range, flush mountable

Three-wire DC, solid-state output

Characteristics				
Sensor type			XS5●●B1●●M8, XS5●●B1●●M12 XS5●●BL●●M8, XS5●●BL●●M12	XS5●●B1●●L2 XS5●●BL●●L2
Product certifications			UL, CSA, CE, E2	
Connection	Connector		M8 on Ø 6.5 and Ø 8, M12 on Ø 8, Ø 12, Ø 18 and Ø 30	–
	Pre-cabled		–	Length: 2 m
Operating zone	Ø 6.5 and Ø 8	mm	0...1.2	
	Ø 12	mm	0...1.6	
	Ø 18	mm	0...4	
	Ø 30	mm	0...8	
Differential travel		%	1...15 of effective sensing distance (Sr)	
Degree of protection	Conforming to IEC 60529		IP 65 and IP 67	IP 65 and IP 68, double insulation □ (except Ø 6.5 and Ø 8: IP 67)
	Conforming to DIN 40050		IP 69K for Ø 12 to Ø 30	
Storage temperature		°C	-40...+85	
Operating temperature		°C	-25...+70	
Materials	Case		Nickel plated brass (except XS506 and XS508: stainless steel, grade 303)	
	Sensing face		PPS	
	Cable		–	PvR 3 x 0.34 mm² except XS506 and XS508 : 3 x 0.11 mm²
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 50 Hz)	
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms	
Output state indication			Yellow LED: 4 viewing ports at 90°	Yellow LED: annular
Rated supply voltage		V	⎯ 12...48 for XS5●●BL ⎯ 12...24 for XS5●●B1 with protection against reverse polarity	
Voltage limits (including ripple)		V	⎯ 10...58 for XS5●●BL ⎯ 10...36 for XS5●●B1	
Switching capacity		mA	≤ 200 with overload and short-circuit protection	
Voltage drop, closed state		V	≤ 2	
Current consumption, no-load		mA	≤ 10	
Maximum switching frequency	XS506, XS508, XS512	Hz	5000	
	XS518	Hz	2000	
	XS530	Hz	1000	
Delays	First-up	ms	≤ 10	
	Response	ms	≤ 0.1: XS506 , XS508 and XS512 ≤ 0.15: XS518 ≤ 0.3: XS530	
	Recovery	ms	≤ 0.1: XS506 , XS508 and XS512 ≤ 0.35: XS518 ≤ 0.7: XS530	



Inductive proximity sensors

XS range, general purpose

Cylindrical, standard range, flush mountable

Three-wire DC, solid-state output

Wiring schemes

Connector	Pre-cabled	PNP	NPN
M8 	M12 	BU: Blue BN: Brown BK: Black 	


For M8 connector, NO and NC outputs on terminal 4

Setting-up

Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object
Flush mountable sensors			
Ø 6.5	$e \geq 3$	$e \geq 18$	$e \geq 4.5$
Ø 8	$e \geq 3$	$e \geq 18$	$e \geq 4.5$
Ø 12	$e \geq 4$	$e \geq 24$	$e \geq 6$
Ø 18	$e \geq 10$	$e \geq 60$	$e \geq 15$
Ø 30	$e \geq 20$	$e \geq 120$	$e \geq 30$

Dimensions




Sensors		Pre-cabled (mm)		M8 connector (mm)		M12 connector (mm)	
Short case model		a	b	a	b	a	b
Ø 6.5	XS506B1	34	—	42	—	45	—
Ø 8	XS508B1	34	25	42	27	45	23
Ø 12	XS512B1	37	25	—	—	50	30
Ø 18	XS518B1	39	28	—	—	50	28
Ø 30	XS530B1	43	32	—	—	54	32
Sensors		Pre-cabled (mm)		M12 connector (mm)			
Long case model		a	b	a	b		
Ø 8	XS508BL	51	42	61	40		
Ø 12	XS512BL	53	42	61	42		
Ø 18	XS518BL	62	52	74	52		
Ø 30	XS530BL	62	52	74	52		

Inductive proximity sensors


XS range, general purpose

Cylindrical, standard range, flush mountable


Two-wire DC




XS506BS●●L2



XS512BS●●L2



XS500BS●●M12



XSZB1●●

Sensors, 2-wire 12-24 V, short case model

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
Ø 6.5, plain				
1.5	NO terminals 1 & 4 (2)	Pre-cabled (L = 2 m) (1)	XS506BSCAL2	0.035
		Remote M12 connector	XS506BSCAL01M12	0.050
	NC	Pre-cabled (L = 2 m) (1)	XS506BSCBL2	0.035
Ø 8, threaded M8 x 1				
1.5	NO terminals 1 & 4 (2)	Pre-cabled (L = 2 m) (1)	XS508BSCAL2	0.035
		Remote M12 connector	XS508BSCAL01M12	0.050
		Remote M12 connector	XS508BSCAL08M12	0.050
	NC	Pre-cabled (L = 2 m) (1)	XS508BSCBL2	0.035
		Remote M12 connector	XS508BSCBL01M12	0.050
Ø 12, threaded M12 x 1				
2	NO	Pre-cabled (L = 2 m) (1)	XS512BSDAL2	0.075
		M12 connector	XS512BSDAM12	0.035
	NO terminals 1 & 4 (2)	M12 connector	XS512BSCAM12	0.035
		Remote M12 connector	XS512BSCAL08M12	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS512BSDBL2	0.075
		M12 connector	XS512BSDBM12	0.035
Ø 18, threaded M18 x 1				
5	NO	Pre-cabled (L = 2 m) (1)	XS518BSDAL2	0.120
		M12 connector	XS518BSDAM12	0.060
	NO terminals 1 & 4 (2)	M12 connector	XS518BSCAM12	0.060
		Remote M12 connector	XS518BSCAL08M12	0.085
	NC	Pre-cabled (L = 2 m) (1)	XS518BSDBL2	0.120
		M12 connector	XS518BSDBM12	0.060
Ø 30, threaded M30 x 1.5				
10	NO	Pre-cabled (L = 2 m) (1)	XS530BSDAL2	0.205
		M12 connector	XS530BSDAM12	0.145
	NO terminals 1 & 4 (2)	M12 connector	XS530BSCAM12	0.145
		Remote M12 connector	XS530BSCAL08M12	0.170
	NC	Pre-cabled (L = 2 m) (1)	XS530BSDBL2	0.205
		M12 connector	XS530BSDBM12	0.145

Accessories (3)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 6.5 (plain)	XSZB165	0.005
	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: XS508BSCAL2 becomes **XS508BSCAL5** with a 5 m cable.

(2) The NO output is connected to terminals 1 and 4 of the M12 connector.


(3) For more information, see page 118.

Inductive proximity sensors


XS range, general purpose

Cylindrical, standard range, flush mountable


Two-wire DC




XS500B100L2




XS500B100M12




XS500B100L01B (2)



XS500B100L01C



XS500B100L01G



XSZB100

Sensors, 2-wire 12-48 V, long case model

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1				
1.5	NO	Pre-cabled (L = 2 m) (1)	XS508B1DAL2	0.035
		Remote M12 connector	XS508B1DAL08M12	0.050
		M12 connector	XS508B1DAM12	0.025
	NO terminals 1 & 4 (3)	M12 connector	XS508B1CAM12	0.025
		Remote M12 connector	XS508B1CAL08M12	0.050
	NC	Pre-cabled (L = 2 m) (1)	XS508B1DBL2	0.035
		M12 connector	XS508B1DBM12	0.025
Ø 12, threaded M12 x 1				
2	NO	Pre-cabled (L = 2 m) (1)	XS512B1DAL2	0.075
		Remote 7/8" connector	XS512B1DAL08U78	0.050
		M12 connector	XS512B1DAM12	0.035
	NO terminals 1 & 4 (3)	M12 connector	XS512B1CAM12	0.035
		Remote M12 connector	XS512B1CAL08M12	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS512B1DBL2	0.075
		M12 connector	XS512B1DBM12	0.035
		Remote M12 connector	XS512B1DBL08M12	0.060
Ø 18, threaded M18 x 1				
5	NO	Pre-cabled (L = 2 m) (1)	XS518B1DAL2	0.120
		Low temperature version (-40 °C)	XS518B1DAL2TF (5)	0.120
		Remote screw terminal connector (2)	XS518B1DAL01B	0.085
		Remote EN 175301-803-A connector	XS518B1DAL01C	0.085
		Remote M18 connector	XS518B1DAL01G	0.085
	NO terminals 1 & 4 (3)	M12 connector	XS518B1DAM12	0.060
		M12 connector	XS518B1CAM12	0.060
		Remote M12 connector	XS518B1CAL08M12	0.085
	NC	Pre-cabled (L = 2 m) (1)	XS518B1DBL2	0.120
		M12 connector	XS518B1DBM12	0.060
		Remote M12 connector	XS518B1DBL08M12	0.085
		Remote screw terminal connector (2)	XS518B1DBL01B	0.120
Ø 30, threaded M30 x 1.5				
10	NO	Pre-cabled (L = 2 m) (1)	XS530B1DAL2	0.205
		Low temperature version (-40 °C)	XS530B1DAL2TF (5)	0.205
		M12 connector	XS530B1DAM12	0.145
		Remote screw terminal connector (2)	XS530B1DAL01B	0.205
		Remote EN 175301-803-A connector	XS530B1DAL01C	0.205
	NO terminals 1 & 4 (3)	Remote M18 connector	XS530B1DAL01G	0.205
		M12 connector	XS530B1CAM12	0.145
		Remote M12 connector	XS530B1CAL08M12	0.170
	NC	Pre-cabled (L = 2 m) (1)	XS530B1DBL2	0.205
		M12 connector	XS530B1DBM12	0.145
		Remote screw terminal connector (2)	XS530B1DBL01B	0.205

Accessories (4)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: XS508B1DAL2 becomes XS508B1DAL5 with a 5 m cable.

(2) Protective cable gland included with sensor.

(3) The NO output is connected to terminals 1 and 4 of the M12 connector.

(4) For more information, see page 118.

(5) For a 5 m cable replace L2 by L5. Please consult our Customer Care Centre for availability.

Example: XS518B1DAL2TF becomes XS518B1DAL5TF with a 5 m cable.

For a PUR cable, replace the letter L by P in the reference.

Example: XS518B1DAL2TF becomes XS518B1DAP2TF.

For a 5 m PUR cable, replace P2 by P5.

Example: XS518B1DAP2TF becomes XS518B1DAP5TF with a 5 m PUR cable.

Inductive proximity sensors

XS range, general purpose

Cylindrical, standard range, flush mountable

Two-wire DC

Characteristics				
Sensor type			XS5●●B1●●M12, XS5●●BS●●M12	XS5●●B1D●L2, XS5●●BS●●L2
Product certifications			UL, CSA, C€	
Connection	Connector		M12	–
	Pre-cabled		–	Length: 2 m
	Remote connector		M12 (L01M12), screw terminal (L01B), EN 175301-803-A (L01C) and M18 (L01G) remote connectors on 0.15 m flying lead M12 (L08M12) and 7/8" (L08U78) remote connectors on 0.80 m flying lead	
Operating zone	Ø 6.5	mm	0...1.2	
	Ø 8	mm	0...1.2	
	Ø 12	mm	0...1.6	
	Ø 18	mm	0...4	
	Ø 30	mm	0...8	
Differential travel		%	1...15 of effective sensing distance (Sr)	
Degree of protection	Conforming to IEC 60529		IP 65 and IP 67	IP 65 and IP 68, double insulation ☐ (except Ø 6.5 and Ø 8: IP 67)
Storage temperature		°C	-40...+85	
Operating temperature		°C	-25...+70; TF products: -40...+70	
Materials	Case		Nickel plated brass (except XS506 and XS508B1: stainless steel, grade 303)	
	Sensing face		PPS	
	Cable		–	PvR 2 x 0.34 mm² (except XS506 and XS508: 2 x 0.11 mm²) PUR available (1)
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms	
Output state indication			Yellow LED: 4 viewing ports at 90°	Yellow LED: annular
Rated supply voltage		V	⎓ 12...48 non polarised for XS5●●B1● ⎓ 12...24 non polarised for XS5●●BS (except Ø 6.5 short and Ø 8 short: polarised) with protection against reverse polarity	
Voltage limits (including ripple)		V	⎓ 10...58 for XS5●●B1● ⎓ 10...36 for XS5●●BS	
Switching capacity		mA	1.5...100 with overload and short-circuit protection	
Voltage drop, closed state		V	≤ 4.2	
Residual current, open state		mA	≤ 0.5	
Maximum switching frequency	XS506, XS508	Hz	1000 for XS5●●BS, 1400 for XS5●●B1●	
	XS512	Hz	1000	
	XS518	Hz	1200	
	XS530	Hz	1300	
Delays	First-up	ms	≤ 10	
	Response	ms	≤ 0.5: XS506, XS508 and XS512 ≤ 0.6: XS518 ≤ 0.6: XS530	
	Recovery	ms	≤ 0.2 (except XS530 ≤ 0.4)	

(1) For PUR cable, replace the letter L in the reference by P. Example: XS506BSCAL2 becomes XS506BSCAP2 with a PUR cable.

Inductive proximity sensors

XS range, general purpose

Cylindrical, standard range, flush mountable

Two-wire DC

Wiring schemes


Connector	Pre-cabled	2-wire  non polarised		
M12 	BU: Blue BN: Brown	NO output		NC output
		XS5...BxDA...	XS5...B1CA...	XS5...BxDB...
2-wire  polarised				
		NO output		NC output
		XS5...BSCA...		XS5...BSCB...

Remote connectors L01B, L01C, L01G, U78

Screw terminal (L01B)


The terminal numbering differs according to the version (2-wire ---, 3-wire ---, 2-wire ~).

EN 175301-803-A (L01C)




The NO or NC outputs are connected to terminal 2.

M18 (L01G)




7/8" (U78)



Terminal 1: not connected
Terminal 2: +/-
Terminal 3: +/-


Setting-up

Minimum mounting distances (mm)




Side by side

Ø 6.5	$e \geq 3$
Ø 8	$e \geq 3$
Ø 12	$e \geq 4$
Ø 18	$e \geq 10$
Ø 30	$e \geq 20$



Face to face


$e \geq 18$
$e \geq 18$
$e \geq 24$
$e \geq 60$
$e \geq 120$



Facing a metal object

$e \geq 4.5$
$e \geq 4.5$
$e \geq 6$
$e \geq 15$
$e \geq 30$

Dimensions



(1) LED


Sensors		Pre-cabled (mm)		M8 connector (mm)		M12 connector (mm)	
Short case model		a	b	a	b	a	b
Ø 6.5	XS506BS	33	—	42	—	45	—
Ø 8	XS508BS	33	25	42	26	45	24
Ø 12	XS512BS	35	25	—	—	50	30
Ø 18	XS518BS	40	28	—	—	50	28
Ø 30	XS530BS	44	32	—	—	55	32
Sensors		Pre-cabled (mm)		M12 connector (mm)			
Long case model		a	b	a	b		
Ø 8	XS508B1	51	42	62	40		
Ø 12	XS512B1	54	42	61	42		
Ø 18	XS518B1	56	44	64	44		
Ø 30	XS530B1	54	42	72	41		

Inductive proximity sensors


XS range, general purpose

Cylindrical, standard range, flush mountable


Two-wire AC or DC ⁽¹⁾




XS5●●B1M●L2



XS5●●B1M●U20



XS530B1●●L2



XSZB1●●

Sensors, 2-wire $\approx$ 24-240 V, long case model

Ø 12, threaded M12 x 1

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
2	NO	Pre-cabled (L = 2 m) (2)	XS512B1MAL2	0.075
		1/2"-20 UNF connector	XS512B1MAU20	0.025
	NC	Pre-cabled (L = 2 m) (2)	XS512B1MBL2	0.075
		1/2"-20 UNF connector	XS512B1MBU20	0.025

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
5	NO	Pre-cabled (L = 2 m) (2)	XS518B1MAL2	0.100
		1/2"-20 UNF connector	XS518B1MAU20	0.060
	NC	Pre-cabled (L = 2 m) (2)	XS518B1MBL2	0.100
		1/2"-20 UNF connector	XS518B1MBU20	0.060

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
10	NO	Pre-cabled (L = 2 m) (2)	XS530B1MAL2	0.205
		1/2"-20 UNF connector	XS530B1MAU20	0.145
	NC	Pre-cabled (L = 2 m) (2)	XS530B1MBL2	0.205
		1/2"-20 UNF connector	XS530B1MBU20	0.145

Accessories ⁽³⁾

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) Ø8 plastic, double insulation version available (see page 64).

(2) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: **XS512B1MAL2** becomes **XS512B1MAL5** with a 5 m cable.

(3) For more information, see page 118.

Inductive proximity sensors

XS range, general purpose


Cylindrical, standard range, flush mountable

Two-wire AC or DC

Characteristics				
Sensor type		XS5...B1M...U20		XS5...B1M...L2
Product certifications		UL, CSA, CÉ		
Connection	Connector	1/2"-20 UNF		
	Pre-cabled	—		Length: 2 m
Operating zone	Ø 12	mm	0...1.6	
	Ø 18	mm	0...4	
	Ø 30	mm	0...8	
Differential travel		%	1...15 of effective sensing distance (Sr)	
Degree of protection	Conforming to IEC 60529		IP 65 and IP 67	IP 65 and IP 68, double insulation □
	Conforming to DIN 40050		IP 69K	
Storage temperature		°C	-40...+85	
Operating temperature		°C	-25...+70	
Materials	Case		Nickel plated brass	
	Sensing face		PPS	
	Cable		—	PvR 2 x 0.34 mm ²
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms	
Output state indication			Yellow LED: 4 viewing ports at 90°	Yellow LED: annular
Rated supply voltage		V	~ or — 24...240 (~ 50/60 Hz)	
Voltage limits (including ripple)		V	~ or — 20...264	
Switching capacity	XS512B1M...	mA	5...200 (1)	
	XS518B1M..., XS530B1M...	mA	~ 5...300 or — 5...200 (1)	
Voltage drop, closed state		V	≤ 5.5	
Residual current, open state		mA	≤ 0.8	
Maximum switching frequency	XS512B1..., XS518B1M...	Hz	~ 25 or — 1000	
	XS530B1M...	Hz	~ 25 or — 500	
Delays	First-up	ms	≤ 20 XS512B1M... ≤ 25 XS518B1M... and XS530B1M...	
	Response	ms	≤ 0.5	
	Recovery	ms	≤ 0.2 XS512B1M... ≤ 0.5 XS518B1M... ≤ 2 XS518B1M...	

(1) It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Wiring schemes

Connector	Pre-cabled	2-wire ~ or — NO or NC output
1/2"-20 UNF	BU: Blue BN: Brown	
		
		⊕: on connector models only


Setting-up

Minimum mounting distances (mm)

Sensor	Side by side	Face to face	Facing a metal object
Ø 12	e ≥ 8	e ≥ 48	e ≥ 12
Ø 18	e ≥ 16	e ≥ 100	e ≥ 25
Ø 30	e ≥ 30	e ≥ 180	e ≥ 45

Dimensions

Sensor	XS6		Connector (mm)	
	Pre-cabled (mm)		a	b
XS512B1M	53	42	62	42
XS518B1M	62	52	73	52
XS530B1M	62	52	73	52




(1) LED

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, flush mountable


Three-wire DC, solid-state output



XS106B3●●L2



XS108B3●●M8



XS112B3●●L2

Sensors, 3-wire 12-24 V, short case model

Sensing distance (Sn) mm	Function	Output	Connection	Sold in lots of	Unit reference	Weight kg
Ø 6.5, plain						
2.5	NO	PNP	Pre-cabled (L = 2 m) (1)	1	XS106B3PAL2	0.060
			M8 connector	1	XS106B3PAM8	0.030
			M12 connector	1	XS106B3PAM12	0.050
			Pre-cabled (L = 2 m)	20	XS106B3PAL2TQ	0.980
			M8 connector	20	XS106B3PAM8TQ	0.320
			Pre-cabled (L = 2 m)	1	XS106B3NAL2	0.060
	NC	PNP	M8 connector	1	XS106B3NAM8	0.030
			Pre-cabled (L = 2 m) (1)	1	XS106B3PBL2	0.060
			M8 connector	1	XS106B3PBM8	0.030
		NPN	Pre-cabled (L = 2 m) (1)	1	XS106B3NBL2	0.060
			M8 connector	1	XS106B3NBM8	0.030
			Pre-cabled (L = 2 m) (1)	1	XS106B3PAL2	0.070
2.5	NO	PNP	M8 connector	1	XS108B3PAM8	0.030
			M12 connector	1	XS108B3PAM12	0.060
			Pre-cabled (L = 2 m)	20	XS108B3PAL2TQ	1.120
			M8 connector	20	XS108B3PAM8TQ	0.460
			M12 connector	20	XS108B3PAM12TQ	0.940
		NPN	Pre-cabled (L = 2 m) (1)	1	XS108B3NAL2	0.070
			M8 connector	1	XS108B3NAM8	0.030
			M12 connector	1	XS108B3NAM12	0.060
			Pre-cabled (L = 2 m)	20	XS108B3NAL2TQ	1.120
			M8 connector	20	XS108B3NAM8TQ	0.460
	NC	PNP	Pre-cabled (L = 2 m) (1)	1	XS108B3PBL2	0.070
			M8 connector	1	XS108B3PBM8	0.030
			M12 connector	1	XS108B3PBM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	1	XS108B3NBL2	0.070
			M8 connector	1	XS108B3NBM8	0.030
			M12 connector	1	XS108B3NBM12	0.060
4	NO	PNP	Pre-cabled (L = 2 m) (1)	1	XS112B3PAL2	0.090
			M12 connector	1	XS112B3PAM12	0.030
			Pre-cabled (L = 2 m)	20	XS112B3PAL2TQ	1.600
			M12 connector	20	XS112B3PAM12TQ	0.470
		NPN	Pre-cabled (L = 2 m) (1)	1	XS112B3NAL2	0.090
			M12 connector	1	XS112B3NAM12	0.030
			Pre-cabled (L = 2 m)	20	XS112B3NAL2TQ	1.600
			M12 connector	20	XS112B3NAM12TQ	0.470
	NC	PNP	Pre-cabled (L = 2 m) (1)	1	XS112B3PBL2	0.090
			M12 connector	1	XS112B3PBM12	0.030
			M12 connector	20	XS112B3PBM12TQ	0.470
		NPN	Pre-cabled (L = 2 m) (1)	1	XS112B3NBL2	0.090
			M12 connector	1	XS112B3NBM12	0.030
			M12 connector	1	XS112B3NBM12	0.030

(1) For a 5 m long cable replace L2 by L5. Please consult our Customer Care Centre for availability.


Example: XS106B3PAL2 becomes XS106B3PAL5 with a 5 m cable.

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, flush mountable


Three-wire DC, solid-state output




XS118B3●●M12



XS118B3●●L2



XS130B3●●L2



XSZB1●●

Sensors, 3-wire 12-24 V, short case model (continued)

Sensing distance (Sn) mm	Function	Output	Connection	Sold in lots of	Unit reference	Weight kg
Ø 18, threaded M18 x 1						
8	NO	PNP	Pre-cabled (L = 2 m) (1)	1	XS118B3PAL2	0.110
			M12 connector	1	XS118B3PAM12	0.060
			Pre-cabled (L = 2 m)	20	XS118B3PAL2TQ	2.000
			M12 connector	20	XS118B3PAM12TQ	1.140
	NPN	NPN	Pre-cabled (L = 2 m) (1)	1	XS118B3NAL2	0.110
			M12 connector	1	XS118B3NAM12	0.060
			Pre-cabled (L = 2 m)	20	XS118B3NAL2TQ	2.000
			M12 connector	20	XS118B3NAM12TQ	1.140
	NC	PNP	Pre-cabled (L = 2 m) (1)	1	XS118B3PBL2	0.110
			M12 connector	1	XS118B3PBM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	1	XS118B3NBL2	0.110
			M12 connector	1	XS118B3NBM12	0.060

Ø 30, threaded M30 x 1.5

15	NO	PNP	Pre-cabled (L = 2 m) (1)	1	XS130B3PAL2	0.180
			M12 connector	1	XS130B3PAM12	0.130
			Pre-cabled (L = 2 m)	20	XS130B3PAL2TQ	3.360
			M12 connector	20	XS130B3PAM12TQ	2.000
	NPN	NPN	Pre-cabled (L = 2 m) (1)	1	XS130B3NAL2	0.180
			M12 connector	1	XS130B3NAM12	0.130
			Pre-cabled (L = 2 m)	20	XS130B3NAL2TQ	2.000
			M12 connector	20	XS130B3NAM12TQ	2.000
	NC	PNP	Pre-cabled (L = 2 m) (1)	1	XS130B3PBL2	0.180
			M12 connector	1	XS130B3PBM12	0.130
		NPN	Pre-cabled (L = 2 m) (1)	1	XS130B3NBL2	0.180
			M12 connector	1	XS130B3NBM12	0.130

Accessories (2)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 6.5 (plain)	XSZB165	0.005
	Ø 8 (M8 x1)	XSZB108	0.006
	Ø 12 (M12 x1)	XSZB112	0.006
	Ø 18 (M18 x1)	XSZB118	0.010
	Ø 30 (M30 x 1.5)	XSZB130	0.020

(1) For a 5 m cable, replace L2 by L5. Please consult our Customer Care Centre for availability.
Example: XS118B3PAL2 becomes **XS118B3PAL5** with a 5 m cable.


(2) For more information, see page 118.

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, flush mountable


Three-wire DC, solid-state output




XS600B100L2




XS600B100M12




XS600B100L01B (2)



XS600B100L01C



XS600B100L01G



XSZB000

Sensors, 3-wire 12-48 V, long case model

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1					
2.5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS608B1PAL2	0.035
			M8 connector	XS608B1PAM8	0.015
			M12 connector	XS608B1PAM12	0.015
		NPN	Pre-cabled (L = 2 m) (1)	XS608B1NAL2	0.035
			M8 connector	XS608B1NAM8	0.015
			M12 connector	XS608B1NAM12	0.015
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS608B1PBL2	0.035
			M8 connector	XS608B1PBM8	0.015
			M12 connector	XS608B1PBM12	0.015
		NPN	Pre-cabled (L = 2 m) (1)	XS608B1NBL2	0.035
			M8 connector	XS608B1NBM8	0.015
			M12 connector	XS608B1NBM12	0.015
Ø 12, threaded M12 x 1					
4	NO	PNP	Pre-cabled (L = 2 m) (1)	XS612B1PAL2	0.075
			M12 connector	XS612B1PAM12	0.020
			M12 connector	XS612B1NAM12	0.020
		NPN	Pre-cabled (L = 2 m) (1)	XS612B1NAL2	0.075
			M12 connector	XS612B1NAM12	0.020
			M12 connector	XS612B1NAM12	0.020
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS612B1PBL2	0.075
			M12 connector	XS612B1PBM12	0.020
			M12 connector	XS612B1PBM12	0.020
		NPN	Pre-cabled (L = 2 m) (1)	XS612B1NBL2	0.075
			M12 connector	XS612B1NBM12	0.020
			M12 connector	XS612B1NBM12	0.020
Ø 18, threaded M18 x 1					
8	NO	PNP	Pre-cabled (L = 2 m) (1)	XS618B1PAL2	0.100
			M12 connector	XS618B1PAM12	0.040
			Remote screw terminal connector	XS618B1PAL01B (2)	0.100
			Remote EN 175301-803-A connector	XS618B1PAL01C	0.100
			Remote M18 connector	XS618B1PAL01G	0.100
			M12 connector	XS618B1NAM12	0.040
		NPN	Pre-cabled (L = 2 m) (1)	XS618B1NAL2	0.100
			M12 connector	XS618B1NAM12	0.040
			Remote screw terminal connector	XS618B1NAL01B (2)	0.100
			M12 connector	XS618B1NAM12	0.040
			Remote screw terminal connector	XS618B1PBL01B (2)	0.100
			M12 connector	XS618B1PBM12	0.040
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS618B1PBL2	0.100
			M12 connector	XS618B1PBM12	0.040
			Remote screw terminal connector	XS618B1PBL01B (2)	0.100
			M12 connector	XS618B1PBM12	0.040
			Remote screw terminal connector	XS618B1PBL01B (2)	0.100
			M12 connector	XS618B1PBM12	0.040
		NPN	Pre-cabled (L = 2 m) (1)	XS618B1NBL2	0.100
			M12 connector	XS618B1NBM12	0.040
			Remote screw terminal connector	XS618B1NBL01B (2)	0.100
			M12 connector	XS618B1NBM12	0.040
			Remote screw terminal connector	XS618B1NBL01B (2)	0.100
			M12 connector	XS618B1NBM12	0.040
Ø 30, threaded M30 x 1.5					
15	NO	PNP	Pre-cabled (L = 2 m) (1)	XS630B1PAL2	0.205
			M12 connector	XS630B1PAM12	0.145
			Remote screw terminal connector	XS630B1PAL01B (2)	0.205
			Remote EN 175301-803-A connector	XS630B1PAL01C	0.205
			Remote M18 connector	XS630B1PAL01G	0.205
			M12 connector	XS630B1NAM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS630B1NAL2	0.205
			M12 connector	XS630B1NAM12	0.145
			Remote screw terminal connector	XS630B1NAL01B (2)	0.205
			M12 connector	XS630B1NAM12	0.145
			Remote screw terminal connector	XS630B1PBL01B (2)	0.205
			M12 connector	XS630B1PBM12	0.145
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS630B1PBL2	0.205
			M12 connector	XS630B1PBM12	0.145
			Remote EN 175301-803-A connector	XS630B1PBL01C	0.205
			M12 connector	XS630B1PBM12	0.145
			Remote EN 175301-803-A connector	XS630B1PBL01C	0.205
			M12 connector	XS630B1PBM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS630B1NBL2	0.205
			M12 connector	XS630B1NBM12	0.145
			Remote EN 175301-803-A connector	XS630B1NBL01B (2)	0.205
			M12 connector	XS630B1NBM12	0.145
			Remote EN 175301-803-A connector	XS630B1NBL01B (2)	0.205
			M12 connector	XS630B1NBM12	0.145

Accessories (3)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: XS608B1PAL2 becomes XS608B1PAL5 with a 5 m cable.

(2) Protective cable gland included with sensor.

(3) For more information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, increased range, flush mountable


Three-wire DC, solid-state output

Characteristics			
Sensor type		XS1/XS6...B...M8	XS1/XS6...B...M12
Product certifications		UL, CSA, CE, E2	
Connection	Connector	M8	M12
	Pre-cabled	—	—
	Remote connector	Screw terminal (L01B), EN 175301-803-A (L01C) and M18 (L01G) remote connectors on 0.15 m flying lead	
Operating zone (1)	Ø 6.5 and Ø 8	mm	0...2
	Ø 12	mm	0...3.2
	Ø 18	mm	0...6.4
	Ø 30	mm	0...12
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 65 and IP 67	
	Conforming to DIN 40050	IP 69K	
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Nickel plated brass (except Ø 6.5 and Ø 8: stainless steel, grade 303)	
	Sensing face	PPS	
	Cable	—	
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED, 4 viewing ports at 90°	
Rated supply voltage		V	XS1: 12...24 with protection against reverse polarity XS6: 12...48 with protection against reverse polarity
Voltage limits (including ripple)		V	XS1: 10...36; XS6: 10...58
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	Ø 6.5, Ø 8 and Ø 12	Hz	2500
	Ø 18	Hz	1000
	Ø 30	Hz	500
Delays	First-up	ms	≤ 10
	Response	ms	≤ 0.2 for Ø 6.5, Ø 8 and Ø 12, ≤ 0.3 for Ø 18, ≤ 0.6 for Ø 30
	Recovery	ms	≤ 0.2 for Ø 6.5, Ø 8 and Ø 12, ≤ 0.7 for Ø 18, ≤ 1.4 for Ø 30

(1) Detection curves, see page 122.

Wiring schemes


Connector (1)




Pre-cabled

BU: Blue
BN: Brown
BK: Black

PNP




NPN



For M8 connector, NO and NC outputs on terminal 4

Setting-up


Minimum mounting distances (mm)



Sensors	Side by side	Face to face	Facing a metal object
Ø 6.5	e ≥ 5	e ≥ 30	e ≥ 8
Ø 8	e ≥ 5	e ≥ 30	e ≥ 8
Ø 12	e ≥ 8	e ≥ 48	e ≥ 12
Ø 18	e ≥ 16	e ≥ 100	e ≥ 25
Ø 30	e ≥ 30	e ≥ 180	e ≥ 45

(1) For pin arrangement of remote connectors L01B, L01C and L01G, see page 29.

Dimensions



(1) LED


Sensors		Pre-cabled (mm)		M8 connector (mm)		M12 connector (mm)	
Short case model		a	b	a	b	a	b
Ø 6.5	XS106B3	34	—	42	—	45	—
Ø 8	XS108B3	34	25	42	27	45	23
Ø 12	XS112B3	35	25	—	—	50	30
Ø 18	XS118B3	39	28	—	—	50	28
Ø 30	XS130B3	43	32	—	—	55	32
Sensors		Pre-cabled (mm)		M8 connector (mm)		M12 connector (mm)	
Long case model		a	b	a	b	a	b
Ø 8	XS608B1	51	42	58	43	61	40
Ø 12	XS612B1	53	42	—	—	61	42
Ø 18	XS618B1	62	52	—	—	74	52
Ø 30	XS630B1	62	52	—	—	74	52

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, flush mountable


Two-wire DC, solid-state output




XS606B3●●L2




XS612B3●●L2



XS6●●B1●●L2



XS6●●B1●●M12



XSZB1●●

Sensors, 2-wire 12-24 V, short case model

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
Ø 6.5, plain				
2.5	NO	Pre-cabled (L = 2 m) (1)	XS606B3CAL2	0.060
		Remote M12 connector	XS606B3CAL01M12	0.070
	NC	Pre-cabled (L = 2 m) (1)	XS606B3CBL2	0.060
Ø 8, threaded M8 x 1				
2.5	NO	Pre-cabled (L = 2 m) (1)	XS608B3CAL2	0.070
		Remote M12 connector	XS608B3CAL01M12	0.070
	NC	Pre-cabled (L = 2 m) (1)	XS608B3CBL2	0.070
		Remote M12 connector	XS608B3CBL01M12	0.070
Ø 12, threaded M12 x 1				
4	NO	Pre-cabled (L = 2 m) (1)	XS612B3DAL2	0.090
		M12 connector	XS612B3DAM12	0.030
	NC	Pre-cabled (L = 2 m) (1)	XS612B3DBL2	0.090
		M12 connector	XS612B3DBM12	0.030
Ø 18, threaded M18 x 1				
8	NO	Pre-cabled (L = 2 m) (1)	XS618B3DAL2	0.110
		M12 connector	XS618B3DAM12	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS618B3DBL2	0.110
		M12 connector	XS618B3DBM12	0.060
Ø 30, threaded M30 x 1.5				
15	NO	Pre-cabled (L = 2 m) (1)	XS630B3DAL2	0.180
		M12 connector	XS630B3DAM12	0.130
	NC	Pre-cabled (L = 2 m) (1)	XS630B3DBL2	0.180
		M12 connector	XS630B3DBM12	0.180

Sensors, 2-wire 12-48 V, long case model

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
Ø 6.5, plain				
2.5	NO	Pre-cabled (L = 2 m) (1)	XS606B1DAL2	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS606B1DBL2	0.060
Ø 8, threaded M8 x 1				
2.5	NO	Pre-cabled (L = 2 m) (1)	XS608B1DAL2	0.035
		M12 connector	XS608B1DAM12	0.015
	NC	Pre-cabled (L = 2 m) (1)	XS608B1DBL2	0.035
		M12 connector	XS608B1DBM12	0.015
Ø 12, threaded M12 x 1				
4	NO	Pre-cabled (L = 2 m) (1)	XS612B1DAL2	0.180
		M12 connector	XS612B1DAM12	0.020
	NC	Pre-cabled (L = 2 m) (1)	XS612B1DBL2	0.075
		M12 connector	XS612B1DBM12	0.020
Ø 18, threaded M18 x 1				
8	NO	Pre-cabled (L = 2 m) (1)	XS618B1DAL2	0.100
		M12 connector	XS618B1DAM12	0.040
	NC	Pre-cabled (L = 2 m) (1)	XS618B1DBL2	0.100
		M12 connector	XS618B1DBM12	0.040
Ø 30, threaded M30 x 1.5				
15	NO	Pre-cabled (L = 2 m) (1)	XS630B1DAL2	0.205
		M12 connector	XS630B1DAM12	0.145
	NC	Pre-cabled (L = 2 m) (1)	XS630B1DBL2	0.205
		M12 connector	XS630B1DBM12	0.145

Accessories (2)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 6.5 (plain)	XSZB165	0.005
	Ø 8 (M8 x1)	XSZB108	0.006
	Ø 12 (M12 x1)	XSZB112	0.006
	Ø 18 (M18 x1)	XSZB118	0.010
	Ø 30 (M30 x 1.5)	XSZB130	0.020

(1) For a 5 m cable, replace L2 by L5. Please consult our Customer Care Centre for availability.
Example: XS606B3CAL2 becomes XS606B3CAL5 with a 5 m cable.

(2) For more information, see page 118.

Inductive proximity sensors






XS range, general purpose


Cylindrical, increased range, flush mountable

Two-wire DC, solid-state output

Characteristics			
Sensor type		XS6...B3...M12 XS6...B1D...M12	XS6...B3...L2 XS6...B1D...L2
Product certifications		UL, CSA, CE	
Connection	Connector	M12 or remote M12 connector (L01M12) on 0.15 m flying lead	
	Pre-cabled	Length 2 m	
Operating zone (1)	Ø 6.5 and Ø 8	mm	0...2
	Ø 12	mm	0...3.2
	Ø 18	mm	0...6.4
	Ø 30	mm	0...12
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 65 and IP 67	
	Conforming to DIN 40050	IP 69K	
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Nickel plated brass (except XS606B1D or XS608B1D: stainless steel, grade 303)	
	Sensing face	PPS	
	Cable	PvR 2 x 0.34 mm ² except Ø 6.5 and Ø 8: 2 x 0.11 mm ²	
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED, 4 viewing ports at 90°	
Rated supply voltage		V --- 12...48 non polarised for XS6...B1D --- 12...24 non polarised for XS6...B3... (except Ø 6.5 short and Ø 8 short: polarised), with protection against reverse polarity	
Voltage limits (including ripple)		V --- 10...58 for XS6...B1D --- 10...36 for XS6...B3...	
Switching capacity		mA ≤ 100 with overload and short-circuit protection	
Voltage drop, closed state		V ≤ 4.2	
Residual current, open state		mA ≤ 0.5 mA	
Maximum switching frequency	Ø 6.5, Ø 8	Hz	1400 for XS6...B1D, 1100 for XS6...B3...
	Ø 12	Hz	1300
	Ø 18	Hz	1500
	Ø 30	Hz	800
Delays	First-up	ms	≤ 10
	Response	ms	≤ 0.5
	Recovery	ms	≤ 0.2 for Ø 6.5, Ø 8 and Ø 12; 0.3 for Ø 18; 0.6 for Ø 30

(1) Detection curves, see page 122.

Wiring schemes		Setting-up																									
M12 connector		Pre-cabled																									
		BU: Blue BN: Brown																									
2-wire --- non polarised		Minimum mounting distances (mm)																									
NO output																											
		<table> <tr> <th>Sensors</th><th>Side by side</th><th>Face to face</th><th>Facing a metal object</th></tr> <tr> <td>Ø 6.5</td><td>e ≥ 5</td><td>e ≥ 30</td><td>e ≥ 8</td></tr> <tr> <td>Ø 8</td><td>e ≥ 5</td><td>e ≥ 30</td><td>e ≥ 8</td></tr> <tr> <td>Ø 12</td><td>e ≥ 8</td><td>e ≥ 48</td><td>e ≥ 12</td></tr> <tr> <td>Ø 18</td><td>e ≥ 16</td><td>e ≥ 100</td><td>e ≥ 25</td></tr> <tr> <td>Ø 30</td><td>e ≥ 30</td><td>e ≥ 180</td><td>e ≥ 45</td></tr> </table>		Sensors	Side by side	Face to face	Facing a metal object	Ø 6.5	e ≥ 5	e ≥ 30	e ≥ 8	Ø 8	e ≥ 5	e ≥ 30	e ≥ 8	Ø 12	e ≥ 8	e ≥ 48	e ≥ 12	Ø 18	e ≥ 16	e ≥ 100	e ≥ 25	Ø 30	e ≥ 30	e ≥ 180	e ≥ 45
Sensors	Side by side	Face to face	Facing a metal object																								
Ø 6.5	e ≥ 5	e ≥ 30	e ≥ 8																								
Ø 8	e ≥ 5	e ≥ 30	e ≥ 8																								
Ø 12	e ≥ 8	e ≥ 48	e ≥ 12																								
Ø 18	e ≥ 16	e ≥ 100	e ≥ 25																								
Ø 30	e ≥ 30	e ≥ 180	e ≥ 45																								
NC output																											
																											
2-wire --- polarised																											
XS6...B3CA		XS6...B3CB																									
																											


Dimensions					
		Sensors		Pre-cabled (mm)	
		Short case model		a	b
(1) LED	Ø 6.5	XS606B3C	33	—	—
	Ø 8	XS608B3C	33	25	—
	Ø 12	XS612B3D	35	25	50
	Ø 18	XS618B3D	40	28	50
	Ø 30	XS630B3D	44	32	55
		Long case model		a	b
	Ø 6.5	XS606B1D	50	—	—
	Ø 8	XS608B1D	51	42	62
	Ø 12	XS612B1D	53	42	61
	Ø 18	XS618B1D	62	52	74
	Ø 30	XS630B1D	62	52	74

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, flush mountable


Two-wire AC or DC ⁽¹⁾




XS6...B1M...L2




XS6...B1...U20




XS6...B1...L01B (3)



XS6...B1...L01C



XS6...B1...L01G



XSZB1...

Sensors, 2-wire $\approx$ 24-240 V, long case model

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
Ø 12, threaded M12 x 1				
4	NO	Pre-cabled (L = 2 m) (2)	XS612B1MAL2	0.075
		1/2"-20 UNF connector	XS612B1MAU20	0.025
	NC	Pre-cabled (L = 2 m) (2)	XS612B1MBL2	0.075
		1/2"-20 UNF connector	XS612B1MBU20	0.025

Ø 18, threaded M18 x 1				
8	NO	Pre-cabled (L = 2 m) (2)	XS618B1MAL2	0.100
		1/2"-20 UNF connector	XS618B1MAU20	0.060
		Remote screw terminal connector	XS618B1MAL01B (3)	0.100
		Remote EN 175301-803-A connector	XS618B1MAL01C	0.100
		Remote M18 connector	XS618B1MAL01G	0.100
	NC	Pre-cabled (L = 2 m) (2)	XS618B1MBL2	0.100
		1/2"-20 UNF connector	XS618B1MBU20	0.060
		Remote screw terminal connector	XS618B1MBL01B (3)	0.100
		Remote EN 175301-803-A connector	XS618B1MBL01C	0.100
		Remote M18 connector	XS618B1MBL01G	0.100

Ø 30, threaded M30 x 1.5				
15	NO	Pre-cabled (L = 2 m) (2)	XS630B1MAL2	0.205
		1/2"-20 UNF connector	XS630B1MAU20	0.145
		Remote screw terminal connector	XS630B1MAL01B (3)	0.205
		Remote EN 175301-803-A connector	XS630B1MAL01C	0.205
		Remote M18 connector	XS630B1MAL01G	0.205
	NC	Pre-cabled (L = 2 m) (2)	XS630B1MBL2	0.205
		1/2"-20 UNF connector	XS630B1MBU20	0.145
		Remote screw terminal connector	XS630B1MBL01B (3)	0.205
		Remote EN 175301-803-A connector	XS630B1MBL01C	0.205

Accessories (4)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) Ø8 plastic, double insulation version available (see page 64).

(2) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10. Please consult our Customer Care Centre for availability.

Example: XS612B1MAL2 becomes **XS612B1MAL5** with a 5 m cable.

(3) Protective cable gland included with sensor.

(4) For more information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, increased range, flush mountable


Two-wire AC or DC

Characteristics			
Sensor type		XS6...B1M●U20	XS6...B1M●L●
Product certifications		UL, CSA, CÉ	
Connection	Connector	1/2" - 20 UNF	—
	Pre-cabled	—	Length 2 m
	Remote connector	Screw terminal (L01B), EN 175301-803-A (L01C) and M18 (L01G) remote connectors on 0.15 m flying lead	
Operating zone (1)	Ø 12	mm	0... 3.2
	Ø 18	mm	0... 6.4
	Ø 30	mm	0...12
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 65, IP 67	
	Conforming to DIN 40050	IP 69K	
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Nickel plated brass	
	Sensing face	PPS	
	Cable	PvR 2 x 0.34 mm ²	
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED: annular on pre-cabled version Yellow LED with 4 viewing ports at 90° on connector version	
Rated supply voltage		V	≈ 24...240 (~ 50/60 Hz)
Voltage limits (including ripple)		V	≈ 20...264
Switching capacity	XS612B1M●●●	mA	5...200 (2)
	XS618B1M●●●	mA	~ 5...300 or ~ 5...200 (2)
	XS630B1M●●●	mA	~ 5...300 or ~ 5...200 (2)
Voltage drop, closed state		V	≤ 5.5
Residual current, open state		mA	≤ 0.8
Maximum switching frequency (DC/AC)	Ø 12	Hz	~ 1000 / ~ 25
	Ø 18	Hz	~ 1000 / ~ 25
	Ø 30	Hz	~ 500 / ~ 25
Delays	First-up	ms	≤ 25 for Ø 18 and Ø 30; ≤ 20 for Ø 12
	Response	ms	≤ 0.5
	Recovery	ms	≤ 0.2 for Ø 12; ≤ 0.5 for Ø 18; ≤ 2 for Ø 30

(1) Detection curves, see page 122.

(2) It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Wiring schemes




Connector (1)	Pre-cabled	2-wire ~ or --- NO or NC output
1/2"-20 UNF 	BU: Blue BN: Brown	

±: on 1/2"-20UNF connector models only

(1) For pin arrangement of remote connectors L01B, L01C and L01G, see page 29.


Setting-up

Minimum mounting distances (mm)



Sensors	Side by side	Face to face	Facing a metal object
Ø 12	e ≥ 8	e ≥ 48	e ≥ 12
Ø 18	e ≥ 16	e ≥ 100	e ≥ 25
Ø 30	e ≥ 30	e ≥ 180	e ≥ 45

Dimensions



Sensors		Pre-cabled (mm)		Connector (mm)	
		a	b	a	b
Ø 12	XS612B1M●	53	42	61	42
Ø 18	XS618B1M●	62	52	73	52
Ø 30	XS630B1M●	62	52	73	52


(1) LED

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, non flush mountable


Three-wire DC, solid-state output




XS612B4●●L2



XS618B4●●M12



XS630B5●●M12



XSZB●●●

Sensors, 3-wire 12...48 V, long case model

Ø 8, threaded M8 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
4	NO	PNP	Pre-cabled (L = 2 m)	XS608B4PAL2	0.035
			M8 connector	XS608B4PAM8	0.015
			M12 connector	XS608B4PAM12	0.015
		NPN	Pre-cabled (L = 2 m)	XS608B4NAL2	0.035
			M8 connector	XS608B4NAM8	0.015
			M12 connector	XS608B4NAM12	0.015
	NC	PNP	Pre-cabled (L = 2 m)	XS608B4PBL2	0.035
			M8 connector	XS608B4PBM8	0.015
			M12 connector	XS608B4PBM12	0.015
		NPN	Pre-cabled (L = 2 m)	XS608B4NBL2	0.035
			M8 connector	XS608B4NBM8	0.015
			M12 connector	XS608B4NBM12	0.015

Ø 12, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
7	NO	PNP	Pre-cabled (L = 2 m) (1)	XS612B4PAL2	0.075
			M12 connector	XS612B4PAM12	0.020
		NPN	Pre-cabled (L = 2 m) (1)	XS612B4NAL2	0.075
			M12 connector	XS612B4NAM12	0.020
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS612B4PBL2	0.075
			M12 connector	XS612B4PBM12	0.020
		NPN	Pre-cabled (L = 2 m) (1)	XS612B4NBL2	0.075
			M12 connector	XS612B4NBM12	0.020

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
12	NO	PNP	Pre-cabled (L = 2 m) (1)	XS618B4PAL2	0.100
			M12 connector	XS618B4PAM12	0.040
		NPN	Pre-cabled (L = 2 m) (1)	XS618B4NAL2	0.100
			M12 connector	XS618B4NAM12	0.040
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS618B4PBL2	0.100
			M12 connector	XS618B4PBM12	0.040
		NPN	Pre-cabled (L = 2 m) (1)	XS618B4NBL2	0.100
			M12 connector	XS618B4NBM12	0.040

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
30	NO	PNP	Pre-cabled (L = 2 m) (1)	XS630B5PAL2	0.205
			M12 connector	XS630B5PAM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS630B5NAL2	0.205
			M12 connector	XS630B5NAM12	0.145
	NC	PNP	Pre-cabled (L = 2 m) (1)	XS630B5PBL2	0.205
			M12 connector	XS630B5PBM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS630B5NBL2	0.205

Accessories (2)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108	0.004
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m long cable replace L2 by **L5**; for a 10 m long cable replace L2 by **L10**. Please consult our Customer Care Centre for availability.

Example: XS612B4PAL2 becomes **XS612B4PAL5** with a 5 m cable.

(2) For more information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, increased range, non flush mountable

Three-wire DC, solid-state output

Characteristics			
Sensor type		XS6...B...M8	XS6...B...M12
Product certifications		UL, CSA, CE, E2	
Connection	Connector	M8	M12
	Pre-cabled	—	Length: 2 m
Operating zone	Ø 8	mm	0...3.2
	Ø 12	mm	0...5.6
	Ø 18	mm	0...9.6
	Ø 30	mm	0...24
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 65 and IP 67	
	Conforming to DIN 40050	IP 69K	
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Nickel plated brass, stainless steel grade 303 for XS608	
	Sensing face	PPS	
	Cable	—	PvR 3 x 0.34 mm ² except for Ø 8: 3 x 0.11 mm ²
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms
Output state indication		Yellow LED: 4 viewing ports at 90°	
Rated supply voltage		V	12...48 with protection against reverse polarity
Voltage limits (including ripple)		V	10...58
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	XS608B4... and XS612B4...	Hz	2500
	XS618B4...	Hz	1000
	XS630B5...	Hz	500
Delays	First-up	ms	≤ 10 for Ø 8, Ø 12 and Ø 18; ≤ 15 for Ø 30
	Response	ms	≤ 0.2 for Ø 8 and Ø 12; ≤ 0.3 for Ø 18; ≤ 0.6 for Ø 30
	Recovery	ms	≤ 0.2 for Ø 8 and Ø 12; ≤ 0.7 for Ø 18; ≤ 1.4 for Ø 30

Wiring schemes

Connector	Pre-cabled	PNP	NPN
M8 	M12 	BU: Blue BN: Brown BK: Black 	


Setting-up

Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 8	e ≥ 24	e ≥ 40	e ≥ 12	d ≥ 24, h ≥ 8
Ø 12	e ≥ 48	e ≥ 84	e ≥ 21	d ≥ 36, h ≥ 12
Ø 18	e ≥ 72	e ≥ 144	e ≥ 36	d ≥ 54, h ≥ 18
Ø 30	e ≥ 300	e ≥ 300	e ≥ 90	d ≥ 90, h ≥ 35

Dimensions

	Pre-cabled (mm)			M8 Connector (mm)			M12 Connector (mm)		
	a	b	c	a	b	c	a	b	c
XS6 Ø 8	51	38	4	58	39	4	61	36	4
Ø 12	54	42	5	—	—	—	66	42	5
Ø 18	60	44	8	—	—	—	72	44	8
Ø 30	66	41	13	—	—	—	74	41	13




(1) LED

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, non flush mountable


Three-wire DC, solid-state output



XS212B4●●L●



XS218B4●●M12



XSZB1●●

Sensors, 3-wire 12-24 V, short case model

Ø 12, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
8	NO	PNP	Pre-cabled (L = 2 m)	XS212B4PAL2	0.086
			Pre-cabled (L = 5 m)	XS212B4PAL5	0.160
			M12 connector	XS212B4PAM12	0.032
	NPN	PNP	Pre-cabled (L = 2 m)	XS212B4NAL2	0.086
			M12 connector	XS212B4NAM12	0.032
	NC	PNP	Pre-cabled (L = 2 m)	XS212B4PBL2	0.086
			M12 connector	XS212B4PBM12	0.032
	NPN	PNP	Pre-cabled (L = 2 m)	XS212B4NBL2	0.086

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
16	NO	PNP	Pre-cabled (L = 2 m)	XS218B4PAL2	0.105
			Pre-cabled (L = 5 m)	XS218B4PAL5	0.190
			M12 connector	XS218B4PAM12	0.052
	NPN	PNP	Pre-cabled (L = 2 m)	XS218B4NAL2	0.105
			M12 connector	XS218B4NAM12	0.052
	NC	PNP	Pre-cabled (L = 2 m)	XS218B4PBL2	0.105
			M12 connector	XS218B4PBM12	0.052

Accessories (1)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010

(1) For further information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, increased range, non flush mountable

Three-wire DC, solid-state output

Characteristics			
Sensor type		XS21●B4●●M12	XS21●B4●●L●
Product certifications		UL, CSA, CE, E2	
Connection	Connector	M12	—
	Pre-cabled	—	Length: 2 or 5 m
Operating zone	Ø 12	mm	0...6.4
	Ø 18	mm	0...12.8
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 65 and IP 67	
	Conforming to DIN 40050	IP 69K	
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Brass	
	Sensing face	PPS	
	Cable	—	PvR 3 x 0.34 mm ²
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED, 4 viewing ports at 90°	Yellow LED, annular
Rated supply voltage		V	— 12...24 with protection against reverse polarity
Voltage limits (including ripple)		V	— 10...36
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	XS212B4●●●●	Hz	2000
	XS218B4●●●●	Hz	1000
Delays	First-up	ms	≤ 15
	Response	ms	≤ 0.2 for Ø 12 ≤ 0.3 for Ø 18
	Recovery	ms	≤ 0.2 for Ø 12 ≤ 0.7 for Ø 18

Wiring schemes

Connector	Pre-cabled	PNP	NPN
M12 	BU: Blue BN: Brown BK: Black		


Setting-up

Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 12	e ≥ 100	e ≥ 120	e ≥ 24	d ≥ 36, h ≥ 15
Ø 18	e ≥ 120	e ≥ 200	e ≥ 48	d ≥ 54, h ≥ 18

Dimensions

	Pre-cabled (mm)			M12 connector (mm)		
	a	b	c	a	b	c
Ø 12	37	20	5	51	26	5
Ø 18	41	21	8	51	21	8




(1) LED

Inductive proximity sensors


XS range, general purpose

Cylindrical, increased range, non flush mountable


Two-wire AC or DC



XS6...B4M...L2



XS6...B4M...U20



XSZB1...

Sensors, 2-wire $\approx$ 24... 240 V, long case model

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
12	NO	Pre-cabled (L = 2 m) (1)	XS618B4MAL2	0.120
		1/2"-20 UNF connector	XS618B4MAU20	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS618B4MBL2	0.120
		1/2"-20 UNF connector	XS618B4MBU20	0.060

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
22	NO	Pre-cabled (L = 2 m) (1)	XS630B4MAL2	0.205
		1/2"-20 UNF connector	XS630B4MAU20	0.145
	NC	Pre-cabled (L = 2 m) (1)	XS630B4MBL2	0.205
		1/2"-20 UNF connector	XS630B4MBU20	0.145

Accessories (2)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For a 5 m cable replace L2 by L5; for a 10 m cable replace L2 by L10.

Example: XS618B4MAL2 becomes **XS618B4MAL5** with a 5 m cable.

(2) For more information, see page 118.

Characteristics			
Sensor type		XS6●●B4M●U20	XS6●●B4M●L2
Product certifications		UL, CSA, CÉ	
Connection	Connector	1/2"-20 UNF	—
	1/2"-20 UNF Pre-cabled	—	Length: 2 m
Operating zone	Ø 18	mm	0...9.6
	Ø 30	mm	0...17.6
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection		Conforming to IEC 60529	IP 65 and IP 67 IP 65 and IP 68, double insulation □
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case	Nickel plated brass	
	Sensing face	PPS	
	Cable	—	PvR 2 x 0.34 mm ²
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms
Output state indication		Yellow LED: 4 viewing ports at 90°	Yellow LED: annular
Rated supply voltage		V	~ or — 24...240 (~ 50/60 Hz)
Voltage limits (including ripple)		V	~ or — 20...264
Switching capacity		mA	~ 5...300 or — 5...200 (1)
Voltage drop, closed state		V	≤ 5.5
Residual current, open state		mA	≤ 0.8
Maximum switching frequency	XS618B4M●●●	Hz	~ 25 or — 1000
	XS630B4M●●●	Hz	~ 25 or — 300
Delays	First-up	ms	≤ 30 XS618B4M●●● and XS630B4M●●●
	Response	ms	≤ 0.5
	Recovery	ms	≤ 0.5 XS618B4M●●●, ≤ 2 XS630B4M●●●

(1) It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Wiring schemes

Connector	Pre-cabled	2-wire ~ or —
1/2"-20 UNF	BU: Blue BN: Brown	NO or NC output
		⚡: on connector models only

Setting-up

Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 18	e ≥ 72	e ≥ 144	e ≥ 36	d ≥ 54, h ≥ 18
Ø 30	e ≥ 120	e ≥ 264	e ≥ 66	d ≥ 90, h ≥ 30

Dimensions

	Pre-cabled (mm)			Connector (mm)		
	a	b	c	a	b	c
Ø 18	60	44	8	72	44	8
Ø 30	63	41	13	74	41	13

(1) LED


Inductive proximity sensors

XS range, general purpose, standard range


Flat format, flush mountable

Two-wire DC


Three-wire DC, solid-state output




XS7J1A1●●L2



XS7J1A1●●L01M8



XS7F1A1●●L2



XS7F1A1●●L01M8

Flat, 8 x 22 x 8 mm format ⁽¹⁾ ⁽²⁾

Three-wire ---

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
2.5	NO	PNP	Pre-cabled (L = 2 m) ⁽³⁾	XS7J1A1PAL2	0.060
			Remote M8 connector on 0.15 m flying lead	XS7J1A1PAL01M8	0.040
	NPN	NPN	Pre-cabled (L = 2 m) ⁽³⁾	XS7J1A1NAL2	0.060
			Remote M8 connector on 0.15 m flying lead	XS7J1A1NAL01M8	0.040
	NC	PNP	Pre-cabled (L = 2 m) ⁽³⁾	XS7J1A1PBL2	0.060
			Remote M8 connector on 0.15 m flying lead	XS7J1A1PBL01M8	0.040
		NPN	Pre-cabled (L = 2 m) ⁽³⁾	XS7J1A1NBL2	0.060
			Remote M8 connector on 0.15 m flying lead	XS7J1A1NBL01M8	0.040

Two-wire ---

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
2.5	NO		Pre-cabled (L = 2 m) ⁽³⁾	XS7J1A1DAL2	0.050
			Remote M8 connector on 0.15 m flying lead	XS7J1A1DAL01M8	0.035
	NC		Pre-cabled (L = 2 m) ⁽³⁾	XS7J1A1DBL2	0.050
			Remote M8 connector on 0.15 m flying lead	XS7J1A1DBL01M8	0.035

Flat, 15 x 32 x 8 mm format ⁽¹⁾

Three-wire ---

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
5	NO	PNP	Pre-cabled (L = 2 m) ⁽³⁾	XS7F1A1PAL2	0.065
			Remote M8 connector on 0.15 m flying lead	XS7F1A1PAL01M8	0.045
	NPN	NPN	Pre-cabled (L = 2 m) ⁽³⁾	XS7F1A1NAL2	0.065
			Remote M8 connector on 0.15 m flying lead	XS7F1A1NAL01M8	0.045
	NC	PNP	Pre-cabled (L = 2 m) ⁽³⁾	XS7F1A1PBL2	0.065
			Remote M8 connector on 0.15 m flying lead	XS7F1A1PBL01M8	0.045
		NPN	Pre-cabled (L = 2 m) ⁽³⁾	XS7F1A1NBL2	0.065
			Remote M8 connector on 0.15 m flying lead	XS7F1A1NBL01M8	0.045

Two-wire ---

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
5	NO		Pre-cabled (L = 2 m) ⁽³⁾	XS7F1A1DAL2	0.055
			Remote M8 connector on 0.15 m flying lead	XS7F1A1DAL01M8	0.045
	NC		Pre-cabled (L = 2 m) ⁽³⁾	XS7F1A1DBL2	0.055
			Remote M8 connector on 0.15 m flying lead	XS7F1A1DBL01M8	0.045

(1) For accessories, see page 118.

(2) Sensors **XS7J** include a fixing clamp with screw.

(3) For a 5 m long cable replace L2 by **L5**; for a 10 m long cable replace L2 by **L10**.
Example: **XS7J1A1PAL2** becomes **XS7J1A1PAL5** with a 5 m long cable.

Inductive proximity sensors

XS range, general purpose, standard range

Flat format, flush mountable

Two-wire DC

Three-wire DC, solid-state output

Characteristics			
Sensor type		XS7J●●●●●L01M8	XS7F●●●●●L01M8
Product certifications		CE	UL, CSA, CE
Connection	Connector	Remote M8 connector on 0.15 m flying lead	
	Pre-cabled	Length: 2 m	
Operating zone	XS7J	mm	0...2
	XS7F	mm	0...4
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529		IP 67 (XS7J), IP 68 (XS7F)
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case		PBT
	Cable		PvR 3 x 0.11 mm ² or 2 x 0.11 mm ² (XS7F: 2 or 3 x 0.34 mm ²)
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms
Output state indication			Yellow LED
Rated supply voltage		V	12...24 with protection against reverse polarity
Voltage limits (including ripple)		V	10...36
Current consumption, no-load	3-wire	mA	≤ 10
Residual current, open state	2-wire	mA	≤ 0.5
Switching capacity	3-wire	mA	100 with overload and short-circuit protection
	2-wire	mA	1.5...100 with overload and short-circuit protection
Voltage drop, closed state	3-wire	V	≤ 2
	2-wire	V	≤ 4
Maximum switching frequency	3-wire	kHz	2
	2-wire	kHz	4 for XS7J, 5 for XS7F
Delays	First-up	ms	Three-wire: 5
		ms	Two-wire: 10 XS7J, 5 XS7F
	Response	ms	Three-wire: 0,1
		ms	Two-wire: 0,5 XS7J, 5 XS7F
	Recovery	ms	Three-wire: 0,1
		ms	Two-wire: 1 XS7J, 5 XS7F

Wiring schemes

Connector	Pre-cabled	PNP NO or NC	NPN NO or NC	2-wire NO
M8 4 1 3	BU: Blue BN: Brown BK: Black			
				2-wire NC


Setting-up

Minimum mounting distances (mm)


Side by side	Face to face	Facing a metal object
XS7J e ≥ 7.5	e ≥ 20	e ≥ 7.5
XS7F e ≥ 15	e ≥ 40	e ≥ 15

Dimensions

XS7F




XS7J



(1) LED
(2) For CHC type screws

Inductive proximity sensors

XS range, general purpose, standard range
 Flat format, flush mountable
 Two-wire DC
 Three-wire DC, solid-state output



Sens. dist. (Sn) mm	Function	Output	Connection	Reference	Weight kg
Flat, 26 x 26 x 13 mm format (1)					
Three-wire ---					
10	NO	PNP	Pre-cabled (L = 2 m) (4)	XS7E1A1PAL2	0.075
			M8 connector	XS7E1A1PAM8	0.040
			Remote M12 connector	XS7E1A1PAL01M12	0.040
		NPN	Pre-cabled (L = 2 m) (4)	XS7E1A1NAL2	0.075
			M8 connector	XS7E1A1NAM8	0.075
			Remote M12 connector	XS7E1A1NAL01M12	0.040
	NC	PNP	Pre-cabled (L = 2 m) (4)	XS7E1A1PBL2	0.075
			M8 connector	XS7E1A1PBM8	0.040
			Remote M12 connector	XS7E1A1PBL01M12	0.040
		NPN	Pre-cabled (L = 2 m) (4)	XS7E1A1NBL2	0.075
			M8 connector	XS7E1A1NBM8	0.040
			Remote M12 connector	XS7E1A1NBL01M12	0.040
Two-wire ---					
10	NO		Pre-cabled (L = 2 m) (4)	XS7E1A1DAL2	0.070
			M8 connector	XS7E1A1DAM8	0.040
			Remote M12 connector	XS7E1A1DAL01M12	0.040
	NO terminals 1 and 4 (2)		Remote M12 connector	XS7E1A1CAL01M12	0.040
			Remote M12 connector (3)	XS7E1A1CAL08M12	0.065
	NC		Pre-cabled (L = 2 m) (4)	XS7E1A1DBL2	0.070
			M8 connector	XS7E1A1DBM8	0.040
			Remote M12 connector	XS7E1A1DBL01M12	0.040
		Flat, 40 x 40 x 15 mm format (1)			
Three-wire ---					
15	NO	PNP	Pre-cabled (L = 2 m) (4)	XS7C1A1PAL2	0.095
			M8 connector	XS7C1A1PAM8	0.060
			Remote M12 connector	XS7C1A1PAL01M12	0.060
		NPN	Pre-cabled (L = 2 m) (4)	XS7C1A1NAL2	0.095
			M8 connector	XS7C1A1NAM8	0.060
			Remote M12 connector	XS7C1A1NAL01M12	0.060
	NC	PNP	Pre-cabled (L = 2 m) (4)	XS7C1A1PBL2	0.095
			M8 connector	XS7C1A1PBM8	0.060
			Remote M12 connector	XS7C1A1PBL01M12	0.060
		NPN	Pre-cabled (L = 2 m) (4)	XS7C1A1NBL2	0.095
			M8 connector	XS7C1A1NBM8	0.060
			Remote M12 connector	XS7C1A1NBL01M12	0.060
Two-wire ---					
15	NO		Pre-cabled (L = 2 m) (4)	XS7C1A1DAL2	0.090
			M8 connector	XS7C1A1DAM8	0.060
			Remote M12 connector	XS7C1A1DAL01M12	0.060
	NO terminals 1 and 4 (2)		Remote M12 connector	XS7C1A1CAL01M12	0.060
			Remote M12 connector (3)	XS7C1A1CAL08M12	0.090
	NC		Pre-cabled (L = 2 m) (4)	XS7C1A1DBL2	0.090
			M8 connector	XS7C1A1DBM8	0.060
			Remote M12 connector	XS7C1A1DBL01M12	0.060
		Flat, 80 x 80 x 26 mm format (1)			
Three-wire ---					
40	NO	PNP	Pre-cabled (L = 2 m) (4)	XS7D1A1PAL2 (5)	0.340
			M12 connector	XS7D1A1PAM12 (5)	0.290
		NPN	Pre-cabled (L = 2 m) (4)	XS7D1A1NAL2 (5)	0.340
			M12 connector	XS7D1A1NAM12 (5)	0.290
	NC	PNP	Pre-cabled (L = 2 m) (4)	XS7D1A1PBL2 (5)	0.340
			M12 connector	XS7D1A1PBM12 (5)	0.290
NPN	Pre-cabled (L = 2 m) (4)	XS7D1A1NBL2 (5)	0.340		
	M12 connector	XS7D1A1NBM12 (5)	0.290		
Two-wire ---					
40	NO		Pre-cabled (L = 2 m) (4)	XS7D1A1DAL2 (5)	0.340
			M12 connector	XS7D1A1DAM12 (5)	0.290
	NO terminals 1 and 4 (2)		M12 connector	XS7D1A1CAM12 (5)	0.290
	NC		Pre-cabled (L = 2 m) (4)	XS7D1A1DBL2 (5)	0.340
			M12 connector	XS7D1A1DBM12 (5)	0.290

(1) For accessories, see page 118.

(2) The NO output is connected to terminals 1 and 4 of the M12 connector.







(3) Remote connector on 0.8 m flying lead.

(4) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.




Example: **S7 J1A1PAL2** becomes **XS7 J1A1PAL5** with a 5 m long cable.(5) For clipping onto 35 mm omega rail or 80 x 80 x 40 mm format, add DIN to the end of the reference. Example: **XS7D1A1PAL2** becomes **XS7D1A1PAL2DIN**.

Characteristics						
Sensor type			XS7E●●●●M8, XS7C●●●●M8, XS7D●●●●M12	XS7E●●●●L01M12, XS7C●●●●L01M12	XS7E●●●●L2, XS7C●●●●L2, XS7D●●●●L2	
Product certifications			UL, CSA, CE, ECOLAB			
Connection	Connector		M8 except M12 on XS7D●●●●M12	M12 on 0.15 m flying lead for XS7●●●●L01M12	–	
	Pre-cabled		–	–	Length: 2 m	
Operating zone	XS7E		mm	0...8		
	XS7C		mm	0...12		
	XS7D		mm	0...32		
Differential travel			%	1...15 of effective sensing distance (Sr)		
Degree of protection		Conforming to IEC 60529	IP 67, double insulation □ (except for M8 connector: IP 67)			IP 68, □
Storage temperature			°C	- 40...+ 85		
Operating temperature			°C	- 25...+ 70		
Materials	Case		PBT			
	Cable		–	PvR 3 x 0.34 mm² or 2 x 0.34 mm²		
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)			
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms			
Output state indication			Yellow LED			
Rated supply voltage			V	12...24 with protection against reverse polarity		
Voltage limits (including ripple)			V	10...36		
Current consumption, no-load		3-wire	mA	≤ 10		
Residual current, open state		2-wire	mA	≤ 0.5		
Switching capacity	3-wire		mA	≤ 100 with overload and short-circuit protection		
	2-wire		mA	1.5...100 with overload and short-circuit protection		
Voltage drop, closed state	3-wire		V	≤ 2		
	2-wire		V	≤ 4		
Maximum switching frequency	XS7E, XS7C		kHz	1		
	XS7D		Hz	100		
Delays	First-up	3-wire	ms	10 XS7E and XS7C, 30 XS7D		
		2-wire	ms	5 XS7E and XS7D, 10 XS7D		
	Response	3-wire	ms	2 XS7E and XS7C, 5 XS7D		
		2-wire	ms	0,3 XS7E and XS7D, 10 XS7D		
	Recovery	3-wire	ms	6 XS7E, 5 XS7C, 35 XS7D		
		2-wire	ms	0,7 XS7E and XS7D, 10 XS7D		




Wiring schemes

Connector	Pre-cabled	PNP (1)	2-wire NO/M12 or M8	2-wire NC/M12 or M8
M12 M8 	BU: Blue BN: Brown BK: Black			
		NPN (1)	2-wire NO/M12 XS7●●●●CA●●●	
				(1) For M8 connector, NO and NC outputs on terminal 4

Setting-up

Minimum mounting distances (mm)				
Side by side	e ≥	XS7E	XS7C	XS7D
		30	45	120
Face to face	e ≥	XS7E	XS7C	XS7D
		72	110	300
Facing a metal object	e ≥	XS7E	XS7C	XS7D
		30	45	120


Dimensions

	XS7C/D/E	XS7C/D	XS7E			
						
Sensor	A (cable)	A (connector)	B	C	D	F
XS7E	14	11	26	13	8.8	20
XS7C	14	11	40	15	9.8	33
XS7D	23	18	80	26	16	65
XS7D●●DIN	23	18	80	40	30	65

(1) LED
(2) For CHC type screws

Inductive proximity sensors

XS range, general purpose
Cubic case, 40 x 40 x 70 mm, M12 or 1/2"-20UNF
connector
5 position turret head

Sensor			Flush mountable in metal		Non flush mountable in metal	
						
Nominal sensing distance (Sn)			15 mm	20 mm	40 mm	
References						
4-wire ---	PNP	NO+NC	–	XS8C2A1PCM12	XS8C2A4PCM12	
	NPN	NO+NC	–	XS8C2A1NCM12	XS8C2A4NCM12	
3-wire ---	PNP	NO	XS7C2A1PAM12	–	–	
	NPN	NO	XS7C2A1NAM12	–	–	
	PNP	NC	XS7C2A1PBM12	–	–	
	NPN	NC	XS7C2A1NBM12	–	–	
2-wire ---	NO		XS7C2A1DAM12	XS8C2A1DAM12	XS8C2A4DAM12	
	NC		XS7C2A1DBM12	XS8C2A1DBM12	XS8C2A4DBM12	
2-wire (~/---) unprotected (1)	NO		XS7C2A1MAU20	XS8C2A1MAU20	XS8C2A4MAU20	
	NC		XS7C2A1MBU20	XS8C2A1MBU20	XS8C2A4MBU20	
Weight (kg)			0.149	0.149	0.149	
Characteristics						
Operating zone			0...12 mm	0...16 mm	0...32 mm	
Product certifications			UL, CSA, CE, TÜV (4-wire), E2 (3-wire and 4-wire)			
Conformity to standards			IEC 60947-5-2			
Conformity to safety standards (2)		For XS8C2A●PCM12	EN 62061 (2005): SILcl2 EN 61508 (2010): SIL 2, EN ISO 13849 (2008): PL d			
Reliability data (2)		For XS8C2A●PCM12	MTTFd = 1546 years PFHd = 7.4 10-8 1/h			
Connection			M12 connector for --- versions 1/2 "-20UNF connector for ~/--- versions			
Differential travel			3...15% of Sr			
Degree of protection		Conforming to IEC 60529 and DIN 40050	IP 65, IP 67 and IP 69K			
Temperature	Storage		- 40...+ 85°C			
	Operation (3)		- 25...+ 70°C			
Material			Case: PBT			
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10...55 Hz)			
Shock resistance		Conforming to IEC 60068-2-27	50 gn for 11 ms			
Indicators		Output state	Yellow LED			
		Power on	Green LED, for 4-wire ---, 3-wire --- and 2-wire ~/--- versions			
Rated supply voltage	4-wire ---		12...48 V with protection against reverse polarity			
	3-wire ---		12...24 V with protection against reverse polarity			
	2-wire ---		12...48 V with protection against reverse polarity			
	2-wire ~/---		24...240 V (~ 50/60 Hz)			
Voltage limits (including ripple)	4-wire ---		10...58 V			
	3-wire ---		10...36 V			
	2-wire ---		10...58 V			
	2-wire ~/---		20...264 V			
Current consumption, no-load		3-wire and 4-wire ---	< 15 mA			
Residual current, open state	2-wire ---		< 0.6 mA			
	2-wire ~/---		1.5 mA			
Switching capacity	3-wire and 4-wire ---		< 200 mA with overload and short-circuit protection			
	2-wire ---		< 100 mA with overload and short-circuit protection			
	2-wire ~/---		~: 5...300 mA (1) ---: 5...200 mA (1)			
Voltage drop, closed state	3-wire and 4-wire ---		< 2 V			
	2-wire ---		< 4.2 V			
	2-wire ---/~		< 5.5 V			
Maximum switching frequency			Flush mountable: --- 300 Hz, ~ 25 Hz Non flush mountable: --- 150 Hz, ~ 25 Hz			
Delays	First-up		7 ms (3-wire and 4-wire ---), 20 ms (2-wire --- and 2-wire ---/~)			
	Response		Flush mountable: ≤ 1.2 ms. Non flush mountable: ≤ 1.4 ms			
	Recovery		Flush mountable: ≤ 1.8 ms. Non flush mountable: ≤ 3.5 ms			

(1) Sensor must be protected by a 0.4 A quick-blow fuse (reference **XUZE04**) connected in series with the load.

(2) SIL 2 protection can only be obtained by connecting both outputs to a safety PLC.

(3) Sensors are available for very low temperatures (suffix **TF**: - 40°C, + 70°C) or very high temperatures (suffix **TT**: - 25°C, + 85°C). Please consult our Customer Care Centre.

Inductive proximity sensors

XS range, general purpose

Cubic case, 40 x 40 x 70 mm, M12 or 1/2"-20UNF connector

5 position turret head



Setting-up precautions

Minimum mounting distances (mm)


		Side by side	Face to face	Facing a metal object
Sensors flush mountable in metal	XS7C2A1●●	$e \geq 60$	$e \geq 120$	$e \geq 45$
	XS8C2A1●●	$e \geq 80$	$e \geq 160$	$e \geq 60$
Sensors non flush mountable in metal	XS8C2A4●●	$e \geq 160$	$e \geq 320$	$e \geq 120$

Wiring schemes


4-wire ---, NO + NC outputs




3-wire, PNP




3-wire, NPN




2-wire, 1/2"-20UNF




2-wire ---, NO output
(M12 connector)



2-wire ---, NC output
(M12 connector)



M12 connector




1/2"-20UNF connector




Accessory references

Description	Type	Length m	Reference	Weight kg
Pre-wired M12 connectors Female, 4-pin, zinc die-cast, nickel plated clamping ring	Straight	2	XZCP1141L2	0.090
		5	XZCP1141L5	0.190
		10	XZCP1141L10	0.370
	Elbowed	2	XZCP1241L2	0.090
		5	XZCP1241L5	0.190
		10	XZCP1241L10	0.370
Pre-wired 1/2"-20UNF connectors Female, 3-pin, zinc die-cast, nickel plated clamping ring	Straight	5	XZCP1865L5	0.180
		10	XZCP1865L10	0.350
		10	XZCP1865L10	0.350
	Elbowed	5	XZCP1965L5	0.180
		10	XZCP1965L10	0.350
		10	XZCP1965L10	0.350


Dimensions



Head positions



Example SIL 2 wiring scheme (with XPSMCMCP0802 safety PLC)



SFF (Safe Failure Fraction): 92,68 %
DC (Diagnosis Coverage): 75,8 %


Inductive proximity sensors

XS range, general purpose

Plastic case, 40 x 40 x 117 mm, plug-in

5 position turret head

Sensor	Flush mountable in metal	Non flush mountable in metal
--------	--------------------------	------------------------------



Nominal sensing distance (Sn)	15 mm	20 mm	40 mm
-------------------------------	-------	-------	-------

References

4-wire ---	PNP NO+NC	—	XS8C4A1PCP20	XS8C4A4PCP20
	NPN NO+NC	—	XS8C4A1NCP20	XS8C4A4NCP20
2-wire ---	NO or NC programmable	XS7C4A1DPP20	XS8C4A1DPP20	XS8C4A4DPP20
2-wire (~---) unprotected (1)	NO or NC programmable	XS7C4A1MPP20	XS8C4A1MPP20	XS8C4A4MPP20
Weight (kg)		0.244	0.244	0.244

Note: These sensors have an M20 cable entry. They can also be supplied with a PG 13.5 cable entry (e.g. XS8C4A4PCG13) or a 1/2" NPT cable entry (e.g. XS8C4A1MPN12). Please consult our Customer Care Centre.

Characteristics

Operating zone		0...12 mm	0...16 mm	0...32 mm
Product certifications		UL, CSA, CE, TÜV (4-wire), E2 (4-wire)		
Conformity to standards		IEC 60947-5-2		
Conformity to safety standards (2)	For XS8C4A●PCP20	EN 62061 (2005): SILcl2, EN 61508 (2010): SIL 2, EN ISO 13849 (2008): PL d		
Reliability data (2)	For XS8C4A●PCP20	MTTFd = 1546 years PFHd = 7.4 10 ⁻⁸ 1/h		
Connection		Screw terminals, clamping capacity: 2 or 4 x 1.5 mm ² / 2 or 4 x 16 AWG (3)		
Differential travel		3...15% of Sr		
Degree of protection	Conforming to IEC 60529 and DIN 40050	IP 65, IP 67 and IP 69K		
Temperature	Storage	- 40...+ 85°C		
	Operation (4)	- 25...+ 70°C		
Material		Case: PBT		
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10...55 Hz)		
Shock resistance	Conforming to IEC 60068-2-27	50 gn for 11 ms		
Indicators	Output state	Yellow LED		
	Power on	Green LED, for 4-wire --- and 2-wire ~--- versions		
Rated supply voltage	4-wire ---	12...48 V with protection against reverse polarity		
	2-wire ---	12...48 V with protection against reverse polarity		
	2-wire ~---	24...240 V (~ 50/60 Hz)		
Voltage limits (including ripple)	4-wire ---	10...58 V		
	2-wire ---	10...58 V		
	2-wire ~---	20...264 V		
Current consumption, no-load	4-wire ---	< 15 mA		
Residual current, open state	2-wire ---	< 0.6 mA		
	2-wire ~---	1.5 mA		
Switching capacity	4-wire ---	< 200 mA with overload and short-circuit protection		
	2-wire ---	< 100 mA with overload and short-circuit protection		
	2-wire ~---	~: 5...300 mA (1) ---: 5...200 mA (1)		
Voltage drop, closed state	4-wire ---	< 2 V		
	2-wire ---	< 4.2 V		
	2-wire ---/~	< 5.5 V		
Maximum switching frequency		Flush mountable: --- 300 Hz, ~ 25 Hz Non flush mountable: --- 150 Hz, ~ 25 Hz		
Delays	First-up	7 ms (3-wire and 4-wire ---), 20 ms (2-wire --- and 2-wire ---/~)		
	Response	Flush mountable: ≤ 1.2 ms. Non flush mountable: ≤ 1.4 ms		
	Recovery	Flush mountable: ≤ 1.8 ms. Non flush mountable: ≤ 3.5 ms		

(1) Sensor must be protected by a 0.4 A quick-blow fuse (reference XUZ04) connected in series with the load.

(2) SIL 2 protection can only be obtained by connecting both outputs to a safety PLC.

(3) These sensors are supplied without a cable gland. An adaptable PG 13.5 cable gland is available (reference XSZPE13). Accessories are available for connection to an M12 or 7/8"-16UN connector which can be added to the PG 13.5 sensor. Please consult our Customer Care Centre.

(4) Sensors are available for very low temperatures (suffix TF: - 40°C, + 70°C) or very high temperatures (suffix TT: - 25°C, + 85°C). Please consult our Customer Care Centre.

Inductive proximity sensors

XS range, general purpose

Plastic case, 40 x 40 x 117 mm, plug-in

5 position turret head

Setting-up precautions


Minimum mounting distances (mm)

		Side by side	Face to face	Facing a metal object
Sensors flush mountable in metal	XS7C4A1●●	$e \geq 60$	$e \geq 120$	$e \geq 45$
	XS8C4A1●●	$e \geq 80$	$e \geq 160$	$e \geq 60$
Sensors non flush mountable in metal	XS8C4A4●●	$e \geq 160$	$e \geq 320$	$e \geq 120$

Wiring schemes


NO + NC outputs

4-wire ---




NO or NC outputs, depending on position of link


2-wire --- (non polarised)



2-wire ~ or --- (programmable)




Dimensions




(1) 2 elongated holes $\varnothing 5.3 \times 7$ cm.

Tightening torque of cover fixing screws and clamp screws: $< 1.2 \text{ N.m} / < 10.62 \text{ lb-in}$

Head positions



Example SIL 2 wiring scheme (with XPSMCMCP0802 safety PLC)




SFF (Safe Failure Fraction): 92,68 %
DC (Diagnosis Coverage): 75,8 %

Inductive proximity sensors


XS range, general purpose

Multivoltage sensor, cylindrical, flush mountable and non flush mountable


Two-wire AC or DC, short-circuit protection




XS1M12MA250




XS2M12MA250



XS1M18MA250K



XS2M18MA250K



XSZB112

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
Ø 12, threaded M12 x 1				
Flush mountable				
2	NO	Pre-cabled (L = 2 m) (1)	XS1M12MA250	0.075
		1/2"-20UNF connector	XS1M12MA250K	0.025
	NC	Pre-cabled (L = 2 m) (1)	XS1M12MB250	0.075
		1/2"-20UNF connector	XS1M12MB250K	0.025
Non flush mountable				
4	NO	Pre-cabled (L = 2 m) (1)	XS2M12MA250	0.075
		1/2"-20UNF connector	XS2M12MA250K	0.025
	NC	Pre-cabled (L = 2 m) (1)	XS2M12MB250	0.075
Ø 18, threaded M18 x 1				
Flush mountable				
5	NO	Pre-cabled (L = 2 m) (1)	XS1M18MA250	0.120
		1/2"-20UNF connector	XS1M18MA250K	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS1M18MB250	0.120
		1/2"-20UNF connector	XS1M18MB250K	0.060
Non flush mountable				
8	NO	Pre-cabled (L = 2 m) (1)	XS2M18MA250	0.120
		1/2"-20UNF connector	XS2M18MA250K	0.060
	NC	Pre-cabled (L = 2 m) (1)	XS2M18MB250	0.120
		1/2"-20UNF connector	XS2M18MB250K	0.060
Ø 30, threaded M30 x 1.5				
Flush mountable				
10	NO	Pre-cabled (L = 2 m) (1)	XS1M30MA250	0.205
		1/2"-20UNF connector	XS1M30MA250K	0.145
	NC	Pre-cabled (L = 2 m) (1)	XS1M30MB250	0.205
		1/2"-20UNF connector	XS1M30MB250K	0.145
Non flush mountable				
15	NO	Pre-cabled (L = 2 m) (1)	XS2M30MA250	0.205
		1/2"-20UNF connector	XS2M30MA250K	0.145
	NC	Pre-cabled (L = 2 m) (1)	XS2M30MB250	0.205
		1/2"-20UNF connector	XS2M30MB250K	0.145
Accessories (2)				
Description mm			Reference	Weight kg
Fixing clamps	Ø 12		XSZB112	0.006
	Ø 18		XSZB118	0.010
	Ø 30		XSZB130	0.020

(1) For a 5 m long cable add L1 to the reference; for a 10 m long cable add L2 to the reference.
Example: XS1M18MA250 becomes XS1M18MA250L1 with a 5 m long cable.

(2) For further information, see page 118.

Inductive proximity sensors


XS range, general purpose

Multivoltage sensor, cylindrical, flush mountable and non flush mountable

Two-wire AC or DC, short-circuit protection

Characteristics						
Sensor type			XS●M●●M●250K		XS●M●●M●250	
Product certifications			UL, CSA, CE			
Connection			1/2"-20UNF connector		Pre-cabled, length: 2 m	
Operating zone	Ø 12 flush mountable	mm	0...1.6			
	Ø 12 non flush mountable	mm	0...3.2			
	Ø 18 flush mountable	mm	0...4			
	Ø 18 non flush mountable	mm	0...6.4			
	Ø 30 flush mountable	mm	0...8			
	Ø 30 non flush mountable	mm	0...12			
Differential travel			%	1...15 of effective sensing distance (Sr)		
Degree of protection		Conforming to IEC 60529	IP 67		IP 68, double insulation	
Storage temperature			°C			- 40...+ 85
Operating temperature			°C			- 25...+ 70
Materials	Case	Nickel plated brass				
	Cable	–		PvR 2 x 0.34 mm ²		
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)			
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms			
Indicators	Output state	Yellow LED, 4 viewing ports at 90°		Yellow LED		
	Supply on	–		Green LED (only on Ø 18 and Ø 30)		
Rated supply voltage			V	~ 24...240 (50/60 Hz) or --- 24...210		
Voltage limits (including ripple)			V	~ or --- 20...264		
Switching capacity			mA	~ 5...300 or --- 5...200 (except Ø 12: ~ or --- 5...200) with overload and short-circuit protection		
Voltage drop, closed state			V	≤ 5.5		
Current consumption, no-load			mA	–		
Residual current, open state			mA	≤ 1.5		
Maximum switching frequency	Ø 12	Hz	~ 25 or --- 4000			
	Ø 18	Hz	~ 25 or --- 2000			
	Ø 30 flush mountable	Hz	~ 25 or --- 2000			
	Ø 30 non flush mountable	Hz	~ 25 or --- 1000			
Delays	First-up	ms	≤ 70			
	Response	ms	≤ 0.2 for Ø 12, ≤ 2 for Ø 18 and Ø 30			
	Recovery	ms	≤ 0.2 for Ø 12, ≤ 4 for Ø 18, ≤ 5 for Ø 30 flush mountable, ≤ 10 for Ø 30 non flush mountable			

Wiring schemes


1/2"-20UNF connector	Pre-cabled	2-wire ~ or --- NO or NC output
	BU: Blue BN: Brown	
= : on connector models only.		

Setting-up

Sensor	Minimum mounting distances (mm)			
	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 12 flush mountable	e ≥ 4	e ≥ 24	e ≥ 6	d ≥ 12 h ≥ 0
Ø 12 non flush mountable	e ≥ 16	e ≥ 48	e ≥ 12	d ≥ 36 h ≥ 8
Ø 18 flush mountable	e ≥ 10	e ≥ 60	e ≥ 15	d ≥ 18 h ≥ 0
Ø 18 non flush mountable	e ≥ 16	e ≥ 96	e ≥ 24	d ≥ 54 h ≥ 16
Ø 30 flush mountable	e ≥ 20	e ≥ 120	e ≥ 30	d ≥ 30 h ≥ 0
Ø 30 non flush mountable	e ≥ 60	e ≥ 180	e ≥ 45	d ≥ 90 h ≥ 30

Dimensions

Sensor	Flush mountable in metal					Non flush mountable in metal				
	Pre-cabled		Connector		c	Pre-cabled		Connector		c
	a	b	a	b		a	b	a	b	
Ø 12	57	42	66	48	5	57	42	66	42	5
Ø 18	60	51	72	51	8	60	44	72	44	8
Ø 30	60	51	72	51	13	63	41	75	41	13




Inductive proximity sensors

XS range, general purpose


Cylindrical, metal and plastic, flush mountable

and non flush mountable


Four-wire DC, solid-state NO + NC output



XS1L06●C410



XS1●●●●C410



XS2●●●●C410



XS1N●●●C410D

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 6.5 plain					
Stainless steel case, flush mountable					
1.5	NO + NC	PNP	Pre-cabled (L = 2 m)	XS1L06PC410	0.025
		NPN	Pre-cabled (L = 2 m)	XS1L06NC410	0.025
Ø 8, threaded M8 x 1					
Stainless steel case, flush mountable					
1.5	NO + NC	PNP	Pre-cabled (L = 2 m)	XS1M08PC410	0.035
			M12 connector	XS1M08PC410D	0.025
	NPN	Pre-cabled (L = 2 m)	XS1M08NC410	0.035	
		M12 connector	XS1M08NC410D	0.025	
Stainless steel case, non flush mountable					
2.5	NO + NC	NPN	Pre-cabled (L = 2 m)	XS2M08NC410	0.035
			M12 connector	XS2M08NC410D	0.025
Plastic case, non flush mountable					
2.5	NO + NC	PNP (3)	Pre-cabled (L = 2 m) (1)	XS4P08PC410	0.035
Ø 12, threaded M12 x 1					
Brass case, flush mountable					
2	NO + NC	PNP	Pre-cabled (L = 2 m) (1) (2)	XS1N12PC410	0.070
			M12 connector	XS1N12PC410D	0.020
	NPN	Pre-cabled (L = 2 m) (1)	XS1N12NC410	0.070	
		M12 connector	XS1N12NC410D	0.020	
Plastic case, non flush mountable					
4	NO + NC	PNP (3)	Pre-cabled (L = 2 m) (1)	XS4P12PC410	0.070
			M12 connector	XS4P12PC410D	0.020

(1) For a 5 m long cable add L1 to the reference. Example: **XS1N12PC410** becomes **XS1N12PC410L1** with a 5 m long cable.

(2) For a 10 m long cable add L2 to the reference. Example: **XS1N12PC410** becomes **XS1N12PC410L2** with a 10 m long cable.


(3) These sensors can be supplied in NPN versions. Please contact our Customer Care Centre.

Inductive proximity sensors


XS range, general purpose

Cylindrical, metal and plastic, flush mountable and non flush mountable


Four-wire DC, solid-state NO + NC output




XS●●18●C410



XS●●18●C410D



XS●●30●C410



XSZB1●●

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 18, threaded M18 x 1					
Brass case, flush mountable					
5	NO + NC	PNP	Pre-cabled (L = 2 m) (1) (2)	XS1N18PC410	0.100
			M12 connector	XS1N18PC410D	0.040
		NPN	Pre-cabled (L = 2 m)	XS1N18NC410	0.100
			M12 connector	XS1N18NC410D	0.040
Plastic case, non flush mountable					
8	NO + NC	PNP (3)	Pre-cabled (L = 2 m)	XS4P18PC410	0.100
			M12 connector	XS4P18PC410D	0.040
Ø 30, threaded M30 x 1.5					
Brass case, flush mountable					
10	NO + NC	PNP	Pre-cabled (L = 2 m) (1) (2)	XS1N30PC410	0.160
			M12 connector	XS1N30PC410D	0.100
		NPN	Pre-cabled (L = 2 m)	XS1N30NC410	0.160
			M12 connector	XS1N30NC410D	0.100
Plastic case, non flush mountable					
15	NO + NC	PNP (3)	Pre-cabled (L = 2 m)	XS4P30PC410	0.160
			M12 connector	XS4P30PC410D	0.100
Accessories (4)					
Description				Reference	Weight kg
Fixing clamps		Ø 8		XSZB108	0.006
		Ø 12		XSZB112	0.006
		Ø 18		XSZB118	0.010
		Ø 30		XSZB130	0.020

(1) For a 5 m long cable add **L1** to the reference. Example: **XS1N18PC410** becomes **XS1N18PC410L1** with a 5 m long cable.

(2) For a 10 m long cable add **L2** to the reference. Example: **XS1N18PC410** becomes **XS1N18PC410L2** with a 10 m long cable.

(3) These sensors can be supplied in NPN versions. Please contact our Customer Care Centre.

(4) For further information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, metal and plastic, flush mountable
and non flush mountable

Four-wire DC, solid-state NO + NC output

Characteristics							
Sensor type			XS●●●●PC410D	XS●●●●NC410D	XS●●●●PC410	XS●●●●NC410	
Product certifications			UL, CSA, C€, E2 (1)		UL, CSA, C€	UL, CSA, C€, E2 (2)	UL, CSA, C€
Conformity to safety standards		Ø 6.5 and Ø 8	–				
		Ø 12, Ø 18 and Ø 30	EN/IEC 61508: SIL 2 EN/ISO 13849-1: PL =d IEC 62061: SILcl2 (3)	–	EN/IEC 61508: SIL 2 EN/ISO 13849-1: PL =d IEC 62061: SILcl2 (4)	–	
Reliability data		Ø 12, Ø 18 and Ø 30	MTTFd = 1829 years, PFHd = 62 10 ⁻⁹ 1/h, SFF > 92 %, DC > 74 % (with a safety controller) (3)	–	MTTFd = 1829 years, PFHd = 62 10 ⁻⁹ 1/h, SFF > 92 %, DC > 74 % (with a safety controller) (4)	–	
Connection			M12 connector		Pre-cabled, length: 2 m		
Operating zone		Ø 6.5 and Ø 8 flush mountable	mm	0...1.2			
		Ø 8 non flush mountable	mm	0...2			
		Ø 12 flush mountable	mm	0...1.6			
		Ø 12 non flush mountable	mm	0...3.2			
		Ø 18 flush mountable	mm	0...4			
		Ø 18 non flush mountable	mm	0...6.4			
		Ø 30 flush mountable	mm	0...8			
		Ø 30 non flush mountable	mm	0...12			
Differential travel		%	1...15 of effective sensing distance (Sr)				
Degree of protection		Conforming to IEC 60529	IP 65 and IP 67	IP 67	IP 67, double insulation (Ø 6.5 and Ø 8) IP 68, double insulation (Ø 12, Ø 18 and Ø 30)		
		Conforming to DIN 40050	IP 69K (Ø 12, Ø 18 and Ø 30)	–	–		
Storage temperature		°C	- 40...+ 85				
Operating temperature		°C	- 25...+ 70 (5)				
Materials		Case	Nickel plated brass for XS1N●●●. Stainless steel 303 for XS1M08●●● and XS2M08●●●. Plastic, PPS, for XS4P●●●.				
		Cable	–		PvR 4 x 0.08 mm² (Ø 6.5 and Ø 8) PvR 4 x 0.22 mm² (Ø 12, Ø 18 and Ø 30)		
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)				
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms				
Output state indication			Yellow LED, 4 viewing ports at 90°		Yellow LED, annular		
Rated supply voltage		V	≒ 12...24 with protection against reverse polarity				
Voltage limits (including ripple)		V	≒ 9...36 (≒ 10...36 for XS4P●●●)	≒ 10...36	≒ 9...36 (≒ 10...36 for XS4P18●●●)	≒ 10...36	
Switching capacity		mA	≤ 200 with overload and short-circuit protection				
Voltage drop, closed state		V	≤ 2				
Current consumption, no-load		mA	≤ 10				
Maximum switching frequency		Ø 6.5, Ø 8 and Ø 12	Hz	5000			
		Ø 18	Hz	2000			
		Ø 30	Hz	1000			
Delays		First-up	ms	≤ 5			
		Response	ms	≤ 0.1 for Ø 8 and Ø 12, ≤ 0.15 for Ø 18, ≤ 0.3 for Ø 30			
		Recovery	ms	≤ 0.1 for Ø 8 and Ø 12, ≤ 0.35 for Ø 18, ≤ 0.7 for Ø 30			

(1) Except XS4P●●●: UL, CSA and C€.

(2) Except XS4P18●●●: UL, CSA and C€.

(3) Except XS4P●●●.

(4) Except XS4P18●●●.

(5) Sensors are available for very low temperatures (suffix TF: -40°C, + 70°C) or very high temperatures (suffix TT: - 25°C, + 85°C). Please consult our Customer Care Centre.

Inductive proximity sensors

XS range, general purpose

Cylindrical, metal and plastic, flush mountable
and non flush mountable

Four-wire DC, solid-state NO + NC output

Wiring schemes


M12 connector




Pre-cabled

BU: Blue
BN: Brown
BK: Black
WH: White

PNP 4-wire



NPN 4-wire




Setting-up

Minimum mounting distances (mm)

Sensor	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 6.5 flush mountable XS1L06	$e \geq 3$	$e \geq 18$	$e \geq 4.5$	$d \geq 6.5 h \geq 0$
Ø 8 flush mountable XS1M08	$e \geq 3$	$e \geq 18$	$e \geq 4.5$	$d \geq 8 h \geq 0$
Ø 8 non flush mountable XS4P08	$e \geq 10$	$e \geq 30$	$e \geq 7.5$	$d \geq 24 h \geq 5$
Ø 12 flush mountable XS1N12	$e \geq 4$	$e \geq 24$	$e \geq 6$	$d \geq 12 h \geq 0$
Ø 12 non flush mountable XS4P12	$e \geq 16$	$e \geq 48$	$e \geq 12$	$d \geq 36 h \geq 8$
Ø 18 flush mountable XS1N18	$e \geq 10$	$e \geq 60$	$e \geq 15$	$d \geq 18 h \geq 0$
Ø 18 non flush mountable XS4P18	$e \geq 16$	$e \geq 96$	$e \geq 24$	$d \geq 54 h \geq 16$
Ø 30 flush mountable XS1N30	$e \geq 20$	$e \geq 120$	$e \geq 30$	$d \geq 30 h \geq 0$
Ø 30 non flush mountable XS4P30	$e \geq 60$	$e \geq 180$	$e \geq 45$	$d \geq 90 h \geq 30$

Dimensions



Flush mountable in metal

Sensor	Pre-cabled (mm)		M12 connector (mm)	
	a	b	a	b
Ø 6.5 XS1L06 stainless steel	50	—	—	—
Ø 8 XS1M08 stainless steel	51	42	62	40
Ø 12 XS1N12 brass	37	25	50	31
Ø 18 XS1N18 brass	41	29	51	28
Ø 30 XS1N30 brass	45	33	54	33

Non flush mountable in metal


Sensor	Pre-cabled (mm)		M12 connector (mm)	
	a	b	a	b
Ø 8 XS2M08 stainless steel	54	42	65	40
Ø 8 XS4P08 plastic	34	25	—	—
Ø 12 XS4P12 plastic	37	25	50	31
Ø 18 XS4P18 plastic	41	29	51	28
Ø 30 XS4P30 plastic	45	33	54	33

Inductive proximity sensors

XS range, general purpose

Cylindrical, metal, increased range, flush mountable


Four-wire DC, solid-state NO + NC output



XS1●●B3PCL2



XS112B3PCM12



XSZB●●●

Sensors, 4-wire

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1					
2.5	NO + NC	PNP	Pre-cabled (L = 2 m)	XS608B1PCL2	0.035
			M12 connector	XS608B1PCM12	0.025

Ø 12, threaded M12 x 1

4	NO + NC	PNP	Pre-cabled (L = 2 m)	XS112B3PCL2	0.070
			M12 connector	XS112B3PCM12	0.020

Ø 18, threaded M18 x 1

8	NO + NC	PNP	Pre-cabled (L = 2 m)	XS118B3PCL2	0.100
			M12 connector	XS118B3PCM12	0.040

Ø 30, threaded M30 x 1.5

15	NO + NC	PNP	Pre-cabled (L = 2 m)	XS130B3PCL2	0.160
			M12 connector	XS130B3PCM12	0.100

Accessories (1)

Description	For use with sensors	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108	0.006
	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

(1) For further information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, metal, increased range, flush mountable

Four-wire DC, solid-state NO + NC output

Characteristics			
Sensor type		XS1●●B3PCM12 / XS608B1PCM12	XS1●●B3PCL2 / XS608B1PCL2
Product certifications		UL, CSA, CE, E2	
Conformity to safety standards only for Ø 12 to Ø 30		EN/IEC 61508: SIL 2 EN/ISO 13849-1: PL = d IEC 62061: SILcl2	
Reliability data only for Ø 12 to Ø 30		MTTFd = 1829 years, PFHd = 62 10 ⁻⁹ 1/h, SFF > 92 %, DC > 74 % (with a safety controller)	
Connection	Connector	M12	—
	Pre-cabled	—	Length 2 m
Operating zone (1)	Ø 8	mm	0...2
	Ø 12	mm	0...3.2
	Ø 18	mm	0...6.4
	Ø 30	mm	0...12
Differential travel		1...15 of effective sensing distance (Sr)	
Degree of protection	Conforming to IEC 60529	IP 65 and IP 67	IP 65 and IP 68, double insulation □
	Conforming to DIN 40050	IP 69K	—
Storage temperature		°C -40...+85	
Operating temperature		°C -25...+70 (2)	
Materials	Case	Nickel plated brass for Ø 12 to Ø 30, stainless steel grade 303 for Ø 8	
	Sensing face	PPS	
	Cable	—	PvR 4 x 0.22 mm ² except Ø 8: 4 x 0.08 mm ²
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED, 4 viewing ports at 90°	Yellow LED, annular
Rated supply voltage		V --- 12...24 (XS1), --- 12...48 (XS6), with protection against reverse polarity	
Voltage limits (including ripple)		V --- 9...36	
Switching capacity		mA ≤ 200 with overload and short-circuit protection	
Voltage drop, closed state		V ≤ 2	
Current consumption, no-load		mA ≤ 10	
Maximum switching frequency	Ø 8 and Ø 12	Hz	2500
	Ø 18	Hz	1000
	Ø 30	Hz	500
Delays	First-up	ms	≤ 10
	Response	ms	≤ 0.2 for Ø 8 and Ø 12, ≤ 0.3 for Ø 18, ≤ 0.6 for Ø 30
	Recovery	ms	≤ 0.2 for Ø 8 and Ø 12, ≤ 0.7 for Ø 18, ≤ 1.4 for Ø 30

Wiring schemes


M12 connector



Pre-cabled




BU: Blue
BN: Brown
BK: Black
WH: White

PNP 4-wire




Setting-up

Minimum mounting distances (mm)



Sensors	Side by side	Face to face	Facing a metal object
Ø 8	e ≥ 5	e ≥ 30	e ≥ 8
Ø 12	e ≥ 8	e ≥ 50	e ≥ 12
Ø 18	e ≥ 16	e ≥ 100	e ≥ 25
Ø 30	e ≥ 30	e ≥ 180	e ≥ 45

Dimensions



Sensors	Pre-cabled (mm)		M12 connector (mm)	
	a	b	a	b
Ø 8	51	42	61	40
Ø 12	37	25	50	31
Ø 18	41	29	51	28
Ø 30	45	33	54	33

(1) Detection curves, see page 122.

(2) Sensors are available for very low temperatures (suffix **TF**: -40°C, +70°C) or very high temperatures (suffix **TT**: -25°C, +85°C).
Please consult our Customer Care Centre.


(3) LED.

Inductive proximity sensors


XS range, general purpose

Cylindrical, metal and plastic, flush and non flush mountable


Four-wire DC, solid-state PNP + NPN NO/NC programmable output




XS1M12KP340
XS4P12KP340




XS2M12KP340



XS1M18KP340D
XS4P18KP340D



XS2M18KP340D



XSZB112

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 12, threaded M12 x 1					
Metal case, flush mountable					
2	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS1M12KP340	0.075
			M12 connector	XS1M12KP340D	0.025
Metal case, non flush mountable					
4	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS2M12KP340	0.075
			M12 connector	XS2M12KP340D	0.025
Plastic case, non flush mountable					
4	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS4P12KP340	0.075
			M12 connector	XS4P12KP340D	0.025
Ø 18, threaded M18 x 1					
Metal case, flush mountable					
5	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS1M18KP340	0.120
			M12 connector	XS1M18KP340D	0.060
Metal case, non flush mountable					
8	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS2M18KP340	0.120
			M12 connector	XS2M18KP340D	0.060
Plastic case, non flush mountable					
8	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS4P18KP340	0.120
			M12 connector	XS4P18KP340D	0.060
Ø 30, threaded M30 x 1.5					
Metal case, flush mountable					
10	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS1M30KP340	0.205
			M12 connector	XS1M30KP340D	0.145
Metal case, non flush mountable					
15	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS2M30KP340	0.205
			M12 connector	XS2M30KP340D	0.145
Plastic case, non flush mountable					
15	NO/NC programmable	PNP + NPN	Pre-cabled (L = 2 m) (1)	XS4P30KP340	0.205
			M12 connector	XS4P30KP340D	0.145
Accessories (2)					
Description mm				Reference	Weight kg
Fixing clamps		Ø 12	XSZB112	0.006	
		Ø 18	XSZB118	0.010	
		Ø 30	XSZB130	0.020	

(1) For a 5 m long cable add **L1** to the reference; for a 10 m long cable add **L2** to the reference.
Example: **XS1M12KP340** becomes **XS1M12KP340L1** with a 5 m long cable.

(2) For further information, see page 118.

Inductive proximity sensors

XS range, general purpose

Cylindrical, metal and plastic, flush and non flush mountable

Four-wire DC, solid-state PNP + NPN NO/NC
programmable output

Characteristics					
Sensor type			XS●M●●KP340D		XS●M●●KP340
Product certifications			UL, CSA, CE		
Connection			M12 connector		Pre-cabled, length: 2 m
Operating zone	Ø 12 flush mountable	mm	0...1.6		
	Ø 12 non flush mountable	mm	0...3.2		
	Ø 18 flush mountable	mm	0...4		
	Ø 18 non flush mountable	mm	0...6.4		
	Ø 30 flush mountable	mm	0...8		
	Ø 30 non flush mountable	mm	0...12		
Differential travel			%		1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529		IP 67		IP 68, double insulation
Storage temperature			°C		- 40...+ 85
Operating temperature			°C		- 25...+ 70
Materials	Case	Nickel plated brass for XS1M and XS2M, PPS for XS4P			
	Cable		–		PvR 4 x 0.34 mm²
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)		
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms		
Output state indication			Yellow LED, 4 viewing ports at 90°		Yellow LED, annular
Rated supply voltage			V		≐ 12...24 with protection against reverse polarity
Voltage limits (including ripple)			V		≐ 10...36
Switching capacity			mA		≤ 200 with overload and short-circuit protection
Voltage drop, closed state			V		≤ 2.6
Current consumption, no-load			mA		≤ 10
Maximum switching frequency	Ø 12	Hz	5000		
	Ø 18	Hz	2000		
	Ø 30 flush mountable	Hz	1000		
	Ø 30 non flush mountable	Hz	1000		
Delays	First-up	ms	≤ 5		
	Response	ms	≤ 0.1 for Ø 12, ≤ 0.15 for Ø 18, ≤ 0.3 for Ø 30		
	Recovery	ms	≤ 0.1 for Ø 12, ≤ 0.35 for Ø 18, ≤ 0.7 for Ø 30		

Wiring schemes

M12 connector	Pre-cabled	PNP + NPN	
	BU: Blue BN: Brown BK: Black WH: White	4-wire programmable, NO or NC output	
		PNP 	NPN

Setting-up

Sensor	Minimum mounting distances (mm)			
	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 12 flush mountable XS1M12	e ≥ 4	e ≥ 24	e ≥ 6	d ≥ 12 h ≥ 0
Ø 12 non flush mountable XS2M12 and XS4P12	e ≥ 16	e ≥ 48	e ≥ 12	d ≥ 36 h ≥ 8
Ø 18 flush mountable XS1M18	e ≥ 10	e ≥ 60	e ≥ 15	d ≥ 18 h ≥ 0
Ø 18 non flush mountable XS2M18 and XS4P18	e ≥ 16	e ≥ 96	e ≥ 24	d ≥ 54 h ≥ 16
Ø 30 flush mountable XS1M30	e ≥ 20	e ≥ 120	e ≥ 30	d ≥ 30 h ≥ 0
Ø 30 non flush mountable XS2M30 and XS4P30	e ≥ 60	e ≥ 180	e ≥ 45	d ≥ 90 h ≥ 30

Dimensions

Sensor	Flush mountable in metal				Non flush mountable in metal				
	Pre-cabled		Connector		Pre-cabled		Connector		
	a	b	a	b	a	b	a	b	c
Ø 12 metal	54	42	61	42	55	42	66	42	5
Ø 12 plastic	—	—	—	—	54	42	61	43	0
Ø 18 metal	60	51	72	51	60	44	72	44	8
Ø 18 plastic	—	—	—	—	60	51	70	51	0
Ø 30 metal	60	51	72	51	63	41	75	41	13
Ø 30 plastic	—	—	—	—	60	51	70	51	0


Inductive proximity sensors

XS range, general purpose


Plastic, cylindrical, non flush mountable

Two-wire AC or DC


Three-wire DC, solid-state output



XS4P●●●●340
 XS4P●●●●370
 XS4P●●●●230



XS4P●●●●340D
 XS4P●●●●370D
 XS4P●●●●230K



XS4P08●●●340S

Sensing dist. (Sn) mm	Function	Output	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1					
Three-wire ⋮ 12-24 V					
2.5	NO	PNP	Pre-cabled (L = 2 m) (1) (2)	XS4P08PA340	0.025
		NPN	Pre-cabled (L = 2 m) (1) (2)	XS4P08NA340	0.025
	NC	PNP	Pre-cabled (L = 2 m) (1) (2)	XS4P08PB340	0.025
		NPN	Pre-cabled (L = 2 m) (1) (2)	XS4P08NB340	0.025
Three-wire ⋮ 12-48 V					
2.5	NO	PNP	Pre-cabled (L = 2 m) (1)	XS4P08PA370	0.030
Two-wire ~ or ⋮ 24-240 V					
2.5	NO		Pre-cabled (L = 2 m) (1)	XS4P08MA230	0.030
			1/2"-20UNF connector	XS4P08MA230K	0.020
	NC		Pre-cabled (L = 2 m) (1)	XS4P08MB230	0.030
			1/2"-20UNF connector	XS4P08MB230K	0.020
Ø 12, threaded M12 x 1					
Three-wire ⋮ 12-24 V					
4	NO	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P12PA340	0.060
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P12NA340	0.060
	NC	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P12PB340	0.060
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P12NB340	0.060
Three-wire ⋮ 12-48 V					
4	NO	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P12PA370	0.065
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P12NA370	0.065
	NC	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P12PB370	0.065
		NPN	Pre-cabled (L = 2 m) (3)	XS4P12NB370	0.065
Two-wire ~ or ⋮ 24-240 V					
4	NO		Pre-cabled (L = 2 m) (1)	XS4P12MA230	0.065
			1/2"-20UNF connector	XS4P12MA230K	0.030
	NC		Pre-cabled (L = 2 m) (1)	XS4P12MB230	0.065
			1/2"-20UNF connector	XS4P12MB230K	0.030
Ø 18, threaded M18 x 1					
Three-wire ⋮ 12-24 V					
8	NO	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P18PA340	0.090
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P18NA340	0.090
	NC	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P18PB340	0.090
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P18NB340	0.090
Three-wire ⋮ 12-48 V					
8	NO	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P18PA370	0.100
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P18NA370	0.100
	NC	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P18PB370	0.100
		NPN	Pre-cabled (L = 2 m) (3)	XS4P18NB370	0.100
Two-wire ~ or ⋮ 24-240 V					
8	NO		Pre-cabled (L = 2 m) (1)	XS4P18MA230	0.100
			1/2"-20UNF connector	XS4P18MA230K	0.040
	NC		Pre-cabled (L = 2 m) (1)	XS4P18MB230	0.100
			1/2"-20UNF connector	XS4P18MB230K	0.040
Ø 30, threaded M30 x 1.5					
Three-wire ⋮ 12-24 V					
15	NO	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P30PA340	0.120
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P30NA340	0.120
	NC	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P30PB340	0.120
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P30NB340	0.120
Three-wire ⋮ 12-48 V					
15	NO	PNP	Pre-cabled (L = 2 m) (1) (3)	XS4P30PA370	0.140
		NPN	Pre-cabled (L = 2 m) (1) (3)	XS4P30NA370	0.140
	NC	PNP	Pre-cabled (L = 2 m) (3)	XS4P30PB370	0.140
		NPN	Pre-cabled (L = 2 m) (3)	XS4P30NB370	0.140
Two-wire ~ or ⋮					
15	NO		Pre-cabled (L = 2 m) (1)	XS4P30MA230	0.140
			1/2"-20UNF connector	XS4P30MA230K	0.080
	NC		Pre-cabled (L = 2 m) (1)	XS4P30MB230	0.140
			1/2"-20UNF connector	XS4P30MB230K	0.080

(1) For a 5 m long cable add **L1** to the reference; for a 10 m long cable add **L2** to the reference. Example: **XS4P08PA340** becomes **XS4P08PA340L1** with a 5 m long cable.

(2) For an M8 connector, add **S** to the reference. Example: **XS4P08PA340** becomes **XS4P08PA340S** with an M8 connector.

(3) For an M12 connector, add **D** to the reference. Example: **XS4P12PA370** becomes **XS4P12PA370D** with an M12 connector.

Inductive proximity sensors

XS range, general purpose






Plastic, cylindrical, non flush mountable

Two-wire AC or DC

Three-wire DC, solid-state output







Characteristics			
Sensor type		XS4P●●●●340●	XS4P●●●●370●
Product certifications		UL, CSA, CE, ECOLAB	
Connection	Pre-cabled	Length: 2 m	
	Connector	M8 on Ø 8 M12 on Ø 12, Ø 18 and Ø 30	1/2"-20UNF
Operating zone	Ø 8	mm	0...2
	Ø 12	mm	0...3.2
	Ø 18	mm	0...6.4
	Ø 30	mm	0...12
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection		Conforming to IEC 60529	IP 68, double insulation for pre-cabled version (except Ø 8: IP 67) IP 67 for connector version
Storage temperature		°C	- 40...+ 85
Operating temperature		°C	- 25...+ 70
Materials	Case	PPS	
	Cable	PvR 3 x 0.34 mm ² except Ø 8: 3 x 0.11 mm ²	PvR 2 x 0.34 mm ² except Ø 8: 2 x 0.11 mm ²
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms
Output state indication		Yellow LED: annular on pre-cabled version Yellow LED: 4 viewing ports at 90° on connector version	
Rated supply voltage		V	~ 12...24 with protection against reverse polarity
Voltage limits (including ripple)		V	~ 10...36
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Residual current, open state		mA	–
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	Ø 8 and Ø 12	Hz	5000
	Ø 18	Hz	2000
	Ø 30	Hz	1000
		ms	1000, ~ 25
Delays	First-up	ms	≤ 10
	Response	ms	≤ 0.1 for Ø 8 and Ø 12, ≤ 0.15 for Ø 18, ≤ 0.3 for Ø 30
	Recovery	ms	≤ 0.1 for Ø 8 and Ø 12, ≤ 0.35 for Ø 18, ≤ 0.7 for Ø 30
			≤ 0.2 for Ø 8, Ø 12 and Ø 18, ≤ 0.4 for Ø 30

Wiring schemes

Connector	Pre-cabled	PNP	NPN	2-wire ~ or ~
 M8 1 4 3 2	BU: Blue BN: Brown BK: Black	 BN/1 PNP BK/4 (NO) BK/2 (NC) BU/3	 BN/1 NPN BK/4 (NO) BK/2 (NC) BU/3	 BN/2 BU/3
 M12 1 4 3 2				
 1/2"-20UNF 2 3				


For M8 connector, NO and NC outputs on terminal 4

Setting-up

Minimum mounting distances (mm)				
	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 8	 e ≥ 10	 e ≥ 30	 e ≥ 7.5	 d ≥ 24 h ≥ 5
Ø 12	 e ≥ 16	 e ≥ 48	 e ≥ 12	 d ≥ 36 h ≥ 8
Ø 18	 e ≥ 16	 e ≥ 96	 e ≥ 24	 d ≥ 54 h ≥ 16
Ø 30	 e ≥ 60	 e ≥ 180	 e ≥ 45	 d ≥ 90 h ≥ 30

Dimensions

		3-wire ~ 12-24 V				3-wire ~ 12-48 V or 2-wire ~/- 24-240 V			
		Pre-cabled (mm)		Connector (mm)		Pre-cabled (mm)		Connector (mm)	
XS4P		a	b	a	b	a	b	a	b
Ø 8		33	26	42	26	50	42	61	40
Ø 12		35	25	48	27	54	42	61	42
Ø 18		36	25	48	29	62	52	70	52
Ø 30		43	32	50	34	62	52	70	52




Inductive proximity sensors


XS range, general purpose

Cylindrical, almost flush mountable, increased range

Three-wire DC, solid-state output




XS1N●●●●349



XS1N08●●●349S



XS1N●●●●349D



XSZB1●●

References

Sensing distance (Sn) (mm)	Function	Output	Connection	Reference	Weight kg
Ø 8, threaded M8 x 1					
2.5	NO	PNP	Pre-cabled (L = 2 m)	XS1N08PA349	0.035
			M8 connector	XS1N08PA349S	0.015
			M12 connector	XS1N08PA349D	0.020
	NC	PNP	Pre-cabled (L = 2 m)	XS1N08PB349	0.035
			M8 connector	XS1N08PB349S	0.015
			M12 connector	XS1N08PB349D	0.020
Ø 12, threaded M12 x 1					
4	NO	PNP	Pre-cabled (L = 2 m)	XS1N12PA349	0.070
			M12 connector	XS1N12PA349D	0.020
		NPN	Pre-cabled (L = 2 m)	XS1N12NA349	0.070
			M12 connector	XS1N12NA349D	0.020
	NC	PNP	Pre-cabled (L = 2 m)	XS1N12PB349	0.070
			M12 connector	XS1N12PB349D	0.020
		NPN	Pre-cabled (L = 2 m)	XS1N12NB349	0.070
			M12 connector	XS1N12NB349D	0.020
Ø 18, threaded M18 x 1					
10	NO	PNP	Pre-cabled (L = 2 m)	XS1N18PA349	0.100
			M12 connector	XS1N18PA349D	0.040
		NPN	Pre-cabled (L = 2 m)	XS1N18NA349	0.100
			M12 connector	XS1N18NA349D	0.040
	NC	PNP	Pre-cabled (L = 2 m)	XS1N18PB349	0.100
			M12 connector	XS1N18PB349D	0.040
		NPN	Pre-cabled (L = 2 m)	XS1N18NB349	0.100
			M12 connector	XS1N18NB349D	0.040
Ø 30, threaded M30 x 1.5					
20	NO	PNP	Pre-cabled (L = 2 m)	XS1N30PA349	0.160
			M12 connector	XS1N30PA349D	0.100
		NPN	Pre-cabled (L = 2 m)	XS1N30NA349	0.160
			M12 connector	XS1N30NA349D	0.100
	NC	PNP	Pre-cabled (L = 2 m)	XS1N30PB349	0.160
			M12 connector	XS1N30PB349D	0.100
		NPN	Pre-cabled (L = 2 m)	XS1N30NB349	0.160
			M12 connector	XS1N30NB349D	0.100

Accessories (1)

Description mm	Reference	Weight kg
Fixing clamps	Ø 8	XSZB108 0.006
	Ø 12	XSZB112 0.006
	Ø 18	XSZB118 0.010
	Ø 30	XSZB130 0.020

(1) For further information, see page 118.


Inductive proximity sensors

XS range, general purpose









Cylindrical, almost flush mountable, increased range

Three-wire DC, solid-state output


Characteristics			
Sensor type		XS1.....349D	XS1.....349S
Product certifications		UL, CSA, CEC	
Connection		M12 connector	Pre-cabled, length: 2 m
Operating zone	Ø 8	mm	0...2
	Ø 12	mm	0...3.2
	Ø 18	mm	0...8
	Ø 30	mm	0...16
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 67	
	Conforming to DIN 40050	IP 69K for Ø 12 to Ø 30	
Storage temperature		°C	- 40...+ 85
Operating temperature		°C	- 25...+ 70
Materials	Case	Nickel plated brass	
	Cable	PvR 3 x 0.34 mm ² except Ø 8: 3 x 0.11 mm ²	
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED, 4 viewing ports at 90°	
Rated supply voltage		V	12...24 with protection against reverse polarity
Voltage limits (including ripple)		V	10...36
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	Ø 8 and Ø 12	Hz	2500
	Ø 18	Hz	1000
	Ø 30	Hz	500
Delays	First-up	ms	≤ 5
	Response	ms	≤ 0.2 for Ø 8 and Ø 12, ≤ 0.3 for Ø 18, ≤ 0.6 for Ø 30
	Recovery	ms	≤ 0.2 for Ø 8 and Ø 12, ≤ 0.7 for Ø 18, ≤ 1.4 for Ø 30

Wiring schemes			
Connector	Pre-cabled	PNP 3-wire	NPN 3-wire
 	BU: Blue BN: Brown BK: Black		

For M8 connector, NO and NC outputs on terminal 4

Setting-up precautions				
Sensor	Minimum mounting distances (mm)			
	Side by side	Face to face	Facing a metal object	Mounted in a metal support
Ø 8	 e ≥ 5	 e ≥ 30	 e ≥ 7.5	 d ≥ 10 h ≥ 1.6
Ø 12	 e ≥ 8	 e ≥ 48	 e ≥ 12	 d ≥ 14 h ≥ 2.4
Ø 18	 e ≥ 20	 e ≥ 96	 e ≥ 30	 d ≥ 28 h ≥ 3.6
Ø 30	 e ≥ 40	 e ≥ 240	 e ≥ 60	 d ≥ 50 h ≥ 6

Dimensions						
Sensor	Flush mountable in metal					
	Pre-cabled		M8 connector		M12 connector	
	a	b	a	b	a	b
Ø 8	33	25	42	26	45	23
Ø 12	35	25	—	—	50	30
Ø 18	39	28	—	—	50	28
Ø 30	43	32	—	—	55	32




Inductive proximity sensors


XS range, general purpose

Miniature, cylindrical, flush mountable


Three-wire DC, solid-state output




XS1L04●●310



XS1N05●●310



XS1N05●●311S



XS1L04●●310S

Ø 4 plain ⁽¹⁾

Sensing distance (Sn) mm	Function	Output	Connection (2)	Reference	Weight kg
Brass case, flush mountable					
1	NO	PNP	Pre-cabled (L = 2 m)	XS1L04PA310	0,025
			M8 connector	XS1L04PA310S	0.010
	NPN	NPN	Pre-cabled (L = 2 m)	XS1L04NA310	0.025
			M8 connector	XS1L04NA310S	0.010
	NC	PNP	Pre-cabled (L = 2 m)	XS1L04PB310	0.025
			M8 connector	XS1L04PB310S	0.010
		NPN	Pre-cabled (L = 2 m)	XS1L04NB310	0.025
			M8 connector	XS1L04NB310S	0.010

Stainless steel case, flush mountable

0,8	NO	PNP	Pre-cabled (L = 2 m)	XS1L04PA311	0.025
			M8 connector	XS1L04PA311S	0.010
	NPN	NPN	Pre-cabled (L = 2 m)	XS1L04NA311	0.025
			M8 connector	XS1L04NA311S	0.010
	NC	PNP	Pre-cabled (L = 2 m)	XS1L04PB311	0.025
			M8 connector	XS1L04PB311S	0.010
		NPN	Pre-cabled (L = 2 m)	XS1L04NB311	0.025
			M8 connector	XS1L04NB311S	0.010

Ø 5, threaded M5 x 0.5 ⁽¹⁾

Sensing distance (Sn) mm	Function	Output	Connection (2)	Reference	Weight kg
Brass case, flush mountable					
1	NO	PNP	Pre-cabled (L = 2 m)	XS1N05PA310	0,030
		NPN	Pre-cabled (L = 2 m)	XS1N05NA310	0,030
	NC	PNP	Pre-cabled (L = 2 m)	XS1N05PB310	0,030
		NPN	Pre-cabled (L = 2 m)	XS1N05NB310	0,030

Stainless steel case, flush mountable

0.8	NO	PNP	Pre-cabled (L = 2 m)	XS1N05PA311	0.030
			M8 connector	XS1N05PA311S	0.015
	NPN	NPN	Pre-cabled (L = 2 m)	XS1N05NA311	0.030
			M8 connector	XS1N05NA311S	0.015
	NC	PNP	Pre-cabled (L = 2 m)	XS1N05PB311	0.030
			M8 connector	XS1N05PB311S	0.015
		NPN	Pre-cabled (L = 2 m)	XS1N05NB311	0.030
			M8 connector	XS1N05NB311S	0.015

(1) For accessories, see page 118.

(2) For a 5 m long cable add **L1** to the reference; for a 10 m long cable add **L2** to the reference.

Example: **XS1L04PA310** becomes **XS1L04PA310L1** with a 5 m long cable.

Inductive proximity sensors



XS range, general purpose








Miniature, cylindrical, flush mountable

Three-wire DC, solid-state output


Characteristics				
Sensor type			XS1●●●●●●●S	XS1●●●●●●●
Product certifications			UL, CSA, Cc	
Connection (1)	Connector		M8 on XS1●●●●●●●S	—
	Pre-cabled		—	Length: 2 m
Operating zone	Ø 4	mm	0...0.8 (brass), 0...0.6 (stainless steel)	
	Ø 5	mm	0...0.8 (brass), 0...0.6 (stainless steel)	
Degree of protection	Conforming to IEC 60529		IP 67	
Storage temperature			°C	- 40...+ 85
Operating temperature			°C	- 25...+ 70
Materials	Case	Nickel plated brass or stainless steel 303		
	Cable	PvR 3 x 0.11 mm²		
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms	
Output state indication			Yellow LED, 4 viewing ports at 90°	Yellow LED, annular
Rated supply voltage			V	— 5...24 for XS1L04●●●●●●● and XS1N05●●●●●●●
Voltage limits (including ripple)			V	— 5...30 for XS1L04●●●●●●● and XS1N05●●●●●●●
Current consumption, no-load			mA	≤ 10
Switching capacity	3-wire PNP/NPN		mA	≤ 100 with overload and short-circuit protection
Voltage drop, closed state			V	≤ 2
Maximum switching frequency			kHz	5
Delays	First-up	ms	≤ 5	
	Response	ms	≤ 0.1	
	Recovery	ms	≤ 0.1	

(1) Detection curves, see page 122

Wiring schemes				
Connector	Pre-cabled	PNP 3-wire	NPN 3-wire	
M8 	BU: Blue BN: Brown BK: Black			

Setting-up				
Minimum mounting distances (mm)				
Sensor	Side by side	Face to face	Facing a metal object	
Ø 4	 e ≥ 2	 e ≥ 12	 e ≥ 3	 d1 ≥ 4, h ≥ 0
Ø 5	 e ≥ 2	 e ≥ 12	 e ≥ 3	 d1 ≥ 5, h ≥ 0

Tightening torque	
Stainless steel: 2.2 N.m. Brass: 1.6 N.m (values obtained with washers mounted)	

Dimensions				
	Sensor	Pre-cabled		M8 connector
		a	b	a
	Ø 4	28	—	43
	Ø 5	28	24	43

Inductive proximity sensors

XS range

Flush mountability using teach mode: simplicity through innovation

Operating principle

In proposing flush mountable sensors using teach mode, Telemecanique Sensors offers simplicity through innovation.

■ A single product enables flush mounting using teach mode and meets all the requirements for inductive detection of metal objects.
By simply pressing the "Teach mode" button, the sensor automatically acquires optimum configuration for all detection, flush mountability and environment requirements.

■ Other advantages of flush mountable sensors using teach mode

□ Increased performance:


- sensing distance guaranteed and optimised irrespective of the mounting method, object, environment or background,
- suitable for all metal environments.

□ Simplified use provided by:

- the flush mountability using teach mode technology, associated with the availability of the flattest and most compact sensors on the market, ensures full integration in the machine and limits the risks of mechanical damage,
- mechanical adjustments no longer necessary due to teach mode.

□ Lower costs due to:

- the elimination of adjustment times and complex supports
- the elimination of flush mountable and non flush mountable versions, which halves the number of references,
- much easier and much quicker product selection.



Precision position detection


All flush mountable inductive proximity sensors using teach mode benefit from ultra precise adjustment, which is very quick irrespective of the metal environment.

■ Precision side approach detection makes it possible to accurately define the distance at which the object will be detected as it passes the sensor.

On the flush mountable sensors using teach mode, the desired detection position can be stored in memory by simply pressing the teach button.

■ Precision frontal approach detection makes it possible to accurately define the distance at which the object will be detected as it approaches the sensor.

On the flush mountable sensors using teach mode, the desired detection position can be stored in memory by simply pressing the teach button.




Mounting accessories

Telemecanique Sensors offers a complete, inexpensive range of mounting accessories (clamps, plates, brackets, etc.) that provide solutions for all installation problems.

■ Fixing kits for quick installation or replacement of sensors

■ No adjustment required. Simple clipping-in enables the sensor to be fixed in position and ready for operation.



Inductive proximity sensors

XS range

Flush mountability using teach mode:
simplicity through innovation



Cylindrical type

Dimensions (mm)	12	18	30
Sensing distance (mm)	Flush mounted use	0...3.4	0...6
	Non flush mounted use	0...5	0...9
Sensor type	XS612B2	XS618B2	XS630B2
Page	72		

Block type

Dimensions (mm)	26 x 26 x 13	40 x 40 x 15	80 x 80 x 26
Sensing distance (mm)	Flush mounted use	0...10	0...15
	Non flush mounted use	0...15	0...25
Sensor type	XS8E1A1	XS8C1A1	XS8D1A1
Page	74		


Inductive proximity sensors

XS range, Application


Adjustable range sensors

Cylindrical, flush mountable using teach mode ⁽¹⁾


Three-wire DC, solid-state output



XS6●●B2●●L01M12



XSZBPM12



XSZB●●●

Ø 12, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
5	NO	PNP	Remote M12 connector on 0.15 m flying lead	XS612B2PAL01M12	0.100
		NPN	Remote M12 connector on 0.15 m flying lead	XS612B2NAL01M12	0.100
	NC	PNP	Remote M12 connector on 0.15 m flying lead	XS612B2PBL01M12	0.100
		NPN	Remote M12 connector on 0.15 m flying lead	XS612B2NBL01M12	0.100

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
9	NO	PNP	Remote M12 connector on 0.15 m flying lead	XS618B2PAL01M12	0.140
		NPN	Remote M12 connector on 0.15 m flying lead	XS618B2NAL01M12	0.140
	NC	PNP	Remote M12 connector on 0.15 m flying lead	XS618B2PBL01M12	0.140
		NPN	Remote M12 connector on 0.15 m flying lead	XS618B2NBL01M12	0.140

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
18	NO	PNP	Remote M12 connector on 0.15 m flying lead	XS630B2PAL01M12	0.220
		NPN	Remote M12 connector on 0.15 m flying lead	XS630B2NAL01M12	0.220
	NC	PNP	Remote M12 connector on 0.15 m flying lead	XS630B2PBL01M12	0.220
		NPN	Remote M12 connector on 0.15 m flying lead	XS630B2NBL01M12	0.220

Accessories ⁽²⁾

Description	Reference	Weight kg
Remote control fixing clamp	XSZBPM12	0.015
Sensor fixing clamps	Ø 12 XSZB112	0.006
	Ø 18 XSZB118	0.010
	Ø 30 XSZB130	0.020

(1) For further information on flush or non flush mountable sensors using teach mode, see page 70.

(2) For further information, see page 118.

Inductive proximity sensors

XS range, Application

Adjustable range sensors

Cylindrical, flush mountable using teach mode

Three-wire DC, solid-state output

Characteristics			
Sensor type		XS6●●B2●●L01M12	
Product certifications		UL, CSA, CE	
Connection	Connector	Remote M12 connector on 0.15 m flying lead	
Sensing distance and adjustment zone	Ø 12	Nominal sensing distance (Sn)	mm 0...5 non flush mounted / 0...3.4 flush mounted
		Precision adjustment zone	mm 1.7...5 non flush mounted / 1.7...3.4 flush mounted
	Ø 18	Nominal sensing distance (Sn)	mm 0...9 non flush mounted / 0...6 flush mounted
		Precision adjustment zone	mm 3...9 non flush mounted / 3...6 flush mounted
	Ø 30	Nominal sensing distance (Sn)	mm 0...18 non flush mounted / 0...11 flush mounted
		Precision adjustment zone	mm 6...18 non flush mounted / 6...11 flush mounted
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection		Conforming to IEC 60529	IP 67, 
Storage temperature		°C	- 40...+ 85
Operating temperature		°C	- 25...+ 70
Materials	Case	Nickel plated brass	
	Remote control	PBT	
	Cable	PvR - Ø 4.2 mm	
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance		Conforming to IEC 60068-2-27	50 gn, duration 11 ms
Indicators	Output state	Yellow LED	
	Supply on and teach mode	Green LED	
Rated supply voltage		V	 12...24 with protection against reverse polarity
Voltage limits (including ripple)		V	 10...36
Switching capacity		mA	≤ 100 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency		Hz	1000
Delays	First-up	ms	≤ 10
	Response	ms	≤ 0.3
	Recovery	ms	≤ 0.7

Wiring schemes	
Connector	
M12	
PNP	
NPN	

Setting-up			
Minimum mounting distances (mm)			
	Side by side		Facing a metal object
	flush mounted	not flush mounted	
Ø 12	e ≥ 14	50	e ≥ 3.4
Ø 18	e ≥ 28	100	e ≥ 6
Ø 30	e ≥ 48	180	e ≥ 11
	Face to face		
	flush mounted	not flush mounted	
Ø 12	e ≥ 50	100	
Ø 18	e ≥ 100	200	
Ø 30	e ≥ 180	360	

Dimensions			
XS6			
(1) Teach mode button (2) LED			
Connector (mm)			
	a	b	c
Ø 12	59	42	5
Ø 18	64	44	8
Ø 30	62.6	41	13


Inductive proximity sensors

XS range, general purpose with increased range

 Flat, flush mountable using teach mode ⁽¹⁾

Two-wire AC or DC

Three-wire DC, solid-state output



Flat, 26 x 26 x 13 mm format ⁽²⁾

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire --- with overload and short-circuit protection					
15	NO	PNP	Pre-cabled (L = 2 m) (3)	XS8E1A1PAL2	0.075
			M8 connector	XS8E1A1PAM8	0.040
			Remote M12 connector	XS8E1A1PAL01M12	0.040
	NPN	PNP	Pre-cabled (L = 2 m) (3)	XS8E1A1NAL2	0.075
			M8 connector	XS8E1A1NAM8	0.040
			Remote M12 connector	XS8E1A1NAL01M12	0.040
NC	PNP	PNP	Pre-cabled (L = 2 m) (3)	XS8E1A1PBL2	0.075
			M8 connector	XS8E1A1PBM8	0.040
			Remote M12 connector	XS8E1A1PBL01M12	0.040
	NPN	PNP	Pre-cabled (L = 2 m) (3)	XS8E1A1NBL2	0.075
			M8 connector	XS8E1A1NBM8	0.040
			Remote M12 connector	XS8E1A1NBL01M12	0.040

Two-wire ~ or --- unprotected ⁽⁴⁾

15	NO	-	Pre-cabled (L = 2 m) (3)	XS8E1A1MAL2	0.070
			Remote 1/2"-20UNF connector	XS8E1A1MAL01U20	0.040
	NC	-	Pre-cabled (L = 2 m) (3)	XS8E1A1MBL2	0.070
			Remote 1/2"-20UNF connector	XS8E1A1MBL01U20	0.040

Flat, 40 x 40 x 15 mm format ⁽²⁾

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire --- with overload and short-circuit protection					
25	NO	PNP	Pre-cabled (L = 2 m) (3)	XS8C1A1PAL2	0.095
			M8 connector	XS8C1A1PAM8	0.060
			Remote M12 connector	XS8C1A1PAL01M12	0.060
	NPN	PNP	Pre-cabled (L = 2 m) (3)	XS8C1A1NAL2	0.095
			M8 connector	XS8C1A1NAM8	0.060
			Remote M12 connector	XS8C1A1NAL01M12	0.060
NC	PNP	PNP	Pre-cabled (L = 2 m) (3)	XS8C1A1PBL2	0.095
			M8 connector	XS8C1A1PBM8	0.060
			Remote M12 connector	XS8C1A1PBL01M12	0.060
	NPN	PNP	Pre-cabled (L = 2 m) (3)	XS8C1A1NBL2	0.095
			M8 connector	XS8C1A1NBM8	0.060
			Remote M12 connector	XS8C1A1NBL01M12	0.060

Two-wire ~ or --- unprotected ⁽⁴⁾

25	NO	-	Pre-cabled (L = 2 m) (3)	XS8C1A1MAL2	0.090
			Remote 1/2"-20UNF connector	XS8C1A1MAL01U20	0.060
	NC	-	Pre-cabled (L = 2 m) (3)	XS8C1A1MBL2	0.090
			Remote 1/2"-20UNF connector	XS8C1A1MBL01U20	0.060

Flat, 80 x 80 x 26 mm format ⁽²⁾

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire --- with overload and short-circuit protection					
60	NO	PNP	Pre-cabled (L = 2 m) (3)	XS8D1A1PAL2 (5)	0.390
			M12 connector	XS8D1A1PAM12 (5)	0.340
		NPN	Pre-cabled (L = 2 m) (3)	XS8D1A1NAL2 (5)	0.390
	M12 connector		XS8D1A1NAM12 (5)	0.340	
	NC	PNP	Pre-cabled (L = 2 m) (3)	XS8D1A1PBL2 (5)	0.390
			M12 connector	XS8D1A1PBM12 (5)	0.340
NPN		Pre-cabled (L = 2 m) (3)	XS8D1A1NBL2 (5)	0.390	
		M12 connector	XS8D1A1NBM12 (5)	0.340	
Two-wire ~ or --- unprotected (4)					
60	NO	—	Pre-cabled (L = 2 m) (3)	XS8D1A1MAL2 (5)	0.390
			1/2"-20UNF connector	XS8D1A1MAU20 (5)	0.340
	NC	—	Pre-cabled (L = 2 m) (3)	XS8D1A1MBL2 (5)	0.390
			1/2"-20UNF connector	XS8D1A1MBU20 (5)	0.340

⁽¹⁾ For further information on flush or non flush mountable sensors using teach mode, see page 70.

⁽²⁾ For accessories, see page 118.

⁽³⁾ For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.

⁽⁴⁾ It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

⁽⁵⁾ For clipping onto 35 mm omega rail or 80 x 80 x 40 mm format, add DIN to the end of the reference. Example: **XS8D1A1PAL2 DIN**.

Characteristics			
Sensor type		XS8E●●●●M8, XS8C●●●●M8, XS8D●●●●M12, XS8D●●●●U20	XS8E●●●●L01M12, XS8E●●●●L01U20, XS8C●●●●L01M12, XS8C●●●●L01U20
Product certifications		UL, CSA, CE, ECOLAB	XS8E●●●●L2, XS8C●●●●L2, XS8D●●●●L2
Connection	Connector	M8 except XS8●●●●M12: M12 XS8●●●●U20: 1/2"-20UNF	Remote on 0.15 m flying lead XS8●●●●L01M12: M12 XS8●●●●L01U20: 1/2"-20UNF
	Pre-cabled	—	—
Sensing distance and adjustment zone	XS8E	Nominal sensing dist. Sn	mm 0...15 not flush mounted / 0...10 flush mounted
		Fine adjustment zone	mm 5...15 not flush mounted / 5...10 flush mounted
	XS8C	Nominal sensing dist. Sn	mm 0...25 not flush mounted / 0...15 flush mounted
		Fine adjustment zone	mm 8...25 not flush mounted / 8...15 flush mounted
	XS8D	Nominal sensing dist. Sn	mm 0...60 not flush mounted / 0...40 flush mounted
		Fine adjustment zone	mm 20...60 not flush mounted / 20...40 flush mounted
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529		IP 67, double insulation □ (except M8 connector: IP 67)
Storage temperature		°C	-40...+85
Operating temperature		°C	-25...+70
Materials	Case		PBT
	Cable		—
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance	Conforming to IEC 60068-2-27		50 gn, duration 11 ms
Indicators	Output state		Yellow LED
	Supply on and teach mode		Green LED
Rated supply voltage	3-wire	V	12...24 with protection against reverse polarity
	2-wire	V	~ or — 24...240 (~ 50/60 Hz)
Voltage limits (including ripple)	3-wire	V	10...36
	2-wire	V	~ or — 20...264
Current consumption, no-load	3-wire	mA	≤ 10
Residual current, open state	2-wire	mA	≤ 1.5
Switching capacity	3-wire	mA	≤ 100 XS8E, ≤ 200 XS8C and XS8D, with overload and short-circuit protection
	2-wire	mA	5...200 ~ XS8E, 5...300 ~ XS8C and XS8D, 5...200 — XS8C and XS8D
Voltage drop, closed state	3-wire	V	≤ 2
	2-wire	V	≤ 5.5
Maximum switching frequency		Hz	2000 XS8E, 1000 XS8C, 150 XS8D
Delays	First-up	ms	≤ 10 XS8E, XS8C and XS8D (3-wire), ≤ 10 XS8E and XS8C, ≤ 15 XS8D (2-wire)
	Response	ms	≤ 0.3
	Recovery	ms	≤ 0.8 XS8E and XS8C, ≤ 6 XS8D

Wiring schemes

Connector	Pre-cabled	PNP/M12 or M8	NPN/M12 or M8	2-wire 1/2"-20UNF
 M8 M12 1/2"-20UNF	BU: Blue BN: Brown BK: Black	 PNP/M12 or M8	 NPN/M12 or M8	 2-wire 1/2"-20UNF

For M8 connector, NO and NC outputs on terminal 4

Setting-up

Minimum mounting distances (mm)				
Side by side	e ≥	XS8E	XS8C	XS8D
Flush mounted		40	60	200
Not flush mounted		150	125	600
Face to face	e ≥	XS8E	XS8C	XS8D
Flush mounted		80	120	400
Not flush mounted		300	250	not recommended
Facing a metal object	e ≥	XS8E	XS8C	XS8D
		10	15	40

Dimensions

	XS8C/D/E		XS8C/D		XS8E	
Sensor	A (cable)	A (connector)	B	C	D	E
XS8E	14	11	26	13	8.8	20
XS8C	14	11	40	15	9.8	33
XS8D	23	18	80	26	16	65
XS8D●●DIN	23	18	80	40	30	65
						F
						G
						H

(1) LED
(2) Teach mode button
(3) For CHC type screws

Inductive proximity sensors


XS range, Application

Sensors for rotation monitoring, slip detection, shaft overload detection


Cylindrical form

Example:
Coupling breakage monitoring

822138



DF602242



Functions

These self-contained rotation speed monitoring sensors have the special feature of incorporating, in the same case, the pulse sensing and processing electronics as well as the output switching amplifier that are required to establish an integrated rotation monitoring device.

The unit provides an economical solution for detecting slip, belt breakage, drive shaft shear and overloading, etc., in the following applications: conveyor belts, bucket elevators, Archimedian screws, grinders, crushers, pumps, centrifugal driers, mixers, etc.

Operating principle

The output signal of this type of sensor is processed by an impulse comparator incorporated in the sensor. The impulse frequency F_c generated by the moving part to be monitored is compared to the frequency F_r preset on the sensor. The output switching circuit of the sensor is in the closed state for $F_c > F_r$ and the open state for $F_c < F_r$.

Sensors XSAV are particularly suitable for the detection of underspeed: when the speed of the moving part F_c falls below a preset threshold F_r , this causes the output circuit of the sensor to switch off.

Note: Following power-up, the operational status of the sensor is subject to a delay of 9 seconds in order for the moving part being monitored to run-up to its nominal speed. During this time, the output of the sensor remains in the closed state.

Adjustment of frequency threshold



- Adjustment of sensor's frequency threshold: using potentiometer, 15 turns approximately.
- To increase the frequency threshold: turn the adjustment screw clockwise (+).
- To decrease the frequency threshold: turn the adjustment screw anti-clockwise (-).

1: Potentiometer	Diameter of sensor		
2: LED	a	b	c
3: Metal target	M30	4...6 mm	30 mm
			60 mm

Potentiometer adjustment curves (for XSAV1●801, 2-wire ~ or --- sensors)

Low speed version (6...150 impulses/minute)


High speed version (120...3000 impulses/minute)



Setting-up


Minimum distances (mm)

Side by side




$e \geq 20$

Facing a metal object




$e \geq 30$

Face to face



$e \geq 120$



Mounted in a metal support



$d \geq 30, h \geq 0$

Fixing nut tightening torque: $< 50 \text{ N.m} / 442.53 \text{ lb-in}$

Flush mountable in metal



Lengths (mm):

a = Overall

b = Threaded section

a = 81

b = 67

Ø = M30

	DC	DC	AC/DC	AC/DC
Nominal sensing distance (Sn)	10 mm	10 mm	10 mm	10 mm
Adjustable frequency range	6...150 impulses/min	120...3000 impulses/min	6...150 impulses/min	120...3000 impulses/min

References


3-wire	PNP / NC	XSAV11373	XSAV12373	—	—
2-wire	— or ~ / NC	—	—	XSAV11801	XSAV12801
Weight (kg)	0.300				

Characteristics


Connection	Pre-cabled, 3 x 0.34 mm ² , length 2 m (1)	Pre-cabled, 2 x 0.34 mm ² , length 2 m (1)
Degree of protection conforming to IEC 60529	IP 67	
Operating zone	0...8 mm	
Repeat accuracy	3 % of Sr	
Differential travel	3...15 % of Fr	
Operating temperature	-25...+70 °C	
Output state indication	Red LED	
Rated supply voltage	— 12...48 V with protection against reverse polarity	~ 24...240 V (50/60 Hz) or — 24...210 V
Voltage limits (including ripple)	— 10...58 V	~ or — 20...264 V
Switching capacity	≤ 200 mA with overload and short-circuit protection	~ 5...350 mA or — 5...200 mA (2)
Voltage drop, closed state	≤ 1.8 V	≤ 5.7 V
Residual current, open state	—	≤ 1.5 mA
Current consumption, no-load	≤ 15 mA	—
Maximum switching frequency	6000 impulses/min (for XSAV11●●●); 48,000 impulses/min (for XSAV12●●●)	
"Run-up" delay following power-up	9 seconds ± 20 % + 1/Fr (3)	

Wiring schemes

3-wire —
XSAV1●373



2-wire ~ or —
XSAV1●801



(1) For a 5 m long cable add L05 to the reference, for a 10 m long cable add L10 to the reference.

Example: XSAV11373 becomes XSAV11373L05 with a 5 m long cable.

(2) These sensors do not incorporate overload or short-circuit protection and therefore, it is essential to connect a 0.4 A "quick-blow" fuse in series with the load, see page 118.


(3) For a sensor without a "run-up" delay following power-up, replace XSAV1 in the reference by XSAV0. Example: XSAV11801 becomes XSAV01801 without a "run-up" delay. For a reduced "run-up" delay of 3 s, replace XSAV1 in the reference by XSAV3.

Inductive proximity sensors

XS range, Application


Sensors for rotation monitoring, slip detection and shaft overload detection, with teach mode

Operating principle and applications



- These inductive proximity sensors are designed for monitoring rotational speed or the speed of the flow of objects to be protected or monitored. They operate on the principle of comparing a speed threshold preset by the operator against the instantaneous measurement of the speed of the moving object to be protected.
- They provide a simple, economical solution for detecting slip, belt breakage, coupling breakage and overload, etc.
- They are widely used in grinder/crusher, mixer, pump, centrifugal driver, conveyor belt, bucket elevator, Archimedeian screw, etc. type applications.

Installation and setting-up



Setting-up and positioning the sensor

- In the positioning phase, the XS9 sensor can operate as a standard inductive sensor (Schneider Electric patent). Operation in inductive mode enables validation of reliable detection of all the moving objects to be monitored.
- Using this system, the positioning is therefore made 100 % reliable and can be checked at any time without altering the settings of the sensor.

Speed adjustment in teach mode

- The normal or reference speed of the moving object (1) to be monitored is adjusted by simply pressing the teach mode button (2) and is then validated by the display LED.
- If in doubt, the sensor can be reset at any time to the factory settings.
- (1) To allow the moving object to reach its normal speed (machine inertia), the sensor holds its output closed for 9 seconds.
- (2) The sensor's default drop-out underspeed corresponds to the preset speed - 30 %.

Example: If the preset speed is 1000 rpm, the sensor drops out on underspeed when the speed of the moving object drops below $1000 - (1000 \times 0.3) = 700$ rpm.

- 20 %, - 11 % and - 6 % thresholds can be obtained by pressing the teach mode button.


Setting-up

Minimum mounting distances (mm)

Type	Side by side	Face to face
XS9E	$e \geq 40$	$e \geq 80$
XS9C	$e \geq 60$	$e \geq 120$

Dimensions

XS9E, XS9C



(1) For CHC type screws

Type	A	B	C	D	E	F
XS9E	14	26	13	8.8	20	3.5
XS9C	14	40	15	9.8	33	4.5



Inductive proximity sensors

XS range, Application

Sensors for rotation monitoring, slip detection and shaft overload detection, with teach mode

Flush mountable in metal

PBT case



Nominal sensing distance (Sn)	10 mm	15 mm	10 mm	15 mm
Adjustable frequency range	6...6000 impulses/min			

References

3-wire	PNP / NC	XS9E11RPBL01M12	XS9C11RPBL01M12	—	—
2-wire	— or ~ / NC	—	—	XS9E11RMBL01U20	XS9C11RMBL01U20
Weight (kg)		0.040	0.060	0.040	0.060

Characteristics

Product certifications		UL, CSA, C€			
Connection		Remote M12 connector on 0.15 m flying lead		Remote 1/2"-20UNF connector on 0.15 m flying lead	
Operating zone		0...8 mm	0...12 mm	0...8 mm	0...12 mm
Degree of protection	Conforming to IEC 60529	IP 67, double insulation □			
Storage temperature		- 40...+ 85 °C			
Operating temperature		- 25...+ 70 °C			
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)			
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms			
Indicators	Output state	Yellow LED			
	Supply on	Green LED			
Rated supply voltage		≡ 12...24 V		~ or ≡ 24...240 V (50/60 Hz)	
Voltage limits (including ripple)		≡ 10...36 V		~ or ≡ 20...264 V	
Switching capacity		≤ 100 mA (1)	≤ 200 mA (1)	~ or ≡ 5...100 mA (2)	≡ 5...200 mA, ~ 5...300 mA(2)
Voltage drop, closed state		≤ 2 V		≤ 5.5 V	
Residual current, open state		≤ 100 mA		≤ 1.5 mA	
Current consumption, no-load		≤ 10 mA		—	
Maximum switching frequency		48,000 impulses/min			
“Run-up” delay following power-up		9 seconds + 1/Fr			

(1) With overload and short-circuit protection.


(2) It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Wiring schemes

Connector		3-wire —	2-wire ~ or —
M12	1/2"-20UNF	XS9•11RPBL01M12	XS9•11RMBL01U20

Accessory (1)

	Description	Reference	Weight kg
	Remote control fixing clamp	XSZBPM12	0.015



XSZBPM12

(1) For accessories, see page 118.

Inductive proximity sensors


XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾
or 4...20 mA

For position, displacement and deformation control/monitoring

Functions

Example:
Sorting parts



These analogue output proximity sensors are solid-state sensors designed for monitoring displacement. They are not measuring sensors. They are suitable for use in many sectors, particularly for applications involving:

- deformation and displacement monitoring,
- vibration amplitude and frequency monitoring,
- control of dimensional tolerances,
- position control,
- concentricity or eccentricity monitoring.

Operating principle


The operating principle of the sensor is that of a damped oscillator. The degree of damping will depend on the distance of an object from the sensing face. The sensor will sense the distance and produce an output current with a value directly proportional to this distance.

Output curves 4...0.20 mA, 2-wire connection

XS1M12AB120

Sn = 0.2...2 mm


Ø 12 mm



XS1M18AB120

Sn = 0.5...5 mm


Ø 18 mm



XS1M30AB120

Sn = 1...10 mm


Ø 30 mm



XS4P12AB120

Sn = 0.4...4 mm


Ø 12 mm



XS4P18AB120

Sn = 0.8...8 mm


Ø 18 mm



XS4P30AB120

Sn = 1.5...15 mm

Ø 30 mm




Output curves 0...10 V, 3-wire connection

XS4P12AB110

Sn = 0.4...4 mm


Ø 12 mm



XS4P18AB110

Sn = 0.8...8 mm


Ø 18 mm



XS4P30AB110


Sn = 1.5...15 mm

Ø 30 mm



Wiring schemes


2-wire connection



	Output current	Load impedance value
12 V	4...20 mA	$R \leq 8.2 \Omega$
24 V	4...20 mA	$R \leq 470 \Omega$

Ensure a minimum of 10 V between the + and the - (terminal 3) of the sensor.

3-wire connection



	Output current	Load impedance value	Output voltage	Load impedance value
24 V	0...10 mA	$R \leq 1500 \Omega$	0...10 V	$R = 1000 \Omega$
48 V	0...10 mA	$R \leq 3300 \Omega$	0...10 V	$R = 1000 \Omega$

Ensure a minimum of 5 V between the + and the sensor output (terminal 4).





⁽¹⁾ Voltage range only obtained with a load impedance of 1000 Ω .

Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾
or 4...20 mA

For position, displacement and deformation control/monitoring

Sensor	Flush mountable in metal	Non flush mountable in metal	
			
Lengths (mm): a = Overall b = Threaded section	a = 50 b = 42	a = 50 b = 42	a = 54 b = 42
Nominal sensing distance (Sn)	Metal case	Plastic case	Plastic case
	2 mm	4 mm	4 mm

References

3-wire ---	Output 0...10 V (2)	—	—	XS4P12AB110
2-wire ---	Output 4...20 mA (2)	XS1M12AB120	XS4P12AB120	—
Weight (kg)		0.075	0.065	0.065





Characteristics

Product certifications	CE, UL, CSA		
Connection	Pre-cabled, PvR 3 x 0.34 mm ² , length 2 m		
Degree of protection Conforming to IEC 60529	IP 67		
Operating zone	0.2...2 mm	0.4...4 mm	0.4...4 mm
Repeat accuracy	± 3 %		
Linearity error	± 2 mA		± 1 V
Ambient air temperature	For operation: - 25...+ 70 °C		
Rated supply voltage	--- 12...24 V	--- 12...24 V	--- 24...48 V
Voltage limits (including ripple)	--- 10...36 V	--- 10...36 V	--- 15...58 V
Output current drift Ambient temperature: - 25...+ 70 °C	≤ 10 %		
Current consumption, no-load	4 mA		
Maximum operating rate	1500 Hz		

(1) Voltage range only obtained with a load impedance of 1000 Ω.

(2) Output current range Is, see page 80.





Setting-up

Minimum mounting distances (mm)	Side by side	Face to face	Facing a metal object	Mounted in a metal support
				
XS1M12AB120 flush mountable	e ≥ 4	e ≥ 24	e ≥ 6	d ≥ 12, h ≥ 0
XS4P12AB110 non flush mountable	e ≥ 16	e ≥ 48	e ≥ 12	d ≥ 36, h ≥ 8
XS4P12AB120 non flush mountable	e ≥ 16	e ≥ 48	e ≥ 12	d ≥ 36, h ≥ 8
Fixing nut tightening torque	< 6 N.m (metal case), < 2 N.m (plastic case)			
Other versions	Please consult our Customer Care Centre.			

Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾
or 4...20 mA





Sensor	Flush mountable in metal	Non flush mountable in metal	
			
Lengths (mm): a = Overall b = Threaded section c = For non flush mountable sensors	a = 53 b = 44 c = 0	a = 41 b = 26 c = 8	a = 41 b = 26 c = 8
Nominal sensing distance (S _n)	Metal case 5 mm	Plastic case 8 mm	Plastic case 8 mm

References				
3-wire ---	Output 0...10 V (2)	—	—	XS4P18AB110
2-wire ---	Output 4...20 mA (2)	XS1M18AB120	XS4P18AB120	—
Weight (kg)		0.120	0.080	0.080

Characteristics			
Product certifications	CE, UL, CSA		
Connection	Pre-cabled, PVR 3 x 0.34 mm², length 2 m		
Degree of protection Conforming to IEC 60529	IP 67		
Operating zone	0.5...5 mm	0.8...8 mm	0.8...8 mm
Repeat accuracy	± 3 %		
Linearity error	± 2 mA		± 1 V
Ambient air temperature	For operation: - 25...+ 70 °C		
Rated supply voltage	--- 12...24 V	--- 12...24 V	--- 24...48 V
Voltage limits (including ripple)	--- 10...36 V	--- 10...36 V	--- 15...58 V
Output current drift Ambient temperature: - 25...+ 70 °C	≤ 10 %		
Current consumption, no-load	4 mA		
Maximum operating rate	500 Hz		

(1) Voltage range only obtained with a load impedance of 1000 Ω.





(2) Output current range I_s, see page 80.

Setting-up				
Minimum mounting distances (mm)	Side by side	Face to face	Facing a metal object	Mounted in a metal support
				
XS1M18AB120 flush mountable	e ≥ 10	e ≥ 60	e ≥ 15	d ≥ 18, h ≥ 0
XS4P18AB110 non flush mountable	e ≥ 32	e ≥ 96	e ≥ 24	d ≥ 54, h ≥ 16
XS4P18AB120 non flush mountable	e ≥ 32	e ≥ 96	e ≥ 24	d ≥ 54, h ≥ 16
Fixing nut tightening torque	< 15 N.m (metal case), < 5 N.m (plastic case)			
Other versions	Please consult our Customer Care Centre.			

Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾
or 4...20 mA

Sensor	Flush mountable in metal	Non flush mountable in metal	
			
Lengths (mm): a = Overall b = Threaded section c = For non flush mountable sensors	a = 50 b = 42 c = 0	a = 53 b = 32 c = 13	a = 53 b = 32 c = 13
Nominal sensing distance (Sn)	Metal case 10 mm	Plastic case 15 mm	Plastic case 15 mm

References

3-wire ---	Output 0...10 V (2)	—	—	XS4P30AB110
2-wire ---	Output 4...20 mA (2)	XS1M30AB120	XS4P30AB120	—
Weight (kg)		0.200	0.100	0.100





Characteristics

Product certifications	CE, UL, CSA		
Connection	Pre-cabled, PvR 3 x 0.34 mm ² , length 2 m		
Degree of protection Conforming to IEC 60529	IP 67		
Operating zone	1...10 mm	1.5...15 mm	1.5...15 mm
Repeat accuracy	± 3 %		
Linearity error	± 2 mA		± 1 V
Ambient air temperature	For operation: - 25...+ 70 °C		
Rated supply voltage	--- 12...24 V	--- 12...24 V	--- 24...48 V
Voltage limits (including ripple)	--- 10...36 V	--- 10...36 V	--- 15...58 V
Output current drift Ambient temperature: - 25...+ 70 °C	≤ 10 %		
Current consumption, no-load	4 mA		
Maximum operating rate	300 Hz		

(1) Voltage range only obtained with a load impedance of 1000 Ω.

(2) Output current range Is, see page 80.

Setting-up

Minimum mounting distances (mm)	Side by side	Face to face	Facing a metal object	Mounted in a metal support
				
XS1M30AB120 flush mountable	e ≥ 20	e ≥ 120	e ≥ 30	d ≥ 30, h ≥ 0
XS4P30AB110 non flush mountable	e ≥ 60	e ≥ 180	e ≥ 45	d ≥ 90, h ≥ 30
XS4P30AB120 non flush mountable	e ≥ 60	e ≥ 180	e ≥ 45	d ≥ 90, h ≥ 30
Fixing nut tightening torque	< 40 N.m (metal case), < 20 N.m (plastic case)			
Other versions	Please consult our Customer Care Centre.			

Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾

For position, displacement and deformation control/monitoring

Functions

These analogue output proximity sensors are solid-state sensors designed for monitoring displacement. They are not measuring sensors.

They are suitable for use in many sectors, particularly for applications involving:

- ☐ deformation and displacement monitoring,
- ☐ vibration amplitude and frequency monitoring,
- ☐ control of dimensional tolerances,
- ☐ position control,
- ☐ concentricity or eccentricity monitoring.


Operating principle

The operating principle of the sensor is that of a damped oscillator. The degree of damping will depend on the distance of an object from the sensing face. The sensor will sense the distance and produce an output current with a value directly proportional to this distance.

Output curves 0...10 V, 3-wire connection


XS9F

$S_n = 1 \dots 5 \text{ mm}$




XS9E

$S_n = 1 \dots 10 \text{ mm}$




XS9C

$S_n = 2 \dots 15 \text{ mm}$



XS9D

$S_n = 5 \dots 40 \text{ mm}$



Wiring schemes


Connector



Pre-cabled

BN: Brown
BU: Blue
BK: Black

3-wire connection



	Output current	Load impedance value	Output voltage	Load impedance value
24 V	0...10 mA	$R \leq 1400 \Omega$	0...10 V	$R = 1000 \Omega$

Note: Ensure a minimum of 5 V between the + (terminal 1) and the sensor output (terminal 4).

⁽¹⁾ Voltage range only obtained with a load impedance of 1000 Ω .

Inductive proximity sensors

XS range, Application


Sensors with analogue output signal 0...10 V ⁽¹⁾

For position, displacement and deformation
control/monitoring

Flush mountable in metal



PBT case



Nominal sensing distance (Sn)	5 mm	10 mm	15 mm	40 mm
-------------------------------	------	-------	-------	-------

References

3-wire ---	Pre-cabled (L = 2 m) (2)	XS9F111A1L2	XS9E111A1L2	XS9C111A1L2	XS9D111A1L2
0...10 V	Connector	XS9F111A1L01M8	XS9E111A1L01M12	XS9C111A1L01M12	XS9D111A1M12
Weight (kg)	Pre-cabled (L = 2 m) (2)	0.060	0.075	0.095	0.340
	Connector	0.040	0.055	0.075	0.320

Characteristics

Product certifications		UL, CSA, Cc		UL, CSA, Cc, ECOLAB	
Connection	Pre-cabled	PvR 3 x 0.34 mm², length 2 m for XS9●111A●L2			
	Connector	0.15 m flying lead with M8 connector	0.15 m flying lead with M12 connector		M12
Operating zone		1...5 mm	1...10 mm	2...15 mm	5...40 mm
Degree of protection	Pre-cabled	IP 68		IP 68, double insulation ☐	
Conforming to IEC 60529	Connector	IP 67		IP 67, double insulation ☐	
Storage temperature		- 40...+ 85 °C			
Operating temperature		- 25...+ 70 °C			
Materials		PBT case			
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)			
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms			
Output state indication		No			
Rated supply voltage		--- 24 V			
Voltage limits (including ripple)		--- 15...36 V			
Repeat accuracy		± 3 %			
Linearity error		± 1 V			
Current consumption, no-load		≤ 4 mA with overload and short-circuit protection			
Maximum operating frequency		2000 Hz	1000 Hz	100 Hz	
Output current drift		≤ 10 % (throughout the operating temperature range)			

Dimensions

XS9F

XS9E/C/D

XS9C/D

XS9E

(3) For CHC type screws

Type	A (L2)	A (M12)	B	C	D	E	F
XS9E	14	—	26	13	8.8	20	3.5
XS9C	14	—	40	15	9.8	33	4.5
XS9D	23	14	80	26	16	65	5.5

Setting-up (Minimum mounting distances (mm))

Type	Side by side	Face to face	Facing a metal object
XS9F			
XS9E	e ≥ 15	e ≥ 36	e ≥ 15
XS9C	e ≥ 30	e ≥ 72	e ≥ 30
XS9D	e ≥ 45	e ≥ 110	e ≥ 45
	e ≥ 120	e ≥ 300	e ≥ 120

(1) Voltage range only obtained with a load impedance of 1000 Ω.

(2) For a 5 m long cable replace L2 by L5, for a 10 m long cable replace L2 by L10.

Example: XS9C111A1L2 becomes **XS9C111A1L5** with a 5 m long cable.

Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 4...20 mA

For position, displacement and deformation control/monitoring

Functions

These analogue output proximity sensors are solid-state sensors designed for monitoring displacement. They are not measuring sensors.

They are suitable for use in many sectors, particularly for applications involving:

- ☐ deformation and displacement monitoring,
- ☐ vibration amplitude and frequency monitoring,
- ☐ control of dimensional tolerances,
- ☐ position control,
- ☐ concentricity or eccentricity monitoring.


Operating principle

The operating principle of the sensor is that of a damped oscillator. The degree of damping will depend on the distance of an object from the sensing face. The sensor will sense the distance and produce an output current with a value directly proportional to this distance.

Output curves 4...20 mA, 2-wire connection


XS9F

Sn = 1...5 mm




XS9E

Sn = 1...10 mm




XS9C

Sn = 2...15 mm




XS9D

Sn = 5...40 mm



Wiring schemes


Connector



Pre-cabled

BN: Brown
BU: Blue
BK: Black

2-wire connection



	Output current	Load impedance value
12 V	4...20 mA	$R \leq 8.2 \Omega$
24 V	4...20 mA	$R \leq 470 \Omega$

Note: Ensure a minimum of 10 V between the + (terminal 1) and - (terminal 3) of the sensor.

Inductive proximity sensors

XS range, Application


Sensors with analogue output signal 4...20 mA

For position, displacement and deformation
control/monitoring

Flush mountable in metal



PBT case



Nominal sensing distance (Sn)	5 mm	10 mm	15 mm	40 mm
-------------------------------	------	-------	-------	-------

References

2-wire ---	Pre-cabled (L = 2 m) (1)	XS9F111A2L2	XS9E111A2L2	XS9C111A2L2	XS9D111A2L2
4...20 mA	Connector	XS9F111A2L01M8	XS9E111A2L01M12	XS9C111A2L01M12	XS9D111A2M12
Weight (kg)	Pre-cabled (L = 2 m)	0.060	0.075	0.095	0.340
	Connector	0.040	0.055	0.075	0.320

Characteristics

Product certifications		UL, CSA, CEC		UL, CSA, CEC, ECOLAB	
Connection	Pre-cabled	PvR 3 x 0.34 mm ² , length 2 m for XS9●111A●L2			
	Connector	0.15 m flying lead with M8 connector	0.15 m flying lead with M12 connector		M12
Operating zone		1...5 mm	1...10 mm	2...15 mm	5...40 mm
Degree of protection	Pre-cabled	IP 68			
Conforming to IEC 60529	Connector	IP 67		IP 67, double insulation ☐	
Storage temperature		- 40...+ 85 °C			
Operating temperature		- 25...+ 60 °C		- 25...+ 70 °C	
Materials		PBT case			
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)			
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms			
Output state indication		No			
Rated supply voltage		--- 12...24 V			
Voltage limits (including ripple)		--- 10...36 V			
Repeat accuracy		± 3 %			
Linearity error		± 2 mA			
Current consumption, no-load		≤ 4 mA with overload and short-circuit protection			
Maximum operating frequency		2000 Hz	1000 Hz	100 Hz	
Output current drift		≤ 10 % (throughout the operating temperature range)			

Dimensions

XS9F

XS9E/C/D

XS9C/D

XS9E

(2) For CHC type screws

Type	A (L2)	A (M12)	B	C	D	E	F
XS9E	14	—	26	13	8.8	20	3.5
XS9C	14	—	40	15	9.8	33	4.5
XS9D	23	14	80	26	16	65	5.5

Setting-up (Minimum mounting distances (mm))

Type	Side by side	Face to face	Facing a metal object
XS9F			
XS9E	e ≥ 15	e ≥ 36	e ≥ 15
XS9C	e ≥ 30	e ≥ 72	e ≥ 30
XS9D	e ≥ 45	e ≥ 110	e ≥ 45
	e ≥ 120	e ≥ 300	e ≥ 120

(1) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.



Example: XS9F111A2L2 becomes XS9F111A2L5 with a 5 m long cable.

Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾
or 4...20 mA. Plastic case, 40 x 40 mm front face
5 position turret head

Sensor	Non flush mountable in metal	
Dimensions	40 x 40 x 70 mm	40 x 40 x 117 mm



Nominal sensing distance (Sn)	25 mm
-------------------------------	-------

References

3-wire ---	0...10 V output ⁽¹⁾	XS9C2A2A1M12	XS9C4A2A1P20 ⁽²⁾
2-wire ---	4...20 mA output	XS9C2A2A2M12	XS9C4A2A2P20 ⁽²⁾

XS9C4...P20 sensors are available with an ISO M20 cable entry and can be supplied with a PG 13.5 (e.g. XS9C4A2A1G13) or a 1/2" NPT (e.g. XS9C4A2A2N12) cable entry: please consult our Customer Care Centre for more information.



Weight (kg)	0.149	0.244
-------------	-------	-------

Characteristics

Product certifications	UL, CSA, CE	
Conformity to standards	IEC 60947-5-2 and IEC 60947-5-7	
Connection	M12 connector (4-pin)	Screw terminals, clamping capacity 3 x 1.5 mm ² / 3 x 16 AWG
Operating zone	2...27 mm	
Linearity error	< 3%	
Repeat accuracy	< 3%	
Output current drift	< 5%	
Degree of protection	Conforming to IEC 60529 and DIN 40050	IP 65, IP 67 and IP 69K
Temperature	Storage	- 40...+ 85°C
	Operation ⁽³⁾	- 25...+ 70°C
Material	Case: PBT	
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10...55 Hz)
Shock resistance	Conforming to IEC 60068-2-27	50 gn for 11 ms
Indicators	Output state (alignment aid)	Yellow LED
Rated supply voltage	4...20 mA	--- 12...24 V with protection against reverse polarity
	0...10 V	--- 24 V with protection against reverse polarity
Voltage limits (including ripple)	4...20 mA	--- 12...36 V
	0...10 V	--- 15...36 V
Current consumption, no-load	3-wire ---	< 4 mA
Delays	First-up	< 7 ms
	Response	< 6 ms
	Recovery	< 6 ms

Analogue outputs 4-20 mA and 0-10 V

XS9C2A2A2M12 and XS9C4A2A2P20	XS9C2A2A1M12 and XS9C4A2A1P20
-------------------------------	-------------------------------



⁽¹⁾ Voltage range only obtained with a load impedance of 1000 Ω.

⁽²⁾ These sensors are supplied without a cable gland. An adaptable PG 13.5 cable gland is available (reference XSZPE13).

⁽³⁾ Sensors are available for very low temperatures (suffix TF: - 40°C, + 70°C) or very high temperatures (suffix TT: - 25°C, + 85°C); please consult our Customer Care Centre.


Inductive proximity sensors

XS range, Application

Sensors with analogue output signal 0...10 V ⁽¹⁾
or 4...20 mA. Plastic case, 40 x 40 mm front face
5 position turret head


Setting-up precautions

Minimum mounting distances (mm)




Side by side

$e \geq 120$



Face to face

$e \geq 240$




Facing a metal object

$e \geq 90$

Sensors non flush mountable in metal

Wiring schemes

2-wire




Output current

Load impedance value

12 V	4...20 mA	$R \leq 82 \Omega$
24 V	4...20 mA	$R \leq 560 \Omega$

Ensure a minimum of 10 V between the + and the - (terminal 3) of the sensor.

3-wire




Output voltage

Output current	Load impedance value	Output voltage	Load impedance value
12 V	0...10 mA	$R \leq 630 \Omega$	—
24 V	0...10 mA	$R \leq 1500 \Omega$	0...10 V
			$R = 1000 \Omega$

Ensure a minimum of 5 V between the + and the sensor output (terminal 4).


Dimensions

XS9C2A2A1M12 and XS9C2A2A2M12




Head positions


XS9C2A2A1M12 and XS9C2A2A2M12



XS9C4A2A1P20 and XS9C4A2A2P20



XS9C4A2A1P20 and XS9C4A2A2P20



(1) 2 elongated holes Ø 5.3 x 7 mm.

Tightening torque of cover fixing screws and clamp screws: < 1.2 N.m / < 10.62 lb-in

(1) Voltage range only obtained with a load impedance of 1000 Ω.


Inductive proximity sensors

XS range, Application


Cylindrical, stainless steel 316L front face

for food and beverage applications and harsh industrial environments. Three-wire DC, solid-state output


ECOLAB®
certified




XS912●1PAM12



XS918●1PAM12




XS930●1PAM12




XUZA118

XSZBS30



XZCP1141L●



XZCP1241L●

Ø 12 mm, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire 12-24V ---, flush mountable					
6	NO	PNP	M12	XS912S1PAM12	0.024

Three-wire 12-24V ---, non flush mountable

10	NO	PNP	M12	XS912S4PAM12	0.023
----	----	-----	-----	--------------	-------

Ø 18 mm, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire 12-24V ---, flush mountable					
10	NO	PNP	M12	XS918S1PAM12	0.051

Three-wire 12-24V ---, non flush mountable

20	NO	PNP	M12	XS918S4PAM12	0.051
----	----	-----	-----	--------------	-------

Ø 30 mm, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire 12-24V ---, flush mountable					
20	NO	PNP	M12	XS930S1PAM12	0.140

Three-wire 12-24V ---, non flush mountable

40	NO	PNP	M12	XS930S4PAM12	0.145
----	----	-----	-----	--------------	-------

Accessories

Description	For use with sensor	Reference	Weight kg
Stainless steel mounting bracket	Ø 12	XSZBS12	0.090
	Ø 18	XUZA118	0.190
	Ø 30	XSZBS30	0.370

Connecting cables (PVC) (1)


Description	Type	Length m	Reference	Weight kg
Pre-wired M12 connectors Female, 4-pin Stainless steel clamping ring	Straight	2	XZCPA1141L2	0.090
		5	XZCPA1141L5	0.190
		10	XZCPA1141L10	0.370
	Elbowed	2	XZCPA1241L2	0.090
		5	XZCPA1241L5	0.190
		10	XZCPA1241L10	0.370

Wiring schemes

M12 connector



PNP



(1) For further information, please consult our site www.tesensors.com.

Inductive proximity sensors

XS range, Application

Cylindrical, stainless steel 316L front face
for food and beverage applications and harsh industrial
environments. Three-wire DC, solid-state output

Characteristics				
Sensor type	Flush	XS912S1PAM12	XS918S1PAM12	XS930S1PAM12
	Non flush	XS912S4PAM12	XS918S4PAM12	XS930S4PAM12
Product certifications		CE, cULus, ECOLAB		
Connection	Connector	M12		
Operating zone	Flush	mm 0...4.8	0...8	0...16
	Non flush	mm 0...8	0...16	0...32
Differential travel		1...15 (real sensing distance Sr)		
Degree of protection	Conforming to IEC 60529	IP 68 (5 meters underwater for 1 month)		
	Conforming to DIN 40050	IP 69K		
Storage temperature		°C -25...+85 (-13...185°F)		
Operating temperature		°C -25...+85 (-13...185°F)		
Materials	Case	Stainless steel 316L		
Front face thickness		mm 0.4	0.6	1.0
Mechanical shock resistance	Conforming to IEC 62262	IK10		
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 1 mm (f = 10 to 55 Hz)		
Shock resistance	Conforming to IEC 60068-2-27	30 gn, duration 11 ms		
Output state indication		Yellow LED, 4 viewing points at 90° (blinking from 0.8 Sr and Sr)		
Rated supply voltage		V 12...24 with protection against reverse polarity		
Voltage limits (including ripple)		V 10...30		
Switching capacity		mA ≤ 200 with overload and short-circuit protection		
Voltage drop, closed state		V ≤ 2		
Current consumption, no-load		mA ≤ 10		
Maximum switching frequency	Flush	Hz 600	300	100
	Non flush	Hz 400	200	90
Delays	First set-up	ms 40		
	Response	µs 0.06		
	Recovery	µs 15		

Setting-up

Minimum mounting distances in mm, flush version

Side by side		Face to face	Facing a metal object	Mounted in a metal support
Ø 12 e ≥ 38		e ≥ 30		
Ø 18 e ≥ 42		e ≥ 40		d ≥ 24
Ø 30 e ≥ 80		e ≥ 70		d ≥ 50
				d ≥ 90

Minimum mounting distances in mm, non flush version

Side by side		Face to face	Facing a metal object	Mounted in a metal support
Ø 12 e ≥ 108		e ≥ 40		
Ø 18 e ≥ 182		e ≥ 70		d ≥ 30 h ≥ 22
Ø 30 e ≥ 270		e ≥ 130		d ≥ 60 h ≥ 34
				d ≥ 120 h ≥ 34

Dimensions


		Flush sensor			Non flush sensor		
		M12	M18	M30	M12	M18	M30
	a (mm)	60	63.5	63.5	60	63.5	63.5
	b (mm)	41	42	42	36	35	32
	c (mm)	0	0	0	5	7	10

Reduction coefficient


Flush-non mounted		Flush sensor			Non flush sensor		
		M12	M18	M30	M12	M18	M30
Steel		1	1	1	1	1	1
Aluminum		1	1	1	1	1	1
Brass		1.3	1.2	1.3	1.4	1.35	1.2
Copper		0.85	0.8	0.9	0.8	0.9	0.9
Stainless steel	Thickness 1 mm	0.5	0.5	0.35	(1)	0.3	(1)
	Thickness 2 mm	0.9	0.9	0.7	0.66	0.6	0.25
Flush mounted		M12	M18	M30	(1) No detection.		
Steel		0.7	0.75	0.9			
Aluminum		1.15	0.9	0.7			
Brass		1.05	0.75	0.6			
Stainless steel		0.8	0.8	1.3			

Inductive proximity sensors


XS range, Application, food and beverage processing series
Cylindrical, stainless steel, non flush mountable
Three-wire DC, solid-state output




XS212SA...L2



XS218SA...M12




XS2L2SA...L2




XS230SA...L2




XUZH2005



XSZBS12



XUZA118



XSZBS30

Ø 12, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
7	NO	PNP	Pre-cabled (L = 2 m) (1)	XS212SAPAL2	0.075
			M12 connector	XS212SAPAM12	0.035
		NPN	Pre-cabled (L = 2 m) (1)	XS212SANAL2	0.075
			M12 connector	XS212SANAM12	0.035

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
12	NO	PNP	Pre-cabled (L = 2 m) (1)	XS218SAPAL2	0.120
			M12 connector	XS218SAPAM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	XS218SANAL2	0.120
			M12 connector	XS218SANAM12	0.060

Ø 18, plain

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
12	NO	PNP	Pre-cabled (L = 2 m) (1)	XS2L2SAPAL2	0.120
			M12 connector	XS2L2SAPAM12	0.060
		NPN	Pre-cabled (L = 2 m) (1)	XS2L2SANAL2	0.120
			M12 connector	XS2L2SANAM12	0.060

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
22	NO	PNP	Pre-cabled (L = 2 m) (1)	XS230SAPAL2	0.205
			M12 connector	XS230SAPAM12	0.145
		NPN	Pre-cabled (L = 2 m) (1)	XS230SANAL2	0.205
			M12 connector	XS230SANAM12	0.145

Accessories (2)

Description	For use with	Reference	Weight kg
Plastic fixing clamp, 24.1 mm centres, with locking screw	Ø 18 sensor, plain case	XUZH2005	0.007
Stainless steel fixing bracket	Ø 12 sensor	XSZBS12	0.060
	Ø 18 sensor	XUZA118	0.045
	Ø 30 sensor	XSZBS30	0.080

Connecting cables

Description	Type	Length m	Reference	Weight kg
Pre-wired M12 connectors Female, 4-pin, stainless steel clamping ring	Straight	2	XZCPA1141L2	0.090
		5	XZCPA1141L5	0.210
		10	XZCPA1141L10	0.410
	Elbowed	2	XZCPA1241L2	0.090
		5	XZCPA1241L5	0.210
		10	XZCPA1241L10	0.410
M12 jumper cable Male, 3-pin, stainless steel clamping ring	Straight	2	XZCRA151140A2	0.095
		5	XZCRA151140A5	0.200

(1) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.



Example: XS212SAPAL2 becomes XS212SAPAL5 with a 5 m long cable.

(2) For further information, see page 118.

Characteristics			
Sensor type		XS2...SA...M12	XS2...SA...L2
Product certifications/approvals		UL, CSA, CE	
Connection	Connector	M12	—
	Pre-cabled	—	Length: 2 m
Operating zone	Ø 12	mm 0...5.6	
	Ø 18	mm 0...9.6	
	Ø 30	mm 0...17.6	
Differential travel		% 1...15 of effective sensing distance (Sr)	
Degree of protection	Conforming to IEC 60529	IP 67	IP 68, double insulation
	DIN 40050	IP 69K	
Storage temperature		°C - 40...+ 85 (1)	
Operating temperature		°C - 25...+ 85	
Materials	Case	Stainless steel 316 L	
	Cable	—	Non-poisonous PVC, 3 x 0.34 mm ²
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED: 4 viewing ports at 90°	Yellow LED: annular
Rated supply voltage		V --- 12...24 with protection against reverse polarity	
Voltage limits (including ripple)		V --- 10...36	
Switching capacity		mA ≤ 200 with overload and short-circuit protection	
Voltage drop, closed state		V ≤ 2	
Current consumption, no-load		mA ≤ 10	
Maximum switching frequency	XS212SA...●●●●	Hz 2500	
	XS218SA...●●●● and XS2L2...●●●●	Hz 1000	
	XS230SA...●●●●	Hz 500	
Delays	First-up	ms ≤ 10	
	Response	ms ≤ 0.2 Ø 12, ≤ 0.3 Ø 18, ≤ 0.6 Ø 30	
	Recovery	ms ≤ 0.2 Ø 12, ≤ 0.7 Ø 18, ≤ 1.4 Ø 30	



(1) + 100 °C for cleaning and sterilization phases whilst not in service.

Wiring schemes

Connector	Pre-cabled	PNP	NPN
M12 4 	BU: Blue BN: Brown BK: Black		


Setting-up

Minimum mounting distances (mm)




Side by side

Ø 12	e ≥ 48
Ø 18	e ≥ 72
Ø 30	e ≥ 120



Face to face

e ≥ 84
e ≥ 144
e ≥ 264



Facing a metal object

e ≥ 21
e ≥ 36
e ≥ 66

Dimensions

<

Ø: 2 elongated holes Ø 4.8 x 12.7


Inductive proximity sensors

XS range, Application


Food and beverage processing series

Cylindrical, stainless steel, non flush mountable


Two-wire AC or DC




XS218SAM•L2




XS218SAM•U20



XS230SAM•L2



XUZA118



XSZBS30

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
12	NO	Pre-cabled (L = 2 m) (1)	XS218SAMAL2	0.120
		1/2"-20UNF connector	XS218SAMAU20	0.060

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
22	NO	Pre-cabled (L = 2 m) (1)	XS230SAMAL2	0.205
		1/2"-20UNF connector	XS230SAMAU20	0.145

Connecting cables

Description	Type	Length m	Reference	Weight kg
Pre-wired connectors 1/2"-20UNF 3-pin female, stainless steel clamping ring	Straight	5	XZCPA1865L5	0.210
		10	XZCPA1865L10	0.410
	Elbowed	5	XZCPA1965L5	0.250
		10	XZCPA1965L10	0.485

Accessories

Description	For use with	Reference	Weight kg
Stainless steel fixing brackets	Ø 18 sensor	XUZA118	0.045
	Ø 30 sensor	XSZBS30	0.080


(1) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.
Example: **XS218SAMAL2** becomes **XS218SAMAL5** with a 5 m long cable.

Characteristics			
Sensor type		XS2●●SAM●U20	XS2●●SAM●L2
Product certifications/approvals		UL, CSA, CE	
Connection	Connector	1/2"-20UNF	—
	Pre-cabled	—	Length: 2 m
Operating zone	Ø 18	mm	0...9.6
	Ø 30	mm	0...17.6
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 67	IP 68, double insulation □
	DIN 40050	IP 69K	
Storage temperature		°C	- 40...+ 85 (1)
Operating temperature		°C	- 25...+ 85
Materials	Case	Stainless steel 316 L	
	Cable	—	Non-poisonous PVC, 2 x 0.34 mm²
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED: 4 viewing ports at 90°	Yellow LED: annular
Rated supply voltage		V	~ or — 24...240 (~ 50/60 Hz)
Voltage limits (including ripple)		V	~ or — 20...264
Switching capacity		mA	~ 5...300 or — 5...200 (2)
Voltage drop, closed state		V	≤ 5.5
Residual current, open state		mA	≤ 0.8
Maximum switching frequency	XS218SAM●●●	Hz	~ 25 or — 1000
	XS230SAM●●●	Hz	~ 25 or — 300
Delays	First-up	ms	≤ 30
	Response	ms	≤ 0.5
	Recovery	ms	≤ 0.5 XS218SAM●●●, ≤ 2 XS230SAM●●●

(1) + 100 °C for cleaning and sterilization phases whilst not in service.





(2) It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Wiring schemes

Connector	Pre-cabled	2-wire ~ or —
1/2"-20UNF	BU: Blue BN: Brown	NO output
 AC/DC: 2 ⊕ : 1 AC/DC: 3		 ⊕ : on connector models only


Setting-up

Minimum mounting distances (mm)

	 Side by side	 Face to face	 Facing a metal object
Ø 18	e ≥ 72	e ≥ 144	e ≥ 36
Ø 30	e ≥ 120	e ≥ 264	e ≥ 66

Dimensions


XS2




(1) LED


	Pre-cabled (mm)		Connector (mm)		
XS2	a	b	a	b	c
Ø 18	60	40	72	44	8
Ø 30	62.5	41	74	40	13

XSZA118






XSZBS30




Ø: 2 elongated holes Ø 7.14 x 29.36

Inductive proximity sensors


XS range, Application, food and beverage processing series
Cylindrical, plastic, non flush mountable
Three-wire DC, solid-state output




XS212AAAL2



XS218AAAL2



XS230AAAL2



XSZB...

Ø 12, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
7	NO	PNP	Pre-cabled (L = 2 m) (1)	XS212AAPAL2	0.065
			M12 connector	XS212AAPAM12	0.030
		NPN	Pre-cabled (L = 2 m) (1)	XS212AANAL2	0.065
			M12 connector	XS212AANAM12	0.030

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
12	NO	PNP	Pre-cabled (L = 2 m) (1)	XS218AAPAL2	0.100
			M12 connector	XS218AAPAM12	0.040
		NPN	Pre-cabled (L = 2 m) (1)	XS218AANAL2	0.100
			M12 connector	XS218AANAM12	0.040

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
22	NO	PNP	Pre-cabled (L = 2 m) (1)	XS230AAPAL2	0.140
			M12 connector	XS230AAPAM12	0.080
		NPN	Pre-cabled (L = 2 m) (1)	XS230AANAL2	0.140
			M12 connector	XS230AANAM12	0.080

Accessories (2)

Description		Reference	Weight kg
Fixing clamps	Ø 12	XSZB112	0.006
	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

Connecting cables

Description	Type	Length m	Reference	Weight kg
Pre-wired M12 connectors Female, 4-pin, stainless steel clamping ring	Straight	2	XZCPA1141L2	0.090
		5	XZCPA1141L5	0.190
		10	XZCPA1141L10	0.370
	Elbowed	2	XZCPA1241L2	0.090
		5	XZCPA1241L5	0.190
		10	XZCPA1241L10	0.370
M12 jumper cable Male, 3-pin, stainless steel clamping ring	Straight	2	XZCRA151140A2	0.090
		5	XZCRA151140A5	0.190

(1) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.

Example: **XS212AAPAL2** becomes **XS212AAPAL5** with a 5 m long cable.


(2) For further information, see page 118.

Characteristics			
Sensor type		XS2...AA...M12	XS2...AA...L2
Product certifications/approvals		UL, CSA, CE	
Connection	Connector	M12	—
	Pre-cabled	—	Length: 2 m
Operating zone	Ø 12	mm	0...5.6
	Ø 18	mm	0...9.6
	Ø 30	mm	0...17.6
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 67	IP 68, double insulation □
	DIN 40050	IP 69K	
Storage temperature		°C	- 40...+ 85
Operating temperature		°C	- 25...+ 85
Materials	Case	PPS	
	Cable	—	PvR and 3 x 0.34 mm ²
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED: annular	
Rated supply voltage		V	— 12...48 for T - 25...+ 85 °C
Voltage limits (including ripple)		V	— 10...58 for T - 25...+ 85 °C
Switching capacity		mA	≤ 200 with overload and short-circuit protection
Voltage drop, closed state		V	≤ 2
Current consumption, no-load		mA	≤ 10
Maximum switching frequency	XS212AA...●●●●	Hz	2500
	XS218AA...●●●●	Hz	1000
	XS230AA...●●●●	Hz	500
Delays	First-up	ms	≤ 10
	Response	ms	≤ 0.2 Ø 12, ≤ 0.3 Ø 18, ≤ 0.6 Ø 30
	Recovery	ms	≤ 0.2 Ø 12, ≤ 0.7 Ø 18, ≤ 1.4 Ø 30

Wiring schemes

Connector	Pre-cabled	PNP	NPN
M12 	BU: Blue BN: Brown BK: Black		


Setting-up



Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object
Ø 12	e ≥ 48	e ≥ 84	e ≥ 21
Ø 18	e ≥ 72	e ≥ 144	e ≥ 36
Ø 30	e ≥ 120	e ≥ 264	e ≥ 66


Dimensions




XS2	Pre-cabled (mm)		Connector (mm)	
	a	b	a	b
Ø 12	50	42	61	43
Ø 18	60	51	70	52
Ø 30	60	51	70	52

Inductive proximity sensors


XS range Application, food and beverage processing series
Cylindrical, plastic, non flush mountable
Two-wire AC or DC




XS218AAM L2



XS230AAM U20



XS230AAM L2



XSZB118

Ø 18, threaded M18 x 1

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
12	NO	Pre-cabled (L = 2 m) (1)	XS218AAMAL2	0.100
		1/2"-20UNF connector	XS218AAMAU20	0.040

Ø 30, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Connection	Reference	Weight kg
22	NO	Pre-cabled (L = 2 m) (1)	XS230AAMAL2	0.140
		1/2"-20UNF connector	XS230AAMAU20	0.080

Accessories (2)

Description		Reference	Weight kg
Fixing clamps	Ø 18	XSZB118	0.010
	Ø 30	XSZB130	0.020

Connecting cables

Description	Type	Length m	Reference	Weight kg
Pre-wired connectors 1/2"-20UNF 3-pin female, stainless steel 316 L clamping ring	Straight	5	XZCPA1865L5	0.180
		10	XZCPA1865L10	0.350
	Elbowed	5	XZCPA1965L5	0.180
		10	XZCPA1965L10	0.350

(1) For a 5 m long cable replace L2 by L5; for a 10 m long cable replace L2 by L10.


Example: **XS218AAMAL2** becomes **XS218AAMAL5** with a 5 m long cable.

(2) For further information, see page 118.


Characteristics			
Sensor type		XS2●●AAM●U20	XS2●●AAM●L2
Product certifications/approvals		UL, CSA, CE	
Connection	Connector	1/2"-20UNF	—
	Pre-cabled	—	Length: 2 m
Operating zone	Ø 18	mm	0...9.6
	Ø 30	mm	0...17.6
Differential travel		%	1...15 of effective sensing distance (Sr)
Degree of protection	Conforming to IEC 60529	IP 67	IP 68, double insulation □
	DIN 40050	IP 69K	
Storage temperature		°C	- 40...+ 85
Operating temperature		°C	- 25...+ 85
Materials	Case	PPS	
	Cable	—	PvR and 2 x 0.34 mm ²
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms	
Output state indication		Yellow LED: annular	
Rated supply voltage		V	~ or — 24...240 (~ 50/60 Hz)
Voltage limits (including ripple)		V	~ or — 20...264
Switching capacity		mA	~ 5...300 or — 5...200 (1)
Voltage drop, closed state		V	≤ 5.5
Residual current, open state		mA	≤ 0.8
Maximum switching frequency	XS218AAM●●●	Hz	~ 25 or — 1000
	XS230AAM●●●	Hz	~ 25 or — 300
Delays	First-up	ms	≤ 30
	Response	ms	≤ 0.5
	Recovery	ms	≤ 0.5 XS218AAM●●●, ≤ 2 XS230AAM●●●

(1) It is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Wiring schemes

Connector	Pre-cabled	2-wire ~ or —
1/2"-20UNF	BU: Blue BN: Brown	NO output
		

Setting-up




Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object
Ø 18	e ≥ 72	e ≥ 144	e ≥ 36
Ø 30	e ≥ 120	e ≥ 264	e ≥ 66

Dimensions

XS2



(1) LED

XS2	Pre-cabled (mm)		Connector (mm)	
	a	b	a	b
Ø 18	60	51	70	52
Ø 30	60	51	70	52


Inductive proximity sensors

XS range, Application


Cylindrical, stainless steel 303 front face

for harsh industrial environments


Three-wire DC, solid-state output




XS908●1PAM12




XS912●1PAM12




XS918●1PAM12



XS930●1PAM12



XZCP1141L●



XZCP1241L●

Ø 8 mm, threaded M8 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
-----------------------------	----------	--------	------------	-----------	--------------

Three-wire 12-24V $\overline{\text{V}}$, flush mountable

3	NO	PNP	M12	XS908R1PAM12	0.018
---	----	-----	-----	--------------	-------

Three-wire 12-24V $\overline{\text{V}}$, non flush mountable

6	NO	PNP	M12	XS908R4PAM12	0.018
---	----	-----	-----	--------------	-------

Ø 12 mm, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
-----------------------------	----------	--------	------------	-----------	--------------

Three-wire 12-24V $\overline{\text{V}}$, flush mountable

6	NO	PNP	M12	XS912R1PAM12	0.024
---	----	-----	-----	--------------	-------

Three-wire 12-24V $\overline{\text{V}}$, non flush mountable

10	NO	PNP	M12	XS912R4PAM12	0.023
----	----	-----	-----	--------------	-------

Ø 18 mm, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
-----------------------------	----------	--------	------------	-----------	--------------

Three-wire 12-24V $\overline{\text{V}}$, flush mountable

10	NO	PNP	M12	XS918R1PAM12	0.044
----	----	-----	-----	--------------	-------

Three-wire 12-24V $\overline{\text{V}}$, non flush mountable

20	NO	PNP	M12	XS918R4PAM12	0.051
----	----	-----	-----	--------------	-------

Ø 30 mm, threaded M30 x 1.5

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
-----------------------------	----------	--------	------------	-----------	--------------

Three-wire 12-24V $\overline{\text{V}}$, flush mountable

20	NO	PNP	M12	XS930R1PAM12	0.140
----	----	-----	-----	--------------	-------

Three-wire 12-24V $\overline{\text{V}}$, non flush mountable

40	NO	PNP	M12	XS930R4PAM12	0.144
----	----	-----	-----	--------------	-------

Connecting cables (PUR) (1)


Description	Type	Length m	Reference	Weight kg
Pre-wired M12 connectors Female, 4-pin Metal clamping	Straight	2	XZCP1141L2	0.090
		5	XZCP1141L5	0.190
		10	XZCP1141L10	0.370
	Elbowed	2	XZCP1241L2	0.090
		5	XZCP1241L5	0.190
		10	XZCP1241L10	0.370

Wiring schemes

M12 connector



PNP



(1) For further information, please consult our site www.tesensors.com.

Inductive proximity sensors

XS range, Application

Cylindrical, stainless steel 303 front face
for harsh industrial environments

Three-wire DC, solid-state output

Characteristics						
Sensor type	Flush		XS908R1PAM12	XS912R1PAM12	XS918R1PAM12	XS930R1PAM12
	Non flush		XS908R4PAM12	XS912R4PAM12	XS918R4PAM12	XS930R4PAM12
Product certifications			CE, cULus			
Connection	Connector		M12			
Operating zone	Flush	mm	0...2.4	0...4.8	0...8	0...16
	Non flush	mm	0...4.8	0...8	0...16	0...32
Differential travel		%	1...15 (real sensing distance Sr)			
Degree of protection	Conforming to IEC 60529		IP 67	IP 68 (5 meters underwater for 1 month)		
	Conforming to DIN 40050		IP 69K			
Storage temperature		°C	-25...+ 70 (-13...158°F)			
Operating temperature		°C	-25...+ 70 (-13...158°F)			
Materials	Case		Stainless steel, 303 grade			
Front face thickness		mm	0.25	0.4	0.6	1.0
Mechanical shock resistance	Conforming to IEC 62262		IK10			
Vibration resistance	Conforming to IEC 60068-2-6		25 gn, amplitude ± 1 mm (f = 10 to 55 Hz)			
Shock resistance	Conforming to IEC 60068-2-27		30 gn, duration 11 ms			
Output state indication			Yellow LED, 4 viewing points at 90° (blinking from 0.8 Sr and Sr)			
Rated supply voltage		V	12...24 with protection against reverse polarity			
Voltage limits (including ripple)		V	10...30			
Switching capacity		mA	≤ 200 with overload and short-circuit protection			
Voltage drop, closed state		V	≤ 2			
Current consumption, no-load		mA	≤ 10			
Maximum switching frequency	Flush	Hz	1000	600	300	100
	Non flush	Hz	700	400	200	90
Delays	First set-up	ms	40			
	Response	µs	0.05	0.06		
	Recovery	µs	23	15		

Setting-up

Minimum mounting distances in mm, flush version

Side by side		Face to face		Facing a metal object		Mounted in a metal support	
Ø 8	e ≥ 14		e ≥ 15		e ≥ 10		d ≥ 12
Ø 12	e ≥ 38		e ≥ 30		e ≥ 20		d ≥ 24
Ø 18	e ≥ 42		e ≥ 40		e ≥ 30		d ≥ 50
Ø 30	e ≥ 80		e ≥ 70		e ≥ 60		d ≥ 90

Minimum mounting distances in mm, non flush version

Side by side		Face to face		Facing a metal object		Mounted in a metal support	
Ø 8	e ≥ 52		e ≥ 25		e ≥ 20		d ≥ 20 h ≥ 15
Ø 12	e ≥ 108		e ≥ 40		e ≥ 30		d ≥ 30 h ≥ 22
Ø 18	e ≥ 182		e ≥ 70		e ≥ 60		d ≥ 60 h ≥ 34
Ø 30	e ≥ 270		e ≥ 130		e ≥ 120		d ≥ 120 h ≥ 34

Dimensions

	Flush sensor				Non flush sensor			
	M8	M12	M18	M30	M8	M12	M18	M30
a (mm)	66	60	63.5	63.5	66	60	63.5	63.5
b (mm)	46	41	42	42	42	36	35	32
c (mm)	0	0	0	0	4	5	7	10

Reduction coefficient

Non flush mounted		Flush sensor				Non flush sensor			
		M8	M12	M18	M30	M8	M12	M18	M30
Steel		1	1	1	1	1	1	1	1
Aluminum		1	1	1	1	1	1	1	1
Brass		1.35	1.3	1.2	1.3	1.4	1.4	1.35	1.2
Copper		0.9	0.85	0.8	0.9	0.85	0.8	0.9	0.9
Stainless steel	Thickness 1 mm	0.3	0.5	0.5	0.35	0.3	(1)	0.3	(1)
	Thickness 2 mm	0.6	0.9	0.9	0.7	0.9	0.66	0.6	0.25
Flush mounted		M8	M12	M18	M30	(1) No detection.			
Steel		1	0.7	0.75	0.9				
Aluminum		0.9	1.15	0.9	0.7				
Brass		0.9	1.05	0.75	0.6				
Stainless steel		1	0.8	0.8	1.3				

Inductive proximity sensors

XS range, Application

For assembly, packaging and light material handling

Plastic case, 12 x 26 x 40 mm

DC supply, solid-state output

Sensor		Flush mountable in metal			Non flush mountable in metal		
Nominal sensing distance (Sn)		2 mm			4 mm		
References							
3-wire	PNP NO	XS7G12PA140	–	XS7G12PA140S	XS8G12PA140	–	XS8G12PA140S
	NPN NO	XS7G12NA140	–	XS7G12NA140S	XS8G12NA140	–	XS8G12NA140S
4-wire (complementary outputs)	PNP NO + NC	–	XS7G12PC440	–	–	XS8G12PC440	–
	NPN NO + NC	–	XS7G12NC440	–	–	XS8G12NC440	–
Weight (kg)		0.100	0.100	0.030	0.100	0.100	0.030
Characteristics							
Product certifications		CSA, UL, CE					
Connection	Pre-cabled	3 x 0.34 mm², length 2 m (1)	4 x 0.34 mm², length 2 m (1)	–	3 x 0.34 mm², length 2 m (1)	4 x 0.34 mm², length 2 m (1)	–
	Connector	–	–	M8	–	–	M8
Operating zone		0...1.6 mm			0...3.2 mm		
Repeat accuracy		≤ 10 % of Sr					
Differential travel		3...20 % of Sr					
Degree of protection		IP 67					
Storage temperature		- 40...+ 85 °C					
Operating temperature		- 25...+ 70 °C					
Materials		Case: PBT, cable: PVC					
Vibration resistance Conforming to IEC 60068-2-6		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)					
Shock resistance Conforming to IEC 60068-2-27		50 gn, duration 11 ms					
Output state indication		Yellow LED (on top of case)					
Rated supply voltage		≐ 12...24 V	≐ 12...48 V	≐ 12...24 V	≐ 12...24 V	≐ 12...48 V	≐ 12...24 V
Voltage limits (including ripple)		≐ 10...30 V	≐ 10...58 V	≐ 10...30 V	≐ 10...30 V	≐ 10...58 V	≐ 10...30 V
Current consumption, no-load		≤ 10 mA					
Switching capacity		0...100 mA (2)	0...200 mA (2)	0...100 mA (2)	0...100 mA (2)	0...200 mA (2)	0...100 mA (2)
Voltage drop, closed state		≤ 1.8 V	≤ 2.6 V	≤ 1.8 V	≤ 1.8 V	≤ 2.6 V	≤ 1.8 mA
Maximum switching frequency		≤ 2 kHz			≤ 1 kHz		
Delays	First-up	≤ 4 ms					
	Response	≤ 0.5 ms					
	Recovery	≤ 1 ms					

(1) Sensors available with other cable lengths:

Length of cable	Suffix to be added to references stated above for 2 m pre-cabled sensors	Weight increase
5 m	L1	0.120 kg
10 m	L2	0.320 kg

Example: sensor XS7G12PA140 with 5 m long cable becomes XS7G12PA140L1.

(2) With overload and short-circuit protection

Inductive proximity sensors

XS range, Application


For assembly, packaging and light material handling

Plastic case, 12 x 26 x 40 mm


DC supply, solid-state output

Dimensions

XS● G12●A140, XS● G12●C440



Rear view




(1) 1 elongated hole $\varnothing 3.1 \times 5.1$.


(2) Cable L = 2 m.

(3) 2 holes M3 x 5.

XS● G12●A140S



Rear view






(1) 1 elongated hole $\varnothing 3.1 \times 5.1$.

(2) 2 holes M3 x 5.

Setting-up

Minimum mounting distances (mm)



Side by side

Face to face

Facing a metal object and mounting in a metal support

XS7G flush mountable

$e \geq 0$

$e \geq 15$

$e \geq 6$

XS8G non flush mountable

$e \geq 10$





$e \geq 60$

$e \geq 12$

Wiring schemes

3-wire ---, NO output

4-wire ---, NO + NC output



Connector

M8





Inductive proximity sensors

XS range, Application

For assembly, packaging and light material handling

Plastic case, 12 x 26 x 40 mm

AC or DC supply

Sensor		Flush mountable in metal	Non flush mountable in metal
			
Nominal sensing distance (Sn)		2 mm	4 mm
References			
2-wire $\overline{\text{---}}$ or $\sim$	NO	XS7G12MA230	XS8G12MA230
	NC	XS7G12MB230	XS8G12MB230
Weight (kg)		0.100	0.100
Characteristics			
Product certifications		CSA, UL, CEC	
Connection		Pre-cabled, 2 x 0.34 mm ² , length 2 m (1)	
Operating zone		0...1.6 mm	0...3.2 mm
Repeat accuracy		≤ 10 % of Sr	
Differential travel		3...20 % of Sr	
Degree of protection		IP 67	
Storage temperature		- 40...+ 85 °C	
Operating temperature		- 25...+ 70 °C	
Materials		Case: PBT, cable: PVC	
Vibration resistance		25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)	
Shock resistance		50 gn, duration 11 ms	
Conforming to IEC 60068-2-27			
Output state indication		Yellow LED (on top of case)	
Rated supply voltage		$\sim$ 24...240 V (50/60 Hz) or $\overline{\text{---}}$ 24...210 V	
Voltage limits (including ripple)		$\sim$ or $\overline{\text{---}}$ 20...264 V	
Switching capacity		5...200 mA (2)	
Voltage drop, closed state		≤ 5.5 V	
Residual current, open state		≤ 0.8 mA/24 V, 1.5 mA/120 V	
Maximum switching frequency		$\sim$ 25 Hz or $\overline{\text{---}}$ 250 Hz	
Delays	First-up	≤ 40 ms	
	Response	≤ 1 ms	
	Recovery	≤ 2 ms	

(1) Sensors available with other cable lengths:

Length of cable	Suffix to be added to references stated above for 2 m pre-cabled sensors	Weight increase
5 m	L1	0.120 kg
10 m	L2	0.320 kg

Example: sensor **XS7G12MA230** with 5 m long cable becomes **XS7G12MA230L1**.

(2) These sensors do not incorporate overload or short-circuit protection and therefore, it is essential to connect a 0.4 A "quick-blow" fuse in series with the load.

Inductive proximity sensors

XS range, Application


For assembly, packaging and light material handling

Plastic case, 12 x 26 x 40 mm

AC or DC supply

Dimensions

XS●G12M●230



Rear view




(1) 1 elongated hole $\varnothing 3.1 \times 5.1$.

(2) Cable $L = 2\text{ m}$.

(3) 2 holes $M3 \times 5$.

Setting-up


Minimum mounting distances (mm)



	Side by side	Face to face	Facing a metal object and mounting in a metal support
XS7G flush mountable	$e \geq 0$	$e \geq 15$	$e \geq 6$
XS8G non flush mountable	$e \geq 10$	$e \geq 60$	$e \geq 12$

Wiring schemes

2-wire $\sim$ or --- , NO or NC output




Inductive proximity sensors

XS range, Application

Flat sensor, flush mountable, increased range, switching capacity 300 mA

80 x 80 x 40 format, DIN rail mounting, solid-state output

Sensor		Flush mountable in metal
		
Dimensions (mm)		80 x 80 x 40
Nominal sensing distance (Sn)		50 mm (not flush mounted: 42 mm)
Reference		
2-wire $\overline{\text{---}}$ (non polarised)	NO	XS7D1A3CAM12DIN
Weight (kg)		0.374
Characteristics		
Product certifications		CE
Degree of protection	Conforming to IEC 60529	IP 67, double insulation $\square$
Temperature	Operating	- 25...+ 70 °C
	Storage	- 40...+ 85 °C
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10 to 55 Hz)
Shock resistance	Conforming to IEC 60068-2-27	50 gn, duration 11 ms
Connection		M12 connector
Operating zone		0...40 mm (not flush mounted: 0...35 mm)
Repeat accuracy		3 % of Sr
Differential travel		1...15 % of Sr
Output state indication		Yellow LED
Rated supply voltage		$\overline{\text{---}}$ 12...48 V with protection against reverse polarity
Voltage limits (including ripple)		$\overline{\text{---}}$ 10...58 V
Residual current, open state		≤ 0.5 mA
Switching capacity		1.5...300 mA with overload and short-circuit protection
Voltage drop, closed state		≤ 4.5 V
Maximum switching frequency		100 Hz
Delays	First-up	≤ 10 ms
	Response	≤ 2 ms
	Recovery	≤ 5 ms

Inductive proximity sensors


XS range, Application

Flat sensor, flush mountable, increased range, switching capacity 300 mA

80 x 80 x 40 format, DIN rail mounting, solid-state output

Dimensions

XS7D1A3CAM12DIN



(1) Output LED

(2) For CHC type screws

Setting-up

Minimum mounting distances (mm)

	Face to face	Side by side	Back to back	Facing a metal object
Flush mounted	450	140	90	150
Not flush mounted	450	180	180	150

Flush/non flush conditions


In A37 steel



Sn	Su	Sn	Su
42 mm	35 mm	50 mm	40 mm

Wiring schemes

2-wire NO/M12 XS7D1A3CAM12DIN




Inductive proximity sensors

XS range, Application


Cylindrical, stainless steel 303 front face

for welding environments


Three-wire DC, solid-state output




XS912RWPAM12



XS918RWPAM12



XZCP1141L●



XZCP1241L●

Ø 12 mm, threaded M12 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire 12-24V $\overline{\text{V}}$, flush mountable					
6	NO	PNP	M12	XS912RWPAM12	0.024

Ø 18 mm, threaded M18 x 1

Sensing distance (Sn) mm	Function	Output	Connection	Reference	Weight kg
Three-wire 12-24V $\overline{\text{V}}$, flush mountable					
10	NO	PNP	M12	XS918RWPAM12	0.051

Connecting cables (PUR) ⁽¹⁾


Description	Type	Length m	Reference	Weight kg
Pre-wired M12 connectors Female, 4-pin Metal clamping ring	Straight	2	XZCP1141L2	0.090
		5	XZCP1141L5	0.190
		10	XZCP1141L10	0.370
	Elbowed	2	XZCP1241L2	0.090
		5	XZCP1241L5	0.190
		10	XZCP1241L10	0.370

Wiring schemes

M12 connector



PNP



(1) For further information, please consult our site www.tesensors.com.

Inductive proximity sensors

XS range, Application

Cylindrical, stainless steel 303 front face

for welding environments

Three-wire DC, solid-state output

Characteristics


Sensor type		Flush	XS912RWPAM12	XS918RWPAM12	
Product certifications			CE, cULus		
Connection		Connector	M12		
Operating zone			mm	0...4.8	0...8
Differential travel			%	1...15 (real sensing distance Sr)	
Degree of protection		Conforming to IEC 60529	IP 68 (5 meters underwater for 1 month)		
		Conforming to DIN 40050	IP 69K		
Storage temperature			°C	-25...+ 70 (-13...158°F)	
Operating temperature			°C	-25...+ 70 (-13...158°F)	
Materials		Case	Stainless steel, 303 grade		
Front face thickness			mm	0.4	0.6
Mechanical shock resistance		Conforming to IEC 62262	IK10		
Vibration resistance		Conforming to IEC 60068-2-6	25 gn, amplitude ± 1 mm (f = 10 to 55 Hz)		
Shock resistance		Conforming to IEC 60068-2-27	30 gn, duration 11 ms		
Output state indication			Yellow LED, 4 viewing points at 90° (blinking from 0.8 Sr and Sr)		
Rated supply voltage			V	12...24 with protection against reverse polarity	
Voltage limits (including ripple)			V	10...30	
Switching capacity			mA	≤ 200 with overload and short-circuit protection	
Voltage drop, closed state			V	≤ 2	
Current consumption, no-load			mA	≤ 10	
Maximum switching frequency			Hz	15	
Delays		First set-up	ms	80	
		Response	µs	100	
		Recovery	µs	15	

Setting-up

Minimum mounting distances in mm, flush version


Side by side

$$\frac{\varnothing 12}{\varnothing 18} \quad \frac{e \geq 38}{e \geq 42}$$




Face to face

$$\frac{e \geq 30}{e \geq 40}$$




Facing a metal object

$$\frac{e \geq 20}{e \geq 30}$$




Mounted in a metal support

$$\frac{d \geq 24}{d \geq 50}$$



Dimensions



Lengths (mm):
a = overall
b = threaded
c = for non flush mountable sensors

	Flush sensor	
	M12	M18
a (mm)	60	63.5
b (mm)	41	42
c (mm)	0	0

Reduction coefficient

Non flush mounted

Steel
Aluminum
Brass
Copper
Stainless steel

Thickness 1 mm
Thickness 2 mm

Flush sensor


	M12	M18
1	1	1
1	1	1
1.3	1.2	1.2
0.85	0.8	0.8
0.5	0.5	0.5
0.9	0.9	0.9

Flush mounted


Steel
Aluminum
Brass
Stainless steel

	M12	M18
0.7	0.75	0.75
1.15	0.9	0.9
1.05	0.75	0.75
0.8	0.8	0.8

Flush mountable in metal



Lengths (mm):
a = Overall
b = To shoulder
c = Removal
d = Shoulder



Ø = 12
a = 55
b = 50
c = 9 (threaded end)
d = 15 hexagonal

Nominal sensing distance (Sn)

3 mm

References


2-wire $\overline{\text{---}}$ (non polarised) Terminal connections	1-4	NO	XSLC1401393L3
Weight (kg)	0.065		



Characteristics

Connection	Remote M12 connector on 0.8 m flying lead
Degree of protection conforming to IEC 60529	IP 67
Operating zone	0...2.4 mm
Repeat accuracy	$\leq 3\%$ of Sr
Differential travel	1...15 % of Sr
Operating temperature	-25...+80 °C
Output state indication	Yellow LED, annular
Rated supply voltage	$\overline{\text{---}}$ 12...48 V
Voltage limits (including ripple)	$\overline{\text{---}}$ 10...58 V
Switching capacity	1.5...100 mA with overload and short-circuit protection
Voltage drop, closed state	≤ 4 V
Residual current, open state	≤ 0.5 mA
Current consumption, no-load	—
Maximum switching frequency	800 Hz
Delays	First-up: ≤ 5 ms; response: ≤ 05 ms; recovery: ≤ 0.5 ms

Wiring schemes





2-wire $\overline{\text{---}}$, non polarised, NO output



Flush mountable in metal		Non flush mountable in metal	
			
$\varnothing = 18$ $a = 40$ $b = 35$ $c = 0$ (PPS front face) $d = \varnothing 22$		$\varnothing = 18$ $a = 45$ $b = 35$ $c = 20$ (Teflon front face and case) $d = \varnothing 22$	
6.3 mm		10 mm	
XSLC1401392L1		XSLC1401405L3	
0.100		0.065	
Remote M12 connector on 1.2 m flying lead		Remote M12 connector on 0.8 m flying lead	
IP 67		Remote M12 connector on 0.15 m flying lead	
0...5 mm		0...8 mm	
3 % of Sr			
1...15 % of Sr			
-25...+70 °C			
Yellow LED, annular			
--- 12...48 V			
--- 10...58 V			
1.5...100 mA with overload and short-circuit protection			
≤ 4 V			
≤ 0.5 mA			
-			
100 Hz			
First-up: ≤ 10 ms; response: ≤ 10 ms; recovery: ≤ 2 ms			

Setting-up

Minimum mounting distances (mm)




		Side by side	Face to face	Facing a metal object	Mounted in a metal support
					
XSLC	Ø 12 (flush mountable)	$e \geq 10$	$e \geq 60$	$e \geq 15$	$d = 12, h = 0$
	Ø 18 (non flush mountable)	$e \geq 16$	$e \geq 96$	$e \geq 24$	$d = 54, h = 16$

Inductive proximity sensors

XS range

Detection at fixed sensing distance. Factor 1 (Fe/Nfe) sensors ⁽¹⁾ for ferrous and non ferrous materials
Solid-state output

Flush mountable in metal



Lengths (mm):
a = Overall
b = Threaded section

a = 60
b = 51.5
Ø = M18 x 1

a = 70
b = 51.5
Ø = M18 x 1

	Brass case	Brass case
Nominal sensing distance (Sn)	5 mm	5 mm

References

4-wire	PNP/PNP programmable NO/NC	XS1M18KPM40	XS1M18KPM40D
Weight (kg)		0.120	0.060

Characteristics

Product certifications		CE, UL, CSA	
Connection		Pre-cabled, PvR 4 x 0.34 mm², length 2 m (2)	M12 connector
Degree of protection	Conforming to IEC 60529	IP 68	IP 67
Operating zone		0...4 mm	
Repeat accuracy		3 % of Sr	
Differential travel		1...15 % of Sr	
Operating temperature		0...+ 50 °C	
Output state indication		Yellow LED, annular	Yellow LED, 4 viewing ports at 90°
Rated supply voltage		--- 12...24 V with protection against reverse polarity	
Voltage limits (including ripple)		--- 10...38 V	
Switching capacity		0...200 mA with overload and short-circuit protection	
Voltage drop, closed state		≤ 2.6 V	
Current consumption, no-load		≤ 15 mA	
Maximum switching frequency		1000 Hz	
Delays	First-up	≤ 10 ms	
	Response	≤ 0.3 ms	
	Recovery	≤ 0.7 ms	

Wiring schemes

M12 connector	Pre-cabled	4-wire, PNP/NPN, NO or NC output
	BN: brown BU: blue BK: black WH: white	PNP BN/1 (NO), BU/3 (NC) + WH/2 BK/4 BU/3 (NO), BN/1 (NC) - NPN BN/1 (NO), BU/3 (NC) + WH/2 BK/4 BU/3 (NO), BN/1 (NC) -


⁽¹⁾ The variation in sensing distance between ferrous and non ferrous materials is typically less than 5 %.

⁽²⁾ Sensors available with other cable lengths: please consult our Customer Care Centre.

Inductive proximity sensors


XS range

Detection at fixed sensing distance. Factor 1 (Fe/Nfe)
sensors ⁽¹⁾ for ferrous and non ferrous materials
Solid-state output



a = 60
b = 51.5
Ø = M30 x 1.5

Stainless steel case
10 mm



a = 60
b = 51.5
Ø = M30 x 1.5

Stainless steel case
10 mm

References

XS1M30KPM40

0.205

XS1M30KPM40LD

0.145

Characteristics

C€, UL, CSA

Pre-cabled, PvR 4 x 0.34 mm², length 2 m ⁽²⁾

IP 68

0...8 mm

3 % of Sr

1...15 % of Sr

0...+ 50 °C

Yellow LED, annular

--- 12...24 V with protection against reverse polarity

--- 10...38 V

0...200 mA with overload and short-circuit protection

≤ 2.6 V

≤ 15 mA

1000 Hz

≤ 5 ms

≤ 0.3 ms

≤ 0.7 ms

M12 connector on 0.8 m flying lead

IP 67

Setting-up




Minimum mounting distances (mm)

Side by side

Face to face

Facing a metal object

Mounted in a metal support



XS1M18 flush mountable

$e \geq 10$

$e \geq 60$

$e \geq 15$

$d \geq 18, h \geq 0$

XS1M30 flush mountable

$e \geq 20$

$e \geq 120$

$e \geq 30$

$d \geq 30, h \geq 0$

Fixing nut tightening torque: XS1M18: < 35 N.m, XS1M30: < 100 N.m

⁽¹⁾ The variation in sensing distance between ferrous and non ferrous materials is typically less than 5 %.



⁽²⁾ Sensors available with other cable lengths: please consult our Customer Care Centre.

Inductive proximity sensors

XS range, Application

Factor 1 sensors for ferrous or non ferrous material detection and welding applications. Plastic case, 40 x 40 mm front face. 5 position turret head

Sensor	Flush mountable in metal	
Dimensions	40 x 40 x 70 mm	40 x 40 x 117 mm



Nominal sensing distance (Sn)	20 mm
--------------------------------------	-------

References

4-wire ☐	PNP NO+NC	XS9C2A1PCM12	XS9C4A1PCP20 (1)
	NPN NO+NC	XS9C2A1NCM12	XS9C4A1NCP20 (1)


XS9C4●●●P20 sensors are available with an ISO M20 cable entry and can be supplied with a Pg 13.5 (e.g. **XS9C4A1PCG13**) or a 1/2" NPT (e.g. **XS9C4A1PCN12**) cable entry: please consult our Customer Care Centre for more information.

Weight (kg)	0.110	0.220
--------------------	-------	-------

Characteristics

Product certifications	UL, CSA, CE	
Conformity to standards	IEC 60947-5-2	
Connection	M12 connector (4-pin)	Screw terminals, clamping capacity 4 x 1.5 mm ² / 4 x 16 AWG
Operating zone	0...16 mm	
Differential travel	3...15% of Sr	
Repeat accuracy	< 3%	
Immunity to magnetic fields	< 250 mTesla	
Degree of protection	Conforming to IEC 60529 and DIN 40050	IP 65, IP 67 and IP 69K
Temperature	Storage	- 40...+ 85°C
	Operation (2)	- 25...+ 70°C
Material	Case: PBT	
Vibration resistance	Conforming to IEC 60068-2-6	25 gn, amplitude ± 2 mm (f = 10...55 Hz)
Shock resistance	Conforming to IEC 60068-2-27	50 gn for 11 ms
Indicators	Output state: yellow LED. Supply on: green LED	
Rated supply voltage	4-wire ☐	☐ 12...24 V with protection against reverse polarity
Voltage limits (including ripple)	4-wire ☐	☐ 10...36 V
Current consumption, no-load	4-wire ☐	< 30 mA
Switching capacity	4-wire ☐	< 200 mA with protection against overload and short-circuit
Voltage drop, closed state	4-wire ☐	< 2 V
Maximum switching frequency	4-wire ☐	250 Hz
Delays	First-up	< 15 ms
	Response	< 2.5 ms
	Recovery	< 2.5 ms

Setting-up



(1) These sensors are supplied without a cable gland. A suitable Pg 13.5 cable gland is available (reference **XSZPE13**).

(2) Sensors are available for very low temperatures (suffix **TF**: - 40°C, + 70°C) or very high temperatures (suffix **TT**: - 25°C, + 85°C); please consult our Customer Care Centre.

Inductive proximity sensors

XS range, Application

Factor 1 sensors for ferrous or non ferrous material detection and welding applications. Plastic case, 40 x 40 mm front face. 5 position turret head

Setting-up (continued)

Minimum mounting distances (mm)

	Side by side	Face to face	Facing a metal object
Sensors flush mountable in metal	$e \geq 80$	$e \geq 200$	$e \geq 60$



Wiring schemes

M12 connector




- 1: + V
- 2: NC Output
- 3: 0 V
- 4: NO Output

4-wire $\overline{\text{NO}}$, NO + NC outputs



Accessories



XSZPSC2




XSZPKC2

Description	Use for	Reference	Weight kg
Stainless steel rigid protective cover (only suitable for use when detecting from the top)	Welding	XSZPSC2	0.010
Protective sheet (for sensing face of sensor)	Welding	XSZPKC2	0.010

Sold in lots of 5


Dimensions

XS9C2A1PCM12 and XS9C2A1NCM12




Head positions


XS9C2A1PCM12 and XS9C2A1NCM12



XS9C4A1PCP20 and XS9C4A1NCP20



XS9C4A1PCP20 and XS9C4A1NCP20



(1) 2 elongated holes $\varnothing 5.3 \times 7$ mm.

Tightening torque of cover fixing screws and clamp screws: $< 1.2 \text{ N.m} / < 10.62 \text{ lb-in}$.

Inductive proximity sensors

XS range, Application


Selective detection of ferrous materials

Selective detection of non ferrous materials

Cylindrical type, solid-state output

Flush mountable

Stainless steel case



Nominal sensing distance (Sn)	5 mm
-------------------------------	------

References

3-wire, ferrous version	PNP	NO	XS1M18PAS40
Insensitive to non ferrous materials			
3-wire, non ferrous version	PNP	NO	XS1M18PAS20
Insensitive to ferrous materials			
Weight (kg)	0.120		


Characteristics

Product certifications	UL, CSA, CEC
Connection	Pre-cabled, PvR, 3 x 0.34 mm ² , length 2 m (1)
Operating zone	0...4 mm
Degree of protection conforming to IEC 60529	IP 68
Operating temperature	-25...+70 °C
Output state indication	Yellow LED, annular
Rated supply voltage	12...24 V with protection against reverse polarity
Voltage limits (including ripple)	10...38 V
Switching capacity	0...200 mA with overload and short-circuit protection
Voltage drop, closed state	≤ 2.6 V
Residual current, open state	—
Current consumption, no-load	≤ 15 mA
Maximum switching frequency	1000 Hz
Delays	First-up
	Response
	Recovery
	≤ 10 ms
	≤ 0.3 ms
	≤ 0.7 ms

(1) Sensors available with other cable lengths: please consult our Customer Care Centre.


Wiring schemes

3-wire PNP



Dimensions


XS1M



a (mm)	b (mm)
60	51.5


Setting-up

Minimum mounting distances (mm)




Side by side

$e \geq 10$




Face to face

$e \geq 60$



Facing a metal object

$e \geq 15$



Mounted in a metal support

$d \geq 18$, $h \geq 0$ (ferrous metal)
 $d \geq 18$, $h \geq 5$ (non ferrous metal)

Inductive proximity sensors

XS range, Application


Selective detection of ferrous materials

Selective detection of non ferrous materials

Cylindrical type, solid-state output

Flush mountable

Stainless steel case



Nominal sensing distance (Sn) 5 mm

References

3-wire, ferrous version Insensitive to non ferrous materials	PNP NO	XS1M18PAS40D
3-wire, non ferrous version Insensitive to ferrous materials	PNP NO	XS1M18PAS20D
Weight (kg)		0.060


Characteristics

Product certifications	UL, CSA, CE
Connection	M12 connector
Degree of protection conforming to IEC 60529	IP 67
Operating zone	0...4 mm
Operating temperature	-25...+70 °C
Output state indication	Yellow LED, 4 viewing ports at 90°
Rated supply voltage	12...24 V with protection against reverse polarity
Voltage limits (including ripple)	10...38 V
Switching capacity	0...200 mA with overload and short-circuit protection
Voltage drop, closed state	≤2.6 V
Residual current, open state	—
Current consumption, no-load	≤15 mA
Maximum switching frequency	1000 Hz
Delays	
First-up	≤10 ms
Response	≤0.3 ms
Recovery	≤0.7 ms

Wiring schemes


M12 connector

3-wire PNP



Dimensions


XS1M



a (mm)	b (mm)
70	51.5


Setting-up

Minimum mounting distances (mm)




Side by side

$e \geq 10$




Face to face

$e \geq 60$



Facing a metal object


$e \geq 15$



Mounted in a metal support

$d \geq 18$, $h \geq 0$ (ferrous metal)
 $d \geq 18$, $h \geq 5$ (non ferrous metal)

XS1M18



Mounting and fixing accessories

Description	For use with sensor		Unit reference	Weight kg	
	Type	Diameter (mm)			
“Clip” mounting plate Can be mounted without “clip” on threaded holes	XS●J	—	XSZBJ00	0.003	
	XS●F	—	XSZBF00	0.005	
	XS●E	—	XSZBE00	0.025	
	XS●C	—	XSZBC00	0.060	
“Clip” 90° mounting bracket Can be mounted without “clip” on threaded holes	XS●J	—	XSZBJ90	0.003	
	XS●F	—	XSZBF90	0.005	
	XS●E	—	XSZBE90	0.025	
	XS●C	—	XSZBC90	0.060	
Replacement bracket	XS●E Replaces: XS7T2, XS8T2, XSE	—	XSZBE10	0.060	
	XS●C Replaces: XS7T4, XS7C40, XS8T4, XS8C40 and XSC	—	XSZBC10	0.110	
	XS●D (for XSD) (1)	—	XSZBD10	0.065	
Fixing clamp for remote control	XS9, XS6●●●B2	—	XSZBPM12	0.015	
Fixing clamps	XS1	4 (plain)	XSZB104	0.005	
		5 (M5 x 0.5)	XSZB105	0.005	
	XS1, XS2	6.5 (plain)	XSZB165	0.005	
	XS1, XS2, XS4, XS5, XS6	8 (M8 x 1)	XSZB108	0.006	
	XS1, XS2, XS4, XS5, XS6, XT1	12 (M12 x 1)	XSZB112	0.006	
		18 (M18 x 1)	XSZB118	0.010	
		30 (M30 x 1.5)	XSZB130	0.020	
	XT1	32 (plain)	XUZB32	0.050	
	Set of 2 metal fixing nuts, nickel plated	XS1	5 (M5 x 0.5)	XSZE105	0.010
		XS1, XS2, XS5, XS6	8 (M8 x 1)	XSZE108	0.015
XS1, XS2, XT1, XS5, XS6		12 (M12 x 1)	XSZE112	0.015	
		18 (M18 x 1)	XSZE118	0.020	
		30 (M30 x 1.5)	XSZE130	0.050	
Set of 2 stainless steel fixing nuts	XS1, XS2, XS5, XS6	8 (M8 x 1)	XSZE308	0.015	
	XS1, XS2, XT1, XS5, XS6	12 (M12 x 1)	XSZE312	0.015	
		18 (M18 x 1)	XSZE318	0.020	
			30 (M30 x 1.5)	XSZE330	0.050
Set of 2 plastic fixing nuts	XS4	8 (M8 x 1)	XSZE208	0.002	
		12 (M12 x 1)	XSZE212	0.003	
	XS4	18 (M18 x 1)	XSZE218	0.004	
			30 (M30 x 1.5)	XSZE230	0.005
Adaptor collar	Ø 20 XS●, XT●	18 (M18 x 1)	XSZA020	0.005	
	Ø 34 XS●, XT●	30 (M30 x 1.5)	XSZA034	0.005	

Protection accessories

Cable sleeve adaptor (CNOMO type)	XS●, XT●	12 (M12 x 1)	XSZP112	0.005
		18 (M18 x 1)	XSZP118	0.005
		30 (M30 x 1.5)	XSZP130	0.010
Outer cover (IP 68)	XT7, XS7, XS8 and XS9 – (C format)		XSCZ01	0.100
Thread adaptor	XS●, XT●	30 (M30 x 1.5)	XTAZ30	0.035
13P cable gland	Clamping capacity Ø 9 to 12 mm		XSZPE13	0.010
Protective cover	M12 universal connectors		XSZF10	0.020


Sold in lots of 50

Fuses (for unprotected 2-wire ~ sensors)


Description	Type	Sold in lots of	Unit reference	Weight kg
Cartridge fuses 5 x 20	0.4 A "quick-blow"	10	XUZE04	0.001
	0.63 A "quick-blow"	10	XUZE06	0.001
	0.8 A "quick-blow"	10	XUZE08	0.001
Fuse terminal block for XUZE0●		50	AB1FU10135U	0.040

(1) Depth adjustment shim for converting 80 x 80 x 26 mm format to 80 x 80 x 40 mm format. Also enables clipping onto 35 mm omega rail.


XSZBJ00




XSZBF00



XSZBE00




XSZBC00




(1) 2 screws M3 x 12 (included).

(1) 4 screws M4 x 14 (included).


XSZBJ90




XSZBF90



XSZBE90




XSZBC90




(1) 2 screws M3 x 12 (included).

(1) 4 screws M4 x 14 (included).


XSZBE10




XSZBC10




XSZBD10 (for mounting on XS●D●●●●)




XSZBPM12



XSZB104, XSZB105



XSZB108, XSZB112, XSZB118, XSZB130, XSZB165




XSZ	a	a1	b	b1	b2	Ø
B108	19.9	14.5	14	12.5	7.5	8
B112	21.9	14.5	16	15.5	8.5	12
B118	26	15.7	22.3	20.1	11.5	18
B130	39	21.7	35.5	31	18.5	30
B165	19.9	14.5	14	12.5	7.5	6.5

(1) 2 elongated holes 4 x 8 mm.

XSZ	Ø
B104	4
B105	5

Note: for fixing clamps XSZB118 and XSZB130, see mounting precautions, page 19.

XUZB32




(1) Maximum value

(2) 2 holes Ø 5.5


2 x M5 screws, HM head, included with fixing clamp

XSZA0●●




XSZ	a	a1
A020	Ø18	Ø20
A034	Ø30	Ø34

XSZP112, XSZP118, XSZP130




XSZ	h	Ø d1	Ø d2
P112	7	12	16,8
P118	6,2	18	23
P130	6,2	30	34,4

XSCZ01



XTAZ30



(1) 13P cable gland

Substitution table

Sensors with the closest functionalities

Inductive proximity sensors

Old sensor	New XS sensor	Old sensor	New XS sensor	Old sensor	New XS sensor
Cylindrical type, DC					
Diameter 6.5 mm					
XS1					
XS1L06NA340	XS506B1NAL2	XS1M08NA370	XS508BLNAL2	XS1N08PB349L1	XS108B3PBL5
XS1L06NA340S	XS506B1NAM8	XS1M08NA370D	XS508BLNAM12	XS1N08PB349D	XS108B3PBM12
XS1L06NB340	XS506B1NBL2	XS1M08NA370L1	XS508BLNAL5	XS1N08PB349S	XS108B3PBM8
XS1L06NB340S	XS506B1NBM8	XS1M08NB370	XS508BLNBL2		
XS1L06PA340	XS506B1PAL2	XS1M08NB370D	XS508BLNBM12		
XS1L06PA340L1	XS506B1PAL5	XS1M08PA370	XS508BLPAL2	XS2	
XS1L06PA340D	XS506B1PAM12	XS1M08PA370D	XS508BLPAM12	XS2M08NA340	XS608B1NAL2
XS1L06PA340S	XS506B1PAM8	XS1M08PA370L1	XS508BLPAL5	XS2N08NA340	XS108B3NAL2
XS1L06PB340	XS506B1PBL2	XS1M08PA370L2	XS508BLPAL10	XS2N08NA340D	XS108B3NAM12
XS1L06PB340L1	XS506B1PBL5	XS1M08PA370LD	XS508BLPAM12 (1)	XS2N08NA340L1	XS108B3NAL5
XS1L06PB340S	XS506B1PBM8	XS1M08PA370S	XS508BLPAM12 (2)	XS2N08NA340L2	XS108B3NAL10
		XS1M08PB370	XS508BLPBL2	XS2N08NA340S	XS108B3NAM8
		XS1M08PB370D	XS508BLPBM12	XS2N08NB340	XS108B3NBL2
		XS1M08PB370L1	XS508BLPBL5	XS2N08NB340D	XS108B3NBM12
		XS1M08PB370L2	XS508BLPBL10	XS2N08NB340S	XS108B3NBM8
				XS2N08PA340	XS108B3PAL2
XS1L06NA349	XS106B3NAL2			XS2N08PA340D	XS108B3PAM12
XS1L06NA349S	XS106B3NAM8	XS1N08NA340	XS508B1NAL2	XS2N08PA340L1	XS108B3PAL5
XS1L06NB349	XS106B3NBL2	XS1N08NA340D	XS508B1NAM12	XS2N08PA340L2	XS108B3PAL10
XS1L06NB349S	XS106B3NBM8	XS1N08NA340L1	XS508B1NAL5	XS2N08PA340S	XS108B3PAM8
XS1L06PA349	XS106B3PAL2	XS1N08NA340L2	XS508B1NAL10	XS2N08PB340	XS108B3PBL2
XS1L06PA349L1	XS106B3PAL5	XS1N08NA340S	XS508B1NAM8	XS2N08PB340D	XS108B3PBM12
XS1L06PA349D	XS106B3PAM12	XS1N08NB340	XS508B1NBL2	XS2N08PB340S	XS108B3PBM8
XS1L06PA349S	XS106B3PAM8	XS1N08NB340D	XS508B1NBM12		
XS1L06PB349	XS106B3PBL2	XS1N08NB340S	XS508B1NBM8		
XS1L06PB349L1	XS106B3PBL5	XS1N08PA340	XS508B1PAL2	XS3	
XS1L06PB349S	XS106B3PBM8	XS1N08PA340D	XS508B1PAM12	XS3P08NA340	XS508B1NAL2 (3)
		XS1N08PA340L1	XS508B1PAL5	XS3P08NA340D	XS508B1NAM12 (3)
		XS1N08PA340L2	XS508B1PAL10	XS3P08NA340L1	XS508B1NAL5 (3)
		XS1N08PA340LD	XS508B1PAM12	XS3P08PA340	XS508B1PAL2 (3)
		XS1N08PA340S	XS508B1PAM8	XS3P08PA340D	XS508B1PAM12 (3)
		XS1N08PB340	XS508B1PBL2	XS3P08PA340L1	XS508B1PAL5 (3)
		XS1N08PB340D	XS508B1PBM12		
		XS1N08PB340L1	XS508B1PBL5		
		XS1N08PB340L2	XS508B1PBL10		
		XS1N08PB340S	XS508B1PBM8		
				XS3P08NA370	XS508BLNAL2 (3)
				XS3P08NA370L1	XS508BLNAL5 (3)
				XS3P08PA370	XS508BLPAL2 (3)
				XS3P08PA370L1	XS508BLPAL5 (3)
XS1M08DA210	XS508B1DAL2	XS1N08NA349	XS108B3NAL2		
XS1M08DA210D	XS508B1DAM12	XS1N08NA349L1	XS108B3NAL5		
XS1M08DA210L1	XS508B1DAL5	XS1N08NA349D	XS108B3NAM12		
XS1M08DA210L2	XS508B1DAL10	XS1N08NA349S	XS108B3NAM8		
XS1M08DA210LD	XS508B1DAL08M12	XS1N08NB349	XS108B3NBL2		
XS1M08DB210	XS508B1DBL2	XS1N08NB349L1	XS108B3NBL5		
XS1M08DB210D	XS508B1DBM12	XS1N08NB349D	XS108B3NBM12		
XS1M08DB210L1	XS508B1DBL5	XS1N08NB349S	XS108B3NBM8		
XS1M08DB210LD	XS508B1DBM12 (1)	XS1N08PA349	XS108B3PAL2		
		XS1N08PA349L1	XS108B3PAL5		
		XS1N08PA349D	XS108B3PAM12		
XS1M08DA214D	XS508B1CAM12	XS1N08PA349S	XS108B3PAM8		
XS1M08DA214LD	XS508B1CAL08M12	XS1N08PB349	XS108B3PBL2		

(1) For the new sensor an integral M12 connector replaces the remote M12 connector on a 0.80 m flying lead.

(2) For the new sensor an M12 connector replaces the M8 connector.

(3) For the new sensor, the metal case replaces the plastic case.

Substitution table

Sensors with the closest functionalities

Inductive proximity sensors

Old sensor	New XS sensor	Old sensor	New XS sensor	Old sensor	New XS sensor
Cylindrical type, DC (continued)					
Diameter 12 mm					
XS1					
XS1M12DA210	XS512B1DAL2	XS1N12PA340S	XS512B1PAM12 (2)	XS2N12PC410D	XS112B3PCM12
XS1M12DA210D	XS512B1DAM12	XS1N12PB340	XS512B1PBL2	XS2N12PC410L1	XS112B3PCM12 + XZCPV1141L5
XS1M12DA210L1	XS512B1DAL5	XS1N12PB340D	XS512B1PBM12	XS2N12PC410L2	XS112B3PCM12 + XZCPV1141L10
XS1M12DA210L2	XS512B1DAL10	XS1N12PB340L1	XS512B1PBL5	XS2N12PB340	XS112B3PBL2
XS1M12DA210LA	XS512B1DAL08U78			XS2N12PB340D	XS112B3PBM12
XS1M12DA210LD	XS512B1DAL08M12	XS1M12PA349D	XS612B1PAM12	XS2N12PB340L1	XS112B3PBL5
XS1M12DB210	XS512B1DBL2	XS1N12NA349	XS112B3NAL2		
XS1M12DB210D	XS512B1DBM12	XS1N12NA349L1	XS112B3NAL5		
XS1M12DB210L1	XS512B1DBL5	XS1N12NA349D	XS112B3NAM12		
XS1M12DB210L2	XS512B1DBL10	XS1N12NB349	XS112B3NBL2	XS3	
XS1M12DB210LD	XS512B1DBL08M12	XS1N12NB349L1	XS112B3NBL5	XS3P12NA340	XS512B1NAL2 (3)
		XS1N12NB349D	XS112B3NBM12	XS3P12NA340D	XS512B1NAM12 (3)
		XS1N12PA349	XS112B3PAL2	XS3P12NA340L1	XS512B1NAL5 (3)
		XS1N12PA349L1	XS112B3PAL5	XS3P12PA340	XS512B1PAL2 (3)
		XS1N12PA349D	XS112B3PAM12	XS3P12PA340D	XS512B1PAM12 (3)
XS1M12DA214D	XS512B1CAM12	XS1N12PB349	XS112B3PBL2	XS3P12PA340L1	XS512B1PAL5 (3)
XS1M12DA214LD	XS512B1CAL08M12	XS1N12PB349L1	XS112B3PBL5		
		XS1N12PB349D	XS112B3PBM12		
				XS3P12NA370	XS512BLNAL2 (3)
XS1M12NA370	XS512BLNAL2			XS3P12NA370L1	XS512BLNAL5 (3)
XS1M12NA370D	XS512BLNAM12			XS3P12PA370	XS512BLPAL2 (3)
XS1M12NA370L1	XS512BLNAL5	XS2		XS3P12PA370L1	XS512BLPAL5 (3)
XS1M12NA370L2	XS512BLNAL10	XS2M12NA370	XS612B1NAL2		
XS1M12NA370S	XS612B1NAM12 (2)	XS2M12NA370D	XS612B1NAM12		
XS1M12NB370	XS512BLNBL2	XS2M12NA370L1	XS612B1NAL5		
XS1M12NB370D	XS512BLNBM12	XS2M12NA370L2	XS612B1NAL10		
XS1M12PA370	XS512BLPAL2	XS2M12NB370	XS612B1NBL2		
XS1M12PA370D	XS512BLPAM12	XS2M12NB370D	XS612B1NBM12		
XS1M12PA370L1	XS512BLPAL5	XS2M12PA370	XS612B1PAL2		
XS1M12PA370L2	XS512BLPAL10	XS2M12PA370D	XS612B1PAM12		
XS1M12PA370LA	XS612B1PAL08U78	XS2M12PA370L1	XS612B1PAL5		
XS1M12PA370LD	XS612B1PAL08M12	XS2M12PA370L2	XS612B1PAL10		
XS1M12PB370	XS512BLPBL2	XS2M12PA370LA	XS612B1PAL08U78		
XS1M12PB370D	XS512BLPBM12	XS2M12PA370LD	XS612B1PAL08M12		
XS1M12PB370L1	XS512BLPBL5	XS2M12PB370	XS612B1PBL2		
XS1M12PB370L2	XS512BLPBL10	XS2M12PB370D	XS612B1PBM12		
XS1M12PB370LD	XS612B1PAM12 (1)	XS2M12PB370L1	XS612B1PBL5		
		XS2M12PB370S	XS612B1PBM12 (2)		
XS1N12NA340	XS512B1NAL2	XS2N12NA340	XS112B3NAL2		
XS1N12NA340D	XS512B1NAM12	XS2N12NA340D	XS112B3NAM12		
XS1N12NA340L1	XS512B1NAL5	XS2N12NA340L1	XS112B3NAL5		
XS1N12NA340L2	XS512B1NAL10	XS2N12NA340L2	XS112B3NAL10		
XS1N12NB340	XS512B1NBL2	XS2N12NB340	XS112B3NBL2		
XS1N12NB340D	XS512B1NBM12	XS2N12NB340D	XS112B3NBM12		
XS1N12NC410L2	XS1N12NC410D + XZCPV1141L10	XS2N12NC410L1	XS2N12NC410D + XZCPV1141L5		
XS1N12PA340	XS512B1PAL2	XS2N12PA340	XS112B3PAL2		
XS1N12PA340D	XS512B1PAM12	XS2N12PA340D	XS112B3PAM12		
XS1N12PA340L1	XS512B1PAL5	XS2N12PA340L1	XS112B3PAL5		
XS1N12PA340L2	XS512B1PAL10	XS2N12PA340L2	XS112B3PAL10		
XS1N12PA340LD	XS512B1PAM12 (1)	XS2N12PC410	XS112B3PCL2		

(1) For the new sensor an integral M12 connector replaces the remote M12 connector on a 0.80 m flying lead.

(2) For the new sensor an M12 connector replaces the M8 connector.

(3) For the new sensor, the metal case replaces the plastic case.

Inductive proximity sensors

- (1) For the new sensor an integral M12 connector replaces the remote M12 connector on a 0.80 m flying lead.
- (3) For the new sensor, the metal case replaces the plastic case.
- (4) For the new sensor, connectors A, B, C and G on 0.1 m flying lead replace integral connectors A, B, C and G.

128

Sensors with the closest functionalities

Inductive proximity sensors

Old sensor	New XS sensor	Old sensor	New XS sensor	Old sensor	New XS sensor
Cylindrical type, DC (continued)		XS1N30NA340	XS530B1NAL2	XS2M30PA370G	XS630B1PAL01G (4)
Diameter 30 mm		XS1N30NA340D	XS530B1NAM12	XS2M30PA370L1	XS630B1PAL5
XS1		XS1N30NA340L1	XS530B1NAL5	XS2M30PA370L2	XS630B1PAL10
XS1M30DA210	XS530B1DAL2	XS1N30NA340L2	XS530B1NAL10	XS2M30PB370	XS630B1PBL2
XS1M30DA210B	XS530B1DAL01B (4)	XS1N30NB340	XS530B1NBL2	XS2M30PB370B	XS630B1PBL01B (4)
XS1M30DA210C	XS530B1DAL01C (4)	XS1N30NB340D	XS530B1NBM12	XS2M30PB370C	XS630B1PBL01C (4)
XS1M30DA210D	XS530B1DAM12	XS1N30PA340	XS530B1PAL2	XS2M30PB370D	XS630B1PBM12
XS1M30DA210G	XS530B1DAL01G (4)	XS1N30PA340D	XS530B1PAM12	XS2M30PB370G	XS630B1PBL01G (4)
XS1M30DA210L1	XS530B1DAL5	XS1N30PA340L1	XS530B1PAL5	XS2M30PB370L1	XS630B1PBL5
XS1M30DA210L2	XS530B1DAL10	XS1N30PA340L2	XS530B1PAL10	XS2M30PB370L2	XS630B1PBL10
XS1M30DA210LD	XS530B1DAL08M12	XS1N30PB340	XS530B1PBL2		
XS1M30DB210	XS530B1DBL2	XS1N30PB340D	XS530B1PBM12		
XS1M30DB210B	XS530B1DBL01B (4)			XS3	
XS1M30DB210D	XS530B1DBM12			XS3P30NA340	XS530B1NAL2 (3)
XS1M30DB210LD	XS530B1DBM12 (1)	XS2		XS3P30NA340D	XS530B1NAM12 (3)
		XS2N30NA340	XS130B3NAL2	XS3P30NA340L1	XS530B1NAL5 (3)
		XS2N30NA340D	XS130B3NAM12	XS3P30PA340	XS530B1PAL2 (3)
XS1M30DA214D	XS530B1CAM12	XS2N30NA340L1	XS130B3NAL5	XS3P30PA340D	XS530B1PAM12 (3)
XS1M30DA214LD	XS530B1CAL08M12	XS2N30NA340L2	XS130B3NAL10	XS3P30PA340L1	XS530B1PAL5 (3)
		XS2N30NB340	XS130B3NBL2	XS3P30PA340L2	XS530B1PAL10 (3)
		XS2N30NC410L1	XS2N30NC410D + XZCPV1141L5		
XS1M30PA349D	XS630B1PAM12 (5)	XS2N30PC410	XS130B3PCL2	XS3P30PA370	XS530BLPAL2 (3)
		XS2N30PC410D	XS130B3PCM12	XS3P30PA370L1	XS530BLPAL5 (3)
		XS2N30PC410L1	XS130B3PCM12 + XZCPV1141L5	XS3P30PA370L2	XS530BLPAL10 (3)
XS1M30NA370	XS530BLNAL2	XS2N30NB340D	XS130B3NBM12	XS3P30NA370	XS530BLNAL2 (3)
XS1M30NA370B	XS630B1NAL01B (4)	XS2N30PA340	XS130B3PAL2	XS3P30NA370L1	XS530BLNAL5 (3)
XS1M30NA370C	XS630B1NAL01C (4)	XS2N30PA340D	XS130B3PAM12		
XS1M30NA370D	XS530BLNAM12	XS2N30PA340L1	XS130B3PAL5	XS4	
XS1M30NA370L1	XS530BLNAL5	XS2N30PA340L2	XS130B3PAL10	XS4P30NA370B	XS4P30NA370L01B (4)
XS1M30NA370L2	XS530BLNAL10	XS2N30PB340	XS130B3PBL2	XS4P30NB370B	XS4P30NB370L01B (4)
XS1M30NB370	XS530BLNBL2	XS2N30PB340D	XS130B3PBM12	XS4P30NC410L2	XS4P30NC410D + XZCPV1141L10
XS1M30NB370B	XS630B1NBL01B (4)			XS4P30PA370B	XS4P30PA370L01B (4)
XS1M30NB370C	XS630B1NBL01C (4)			XS4P30PB370B	XS4P30PB370L01B (4)
XS1M30NB370D	XS530BLNBM12			XS4P30PC410L1	XS4P30PC410D + XZCPV1141L5
XS1M30NB370L1	XS530BLNBL5	XS2M30NA370	XS630B1NAL2	XS4P30PC410L2	XS4P30PC410D + XZCPV1141L10
XS1M30NB370L2	XS530BLNBL10	XS2M30NA370B	XS630B1NAL01B (4)		
XS1M30PA370	XS530BLPAL2	XS2M30NA370C	XS630B1NAL01C (4)		
XS1M30PA370A	XS630B1PAL01U78 (4)	XS2M30NA370D	XS630B1NAM12		
XS1M30PA370B	XS630B1PAL01B (4)	XS2M30NA370L1	XS630B1NAL5		
XS1M30PA370C	XS630B1PAL01C (4)	XS2M30NA370L2	XS630B1NAL10		
XS1M30PA370D	XS530BLPAM12	XS2M30NB370	XS630B1NBL2		
XS1M30PA370G	XS630B1PAL01G (4)	XS2M30NB370B	XS630B1NBL01B (4)		
XS1M30PA370L1	XS530BLPAL5	XS2M30NB370C	XS630B1NBL01C (4)		
XS1M30PA370L2	XS530BLPAL10	XS2M30NB370D	XS630B1NBM12		
XS1M30PB370	XS530BLPBL2	XS2M30NB370L1	XS630B1NBL5		
XS1M30PB370B	XS630B1PBL01B (4)	XS2M30NB370L2	XS630B1NBL10		
XS1M30PB370C	XS630B1PBL01C (4)	XS2M30PA370	XS630B1PAL2		
XS1M30PB370D	XS530BLPBM12	XS2M30PA370A	XS630B1PAL01U78 (4)		
XS1M30PB370G	XS630B1PBL01G (4)	XS2M30PA370B	XS630B1PAL01B (4)		
XS1M30PB370L1	XS530BLPBL5	XS2M30PA370C	XS630B1PAL01C (4)		
XS1M30PB370L2	XS530BLPBL10	XS2M30PA370D	XS630B1PAM12		

(3) For the new sensor, the metal case replaces the plastic case.

(5) For the new sensor, $S_n = 15$ mm instead of 20 mm.

Substitution table

Sensors with the closest functionalities

Inductive proximity sensors

Old sensor	New XS sensor	Old sensor	New XS sensor	Old sensor	New XS sensor
Cylindrical type, AC or DC		Diameter 18 mm (continued)		Diameter 30 mm (continued)	
Diameter 12 mm		XS1		XS1M30MB230C	
XS1		XS1M18MA239A		XS1M30MB230G	
XS1M12MA230	XS512B1MAL2	XS1M18MA239K	XS618B1MAU20 (5)	XS1M30MB230K	XS530B1MBU20
XS1M12MA230K	XS512B1MAU20	XS2		XS1M30MB230L1	XS530B1MBL5
XS1M12MA230L1	XS512B1MAL5	XS2M18MA230		XS1M30MB230L2	XS530B1MBL10
XS1M12MA230L2	XS512B1MAL10	XS2M18MA230A		XS1M30MA239	
XS1M12MB230	XS512B1MBL2	XS2M18MA230B		XS1M30MA239A	
XS1M12MB230K	XS512B1MBU20	XS2M18MA230C		XS2	
XS1M12MB230L1	XS512B1MBL5	XS2M18MA230G		XS2M30MA230	
XS1M12MB230L2	XS512B1MBL10	XS2M18MA230K		XS2M30MA230A	
XS612B1MAL2		XS2M18MA230L1		XS2M30MA230B	
XS1M12MA239	XS612B1MAU20	XS2M18MB230		XS2M30MA230C	
XS1M12MA239K	XS612B1MAU20	XS2M18MB230A		XS2M30MA230G	
XS2		XS2M18MB230B		XS2M30MA230K	
XS2M12MA230	XS612B1MAL2	XS2M18MB230C		XS2M30MA230L1	
XS2M12MA230K	XS612B1MAU20	XS2M18MB230G		XS2M30MA230L2	
XS2M12MA230L1	XS612B1MAL5	XS2M18MB230K		XS2M30MB230	
XS2M12MA230L2	XS612B1MAL10	XS2M18MB230L1		XS2M30MB230A	
XS2M12MB230	XS612B1MBL2	XS2M18MB230L2		XS2M30MB230B	
XS2M12MB230K	XS612B1MBU20	XS3		XS2M30MB230C	
XS2M12MB230L1	XS612B1MBL5	XS3P18MA230		XS2M30MB230G	
XS2M12MB230L2	XS612B1MBL10	XS3P18MA230K		XS2M30MB230K	
XS612B1MAL2 (3)		XS3P18MA230L1		XS2M30MB230L1	
XS3P12MA230	XS612B1MAU20 (3)	XS3P18MA230L2		XS2M30MB230L2	
XS3P12MA230K	XS612B1MAU20 (3)	XS3P18MB230		XS3	
XS3P12MA230L1	XS612B1MAL5 (3)	XS3P18MB230A		XS3P30MA230	
XS3P12MA230L2	XS612B1MAL10 (3)	XS3P18MB230K		XS3P30MA230K	
XS3P12MB230	XS612B1MBL2 (3)	XS3P18MB230L1		XS3P30MA230L1	
XS3P12MB230K	XS612B1MBU20 (3)	XS4		XS3P30MA230L2	
XS3P12MB230L1	XS612B1MBL5 (3)	XS4P18MA230B		XS3P30MB230	
Diameter 18 mm		XS4P18MA230C		XS3P30MB230K	
XS1		XS4P18MA230G		XS3P30MB230L1	
XS1M18MA230	XS518B1MAL2	XS4P18MB230B		XS4	
XS1M18MA230A	XS618B1MAL01U78 (4)	XS4P18MB230C		XS4P30MA230B	
XS1M18MA230B	XS618B1MAL01B (4)	Diameter 30 mm		XS4P30MA230C	
XS1M18MA230C	XS618B1MAL01C (4)	XS1		XS4P30MA230G	
XS1M18MA230G	XS618B1MAL01G (4)	XS1M30MA230		XS4P30MA230L1	
XS1M18MA230K	XS518B1MAU20	XS1M30MA230A		XS4P30MB230B	
XS1M18MA230L1	XS518B1MAL5	XS1M30MA230B		XS4P30MB230C	
XS1M18MA230L2	XS518B1MAL10	XS1M30MA230C		XS4P30MA230L1B (4)	
XS1M18MB230	XS518B1MBL2	XS1M30MA230G		XS4P30MA230L1G (4)	
XS1M18MB230A	XS618B1MBL01U78 (4)	XS1M30MA230K		XS4P30MA230L1G (4)	
XS1M18MB230B	XS618B1MBL01B (4)	XS1M30MA230L1		XS4P30MA230L1G (4)	
XS1M18MB230C	XS618B1MBL01C (4)	XS1M30MA230L2		XS4P30MA230L1G (4)	
XS1M18MB230G	XS618B1MBL01G (4)	XS1M30MB230		XS4P30MA230L1G (4)	
XS1M18MB230K	XS518B1MBU20	XS1M30MB230A		XS4P30MA230L1G (4)	
XS1M18MB230L1	XS518B1MBL5	XS1M30MB230B		XS4P30MA230L1G (4)	
XS1M18MB230L2	XS518B1MBL10	XS1M30MB230C		XS4P30MA230L1G (4)	
XS1M18MA239	XS618B1MAL2 (5)	XS530B1MAL2		XS4P30MA230L1G (4)	

(3) For the new sensor, the metal case replaces the plastic case.

(4) For the new sensor, connectors A, B, C and G on 0.1 m flying lead replace integral connectors A, B, C and G.

(5) For the new sensor, Sn = 8 mm instead of 10 mm.

Substitution table

Sensors with the closest functionalities

Inductive proximity sensors

Old sensor	New XS sensor	Old sensor	New XS sensor
Block type		40 x 40 x 70 mm and 40 x 40 x 117 mm (continued)	
40 x 40 x 70 mm and 40 x 40 x 117 mm		XS8	
XS7		XS8C40DA210	XS8C4A1DPG13
XS7C40DA210	XS7C4A1DPG13	XS8C40DA210H29	XS8C4A1DPP20
XS7C40DA210A	XS7C4A1DPU78	XS8C40DA214D	XS8C4A1DPM12
XS7C40DA210D	XS7C4A1DPM12	XS8C40DP210	XS8C4A1DPG13
XS7C40DA210H29	XS7C4A1DPP20	XS8C40DP210H29	XS8C4A1DPP20
XS7C40DA210H7	XS7C4A1DPN12	XS8C40DP210H7	XS8C4A1DPN12
XS7C40DA214D	XS7C4A1DPM12	XS8C40FP260	XS8C4A1MPG13
XS7C40DP210	XS7C4A1DPG13	XS8C40FP260H29	XS8C4A1MPP20
XS7C40DP210H29	XS7C4A1DPP20	XS8C40FP260H7	XS8C4A1MPN12
XS7C40DP210H7	XS7C4A1DPN12	XS8C40MP230	XS8C4A1MPG13
XS7C40FP260	XS7C4A1MPG13	XS8C40MP230H29	XS8C4A1MPP20
XS7C40FP260A	XS7C4A1MPU78	XS8C40MP230H7	XS8C4A1MPN12
XS7C40FP260H29	XS7C4A1MPP20	XS8C40NC440	XS8C4A1NCG13
XS7C40FP260H7	XS7C4A1MPN12	XS8C40NC440H29	XS8C4A1NCP20
XS7C40KPM40	XS9C4A1PCG13	XS8C40NC449	XS8C4A4NCG13
XS7C40KPM40H29	XS9C4A1PCP20	XS8C40NC449H29	XS8C4A4NCP20
XS7C40KPM40H7	XS9C4A1PCN12	XS8C40NC449H7	XS8C4A4NCN12
XS7C40MP230	XS7C4A1MPG13	XS8C40PC440	XS8C4A1PCG13
XS7C40MP230A	XS7C4A1MPU78	XS8C40PC440D	XS8C4A1PCM12
XS7C40MP230H29	XS7C4A1MPP20	XS8C40PC440H29	XS8C4A1PCP20
XS7C40MP230H7	XS7C4A1MPN12	XS8C40PC440H7	XS8C4A1PCN12
XS7C40NC440	XS8C4A1NCG13	XS8C40PC449	XS8C4A4PCG13
XS7C40NC440D	XS8C4A1NCM12	XS8C40PC449D	XS8C4A4PCM12
XS7C40NC440H29	XS8C4A1NCP20	XS8C40PC449H29	XS8C4A4PCP20
XS7C40NC440H7	XS8C4A1NCN12	XS8C40PC449H7	XS8C4A4PCN12
XS7C40NC449	XS8C4A1NCG13	XS8T4NC440	XS8C2A1NCM12 + XZCP1141L2
XS7C40NC449H29	XS8C4A1NCP20	XS8T4NC440LD01	XS8C2A1NCM12
XS7C40NC449H7	XS8C4A1NCN12	XS8T4PC440	XS8C2A1PCM12 + XZCP1141L2
XS7C40PC440	XS8C4A1PCG13	XS8T4PC440L1	XS8C2A1PCM12 + XZCP1141L5
XS7C40PC440D	XS8C4A1PCM12	XS8T4PC440L2	XS8C2A1PCM12 + XZCP1141L10
XS7C40PC440H29	XS8C4A1PCP20	XS8T4PC440LD	XS8C2A1PCM12
XS7C40PC440H7	XS8C4A1PCN12	XS8T4PC440LD01	XS8C2A1PCM12
XS7C40PC449	XS8C4A1PCG13	40 x 40 x 117 mm	
XS7C40PC449D	XS8C4A1PCM12	XSCH	
XS7C40PC449H29	XS8C4A1PCP20	XSCH203629	XS9C4A2A2G13
XS7C40PC449H7	XS8C4A1PCN12	XSCH203629H7	XS9C4A2A2N12
XS7T4DA210	XS7C2A1DAM12 + XZCP1141L2	XSCH207629	XS9C4A2A1G13
XS7T4DA214LD	XS8C2A1CAM12	XSCH207629H7	XS9C4A2A1N12
XS7T4DA214LD01	XS8C2A1CAM12		
XS7T4DA214LD01W	XS8C2A1CAM12 + XSZPKC2		
XS7T4DA214LDW	XS8C2A1CAM12 + XSZPKC2		
XS7T4NC440	XS8C2A1NCM12 + XZCP1141L2		
XS7T4NC440LD	XS8C2A1NCM12		
XS7T4NC440LD01	XS8C2A1NCM12		
XS7T4PC440	XS8C2A1PCM12 + XZCP1141L2		
XS7T4PC440LD	XS8C2A1PCM12		

		XS130B3NBL2	33	XS1N05NB310	68	XS212SANAM12	92	XS4P08PA370	64
AB1FU10135U	118	XS130B3NBM12	33	XS1N05NB311	68	XS212SAPAL2	92	XS4P08PB340	64
X		XS130B3PAL2	33	XS1N05NB311S	68	XS212SAPAM12	92	XS4P08PC410	56
	XS106B3NAL2	32	XS130B3PAL2TQ	33	XS1N05PA310	68	XS218AAMAL2	98	XS4P12AB110
XS106B3NAM8	32	XS130B3PAM12	33	XS1N05PA311	68	XS218AAMAU20	98	XS4P12AB120	81
XS106B3NBL2	32	XS130B3PAM12TQ	33	XS1N05PA311S	68	XS218AANAL2	96	XS4P12KP340	62
XS106B3NBM8	32	XS130B3PBL2	33	XS1N05PB310	68	XS218AANAM12	96	XS4P12KP340D	62
XS106B3PAL2	32	XS130B3PBM12	33	XS1N05PB311	68	XS218AAPAL2	96	XS4P12MA230	64
XS106B3PAL2TQ	32	XS130B3PCL2	60	XS1N05PB311S	68	XS218AAPAM12	96	XS4P12MA230K	64
XS106B3PAM12	32	XS130B3PCM12	60	XS1N08PA349	66	XS218B4NAL2	42	XS4P12MB230	64
XS106B3PAM8	32	XS1L04NA310	68	XS1N08PA349D	66	XS218B4NAM12	42	XS4P12MB230K	64
XS106B3PAM8TQ	32	XS1L04NA310S	68	XS1N08PA349S	66	XS218B4PAL2	42	XS4P12NA340	64
XS106B3PBL2	32	XS1L04NA311	68	XS1N08PB349	66	XS218B4PAL5	42	XS4P12NA370	64
XS106B3PBM8	32	XS1L04NA311S	68	XS1N08PB349D	66	XS218B4PAM12	42	XS4P12NB340	64
XS108B3NAL2	32	XS1L04NB310	68	XS1N08PB349S	66	XS218B4PBL2	42	XS4P12NB370	64
XS108B3NAL2TQ	32	XS1L04NB310S	68	XS1N12NA349	66	XS218B4PBM12	42	XS4P12PA340	64
XS108B3NAM12	32	XS1L04NB311	68	XS1N12NA349D	66	XS218SAMAL2	94	XS4P12PA370	64
XS108B3NAM8	32	XS1L04NB311S	68	XS1N12NB349	66	XS218SAMAU20	94	XS4P12PB340	64
XS108B3NAM8TQ	32	XS1L04PA310	68	XS1N12NB349D	66	XS218SANAL2	92	XS4P12PB370	64
XS108B3NBL2	32	XS1L04PA310S	68	XS1N12NC410	56	XS218SANAM12	92	XS4P12PC410	56
XS108B3NBM12	32	XS1L04PA311	68	XS1N12NC410D	56	XS218SAPAL2	92	XS4P12PC410D	56
XS108B3NBM8	32	XS1L04PA311S	68	XS1N12PA349	66	XS218SAPAM12	92	XS4P18AB110	82
XS108B3PAL2	32	XS1L04PB310	68	XS1N12PA349D	66	XS230AAMAL2	98	XS4P18AB120	82
XS108B3PAL2TQ	32	XS1L04PB310S	68	XS1N12PB349	66	XS230AAMAU20	98	XS4P18KP340	62
XS108B3PAM12	32	XS1L04PB311	68	XS1N12PB349D	66	XS230AANAL2	96	XS4P18KP340D	62
XS108B3PAM12TQ	32	XS1L04PB311S	68	XS1N12PC410	56	XS230AANAM12	96	XS4P18MA230	64
XS108B3PAM8	32	XS1L06NC410	56	XS1N12PC410D	56	XS230AAPAL2	96	XS4P18MA230K	64
XS108B3PAM8TQ	32	XS1L06PC410	56	XS1N18NA349	66	XS230AAPAM12	96	XS4P18MB230	64
XS108B3PBL2	32	XS1M08NC410	56	XS1N18NA349D	66	XS230SAMAL2	94	XS4P18MB230K	64
XS108B3PBM12	32	XS1M08NC410D	56	XS1N18NB349	66	XS230SAMAU20	94	XS4P18NA340	64
XS108B3PBM8	32	XS1M08PC410	56	XS1N18NB349D	66	XS230SANAL2	92	XS4P18NA370	64
XS112B3NAL2	32	XS1M08PC410D	56	XS1N18NC410	57	XS230SANAM12	92	XS4P18NB340	64
XS112B3NAL2TQ	32	XS1M12AB120	81	XS1N18NC410D	57	XS230SAPAL2	92	XS4P18NB370	64
XS112B3NAM12	32	XS1M12KP340	62	XS1N18PA349	66	XS230SAPAM12	92	XS4P18PA340	64
XS112B3NAM12TQ	32	XS1M12KP340D	62	XS1N18PA349D	66	XS2L2SANAL2	92	XS4P18PA370	64
XS112B3NBL2	32	XS1M12MA250	54	XS1N18PB349	66	XS2L2SANAM12	92	XS4P18PB340	64
XS112B3NBM12	32	XS1M12MA250K	54	XS1N18PB349D	66	XS2L2SAPAL2	92	XS4P18PB370	64
XS112B3PAL2	32	XS1M12MB250	54	XS1N18PC410	57	XS2L2SAPAM12	92	XS4P18PC410	57
XS112B3PAL2TQ	32	XS1M12MB250K	54	XS1N18PC410D	57	XS2M08NC410	56	XS4P18PC410D	57
XS112B3PAM12	32	XS1M18AB120	82	XS1N30NA349	66	XS2M08NC410D	56	XS4P30AB110	83
XS112B3PAM12TQ	32	XS1M18KP340	62	XS1N30NA349D	66	XS2M12KP340	62	XS4P30AB120	83
XS112B3PBL2	32	XS1M18KP340D	62	XS1N30NB349	66	XS2M12KP340D	62	XS4P30KP340	62
XS112B3PBM12	32	XS1M18KPM40	112	XS1N30NB349D	66	XS2M12MA250	54	XS4P30KP340D	62
XS112B3PBM12TQ	32	XS1M18KPM40D	112	XS1N30NC410	57	XS2M12MA250K	54	XS4P30MA230	64
XS112B3PBM12TQ	32	XS1M18MA250	54	XS1N30NC410D	57	XS2M12MB250	54	XS4P30MA230K	64
XS112B3PCL2	60	XS1M18MA250K	54	XS1N30PA349	66	XS2M18KP340	62	XS4P30MB230	64
XS112B3PCM12	60	XS1M18MB250	54	XS1N30PA349D	66	XS2M18KP340D	62	XS4P30MB230K	64
XS118B3NAL2	33	XS1M18MB250K	54	XS1N30PB349	66	XS2M18MA250	54	XS4P30NA340	64
XS118B3NAL2TQ	33	XS1M18PAS20	116	XS1N30PB349D	66	XS2M18MA250K	54	XS4P30NA370	64
XS118B3NAM12	33	XS1M18PAS20D	117	XS1N30PC410	57	XS2M18MB250	54	XS4P30NB340	64
XS118B3NAM12TQ	33	XS1M18PAS40	116	XS1N30PC410D	57	XS2M18MB250K	54	XS4P30NB370	64
XS118B3NBL2	33	XS1M18PAS40D	117	XS212AANAL2	96	XS2M30KP340	62	XS4P30PA340	64
XS118B3NBM12	33	XS1M30AB120	83	XS212AANAM12	96	XS2M30KP340D	62	XS4P30PA370	64
XS118B3PAL2	33	XS1M30KP340	62	XS212AAPAL2	96	XS2M30MA250	54	XS4P30PB340	64
XS118B3PAL2TQ	33	XS1M30KP340D	62	XS212AAPAM12	96	XS2M30MA250K	54	XS4P30PB370	64
XS118B3PAM12	33	XS1M30KPM40	113	XS212B4NAL2	42	XS2M30MB250	54	XS4P30PC410	57
XS118B3PAM12TQ	33	XS1M30KPM40LD	113	XS212B4NAM12	42	XS2M30MB250K	54	XS4P30PC410D	57
XS118B3PBL2	33	XS1M30MA250	54	XS212B4NBL2	42	XS4P08MA230	64	XS506B1NAL2	22
XS118B3PBM12	33	XS1M30MA250K	54	XS212B4PAL2	42	XS4P08MA230K	64	XS506B1NAM8	22
XS118B3PCL2	60	XS1M30MB250	54	XS212B4PAL5	42	XS4P08MB230	64	XS506B1NBL2	22
XS118B3PCM12	60	XS1M30MB250K	54	XS212B4PAM12	42	XS4P08MB230K	64	XS506B1NBM8	22
XS130B3NAL2	33	XS1N05NA310	68	XS212B4PBL2	42	XS4P08NA340	64	XS506B1PAL2	22
XS130B3NAM12	33	XS1N05NA311	68	XS212B4PBM12	42	XS4P08NB340	64	XS506B1PAM12	22
XS130B3NAM12TQ	33	XS1N05NA311S	68	XS212SANAL2	92	XS4P08PA340	64	XS506B1PAM8	22

Product reference index

XS range

XS506B1PBL2	22	XS512BLPBM12	23	XS530B1PAL2	22	XS612B1MBU20	38	XS618B4NAL2	40
XS506B1PBM8	22	XS512BSCAL08M12	26	XS530B1PAM12	22	XS612B1NAL2	34	XS618B4NAM12	40
XS506BSCAL01M12	26	XS512BSCAM12	26	XS530B1PBL2	22	XS612B1NAM12	34	XS618B4NBL2	40
XS506BSCAL2	26	XS512BSDAL2	26	XS530B1PBM12	22	XS612B1NBL2	34	XS618B4NBM12	40
XS506BSCBL2	26	XS512BSDAM12	26	XS530BLNAL2	23	XS612B1NBM12	34	XS618B4PAL2	40
XS508B1CAL08M12	27	XS512BSDBL2	26	XS530BLNAM12	23	XS612B1PAL2	34	XS618B4PAM12	40
XS508B1CAM12	27	XS512BSDBM12	26	XS530BLNBL2	23	XS612B1PAM12	34	XS618B4PBL2	40
XS508B1DAL08M12	27	XS518B1CAL08M12	27	XS530BLNBM12	23	XS612B1PBL2	34	XS618B4PBM12	40
XS508B1DAL2	27	XS518B1CAM12	27	XS530BLPAL2	23	XS612B1PBM12	34	XS630B1DAL2	36
XS508B1DAM12	27	XS518B1DAL01B	27	XS530BLPAM12	23	XS612B2NAL01M12	72	XS630B1DAM12	36
XS508B1DBL2	27	XS518B1DAL01C	27	XS530BLPBL2	23	XS612B2NBL01M12	72	XS630B1DBL2	36
XS508B1DBM12	27	XS518B1DAL01G	27	XS530BLPBM12	23	XS612B2PAL01M12	72	XS630B1DBM12	36
XS508B1NAL2	22	XS518B1DAL2	27	XS530BSCAL08M12	26	XS612B2PBL01M12	72	XS630B1MAL01B	38
XS508B1NAM12	22	XS518B1DAL2TF	27	XS530BSCAM12	26	XS612B3DAL2	36	XS630B1MAL01C	38
XS508B1NAM8	22	XS518B1DAM12	27	XS530BSDAL2	26	XS612B3DAM12	36	XS630B1MAL01G	38
XS508B1NBL2	22	XS518B1DBL01B	27	XS530BSDAM12	26	XS612B3DBL2	36	XS630B1MAL2	38
XS508B1NBM12	22	XS518B1DBL08M12	27	XS530BSDBL2	26	XS612B3DBM12	36	XS630B1MAU20	38
XS508B1NBM8	22	XS518B1DBL2	27	XS530BSDBM12	26	XS612B4NAL2	40	XS630B1MBL01B	38
XS508B1PAL2	22	XS518B1DBM12	27	XS606B1DAL2	36	XS612B4NAM12	40	XS630B1MBL01C	38
XS508B1PAM12	22	XS518B1MAL2	30	XS606B1DBL2	36	XS612B4NBL2	40	XS630B1MBL2	38
XS508B1PAM8	22	XS518B1MAU20	30	XS606B3CAL01M12	36	XS612B4NBM12	40	XS630B1MBU20	38
XS508B1PBL2	22	XS518B1MBL2	30	XS606B3CAL2	36	XS612B4PAL2	40	XS630B1NAL01B	34
XS508B1PBM12	22	XS518B1MBU20	30	XS606B3CBL2	36	XS612B4PAM12	40	XS630B1NAL2	34
XS508B1PBM8	22	XS518B1NAL2	22	XS608B1DAL2	36	XS612B4PBL2	40	XS630B1NAM12	34
XS508BLNAL2	23	XS518B1NAM12	22	XS608B1DAM12	36	XS612B4PBM12	40	XS630B1NBL2	34
XS508BLNAM12	23	XS518B1NBL2	22	XS608B1DBL2	36	XS618B1DAL2	36	XS630B1NBM12	34
XS508BLNBL2	23	XS518B1NBM12	22	XS608B1DBM12	36	XS618B1DAM12	36	XS630B1PAL01B	34
XS508BLNBM12	23	XS518B1PAL2	22	XS608B1NAL2	34	XS618B1DBL2	36	XS630B1PAL01C	34
XS508BLPAL2	23	XS518B1PAM12	22	XS608B1NAM12	34	XS618B1DBM12	36	XS630B1PAL01G	34
XS508BLPAM12	23	XS518B1PBL2	22	XS608B1NAM8	34	XS618B1MAL01B	38	XS630B1PAL2	34
XS508BLPBL2	23	XS518B1PBM12	22	XS608B1NBL2	34	XS618B1MAL01C	38	XS630B1PAM12	34
XS508BLPBM12	23	XS518BLNAL2	23	XS608B1NBM12	34	XS618B1MAL01G	38	XS630B1PBL01C	34
XS508BSCAL01M12	26	XS518BLNAM12	23	XS608B1NBM8	34	XS618B1MAL2	38	XS630B1PBL2	34
XS508BSCAL08M12	26	XS518BLNBL2	23	XS608B1PAL2	34	XS618B1MAU20	38	XS630B1PBM12	34
XS508BSCAL2	26	XS518BLNBM12	23	XS608B1PAM12	34	XS618B1MBL01B	38	XS630B2NAL01M12	72
XS508BSCBL01M12	26	XS518BLPAL2	23	XS608B1PAM8	34	XS618B1MBL01C	38	XS630B2NBL01M12	72
XS508BSCBL2	26	XS518BLPAM12	23	XS608B1PBL2	34	XS618B1MBL01G	38	XS630B2PAL01M12	72
XS512B1CAL08M12	27	XS518BLPBL2	23	XS608B1PBM12	34	XS618B1MBL2	38	XS630B2PBL01M12	72
XS512B1CAM12	27	XS518BLPBM12	23	XS608B1PBM8	34	XS618B1MBU20	38	XS630B3DAL2	36
XS512B1DAL08U78	27	XS518BSCAL08M12	26	XS608B1PCL2	60	XS618B1NAL01B	34	XS630B3DAM12	36
XS512B1DAL2	27	XS518BSCAM12	26	XS608B1PCM12	60	XS618B1NAL2	34	XS630B3DBL2	36
XS512B1DAM12	27	XS518BSDAL2	26	XS608B3CAL01M12	36	XS618B1NAM12	34	XS630B3DBM12	36
XS512B1DBL08M12	27	XS518BSDAM12	26	XS608B3CAL2	36	XS618B1NBL2	34	XS630B4MAL2	44
XS512B1DBL2	27	XS518BSDBL2	26	XS608B3CBL01M12	36	XS618B1NBM12	34	XS630B4MAU20	44
XS512B1DBM12	27	XS518BSDBM12	26	XS608B3CBL2	36	XS618B1PAL01B	34	XS630B4MBL2	44
XS512B1MAL2	30	XS530B1CAL08M12	27	XS608B4NAL2	40	XS618B1PAL01C	34	XS630B4MBU20	44
XS512B1MAU20	30	XS530B1CAM12	27	XS608B4NAM12	40	XS618B1PAL01G	34	XS630B5NAL2	40
XS512B1MBL2	30	XS530B1DAL01B	27	XS608B4NAM8	40	XS618B1PAL2	34	XS630B5NAM12	40
XS512B1MBU20	30	XS530B1DAL01C	27	XS608B4NBL2	40	XS618B1PAM12	34	XS630B5NBL2	40
XS512B1NAL2	22	XS530B1DAL01G	27	XS608B4NBM12	40	XS618B1PBL01B	34	XS630B5PAL2	40
XS512B1NAM12	22	XS530B1DAL2	27	XS608B4NBM8	40	XS618B1PBL2	34	XS630B5PAM12	40
XS512B1NBL2	22	XS530B1DAL2TF	27	XS608B4PAL2	40	XS618B1PBM12	34	XS630B5PBL2	40
XS512B1NBM12	22	XS530B1DAM12	27	XS608B4PAM12	40	XS618B2NAL01M12	72	XS630B5PBM12	40
XS512B1PAL2	22	XS530B1DBL01B	27	XS608B4PAM8	40	XS618B2NBL01M12	72	XS7C1A1CAL01M12	48
XS512B1PAM12	22	XS530B1DBL2	27	XS608B4PBL2	40	XS618B2PAL01M12	72	XS7C1A1CAL08M12	48
XS512B1PBL2	22	XS530B1DBM12	27	XS608B4PBM12	40	XS618B2PBL01M12	72	XS7C1A1DAL01M12	48
XS512B1PBM12	22	XS530B1MAL2	30	XS608B4PBM8	40	XS618B3DAL2	36	XS7C1A1DAL2	48
XS512BLNAL2	23	XS530B1MAU20	30	XS612B1DAL2	36	XS618B3DAM12	36	XS7C1A1DAM8	48
XS512BLNAM12	23	XS530B1MBL2	30	XS612B1DAM12	36	XS618B3DBL2	36	XS7C1A1DBL01M12	48
XS512BLNBL2	23	XS530B1MBU20	30	XS612B1DBL2	36	XS618B3DBM12	36	XS7C1A1DBL2	48
XS512BLNBM12	23	XS530B1NAL2	22	XS612B1DBM12	36	XS618B4MAL2	44	XS7C1A1DBM8	48
XS512BLPAL2	23	XS530B1NAM12	22	XS612B1MAL2	38	XS618B4MAU20	44	XS7C1A1NAL01M12	48
XS512BLPAM12	23	XS530B1NBL2	22	XS612B1MAU20	38	XS618B4MBL2	44	XS7C1A1NAL2	48
XS512BLPBL2	23	XS530B1NBM12	22	XS612B1MBL2	38	XS618B4MBU20	44	XS7C1A1NAM8	48

Product reference index

XS range

XS7C1A1NBL01M12	48	XS7G12MA230	104	XS8D1A1PAM12	74	XS9C4A1NCP20	114	XSZB118	96
XS7C1A1NBL2	48	XS7G12MB230	104	XS8D1A1PBL2	74	XS9C4A1PCP20	114		98
XS7C1A1NBM8	48	XS7G12NA140	102	XS8D1A1PBM12	74	XS9C4A2A1P20	88		118
XS7C1A1PAL01M12	48	XS7G12NA140S	102	XS8E1A1MAL01U20	74	XS9C4A2A2P20	88	XSZB130	22
XS7C1A1PAL2	48	XS7G12NC440	102	XS8E1A1MAL2	74	XS9D111A1L2	85		23
XS7C1A1PAM8	48	XS7G12PA140	102	XS8E1A1MBL01U20	74	XS9D111A1M12	85		26
XS7C1A1PBL01M12	48	XS7G12PA140S	102	XS8E1A1MBL2	74	XS9D111A2L2	87		27
XS7C1A1PBL2	48	XS7G12PC440	102	XS8E1A1NAL01M12	74	XS9D111A2M12	87		30
XS7C1A1PBM8	48	XS7J1A1DAL01M8	46	XS8E1A1NAL2	74	XS9E111A1L01M12	85		33
XS7C2A1DAM12	50	XS7J1A1DAL2	46	XS8E1A1NAM8	74	XS9E111A1L2	85		34
XS7C2A1DBM12	50	XS7J1A1DBL01M8	46	XS8E1A1NBL01M12	74	XS9E111A2L01M12	87		36
XS7C2A1MAU20	50	XS7J1A1DBL2	46	XS8E1A1NBL2	74	XS9E111A2L2	87		38
XS7C2A1MBU20	50	XS7J1A1NAL01M8	46	XS8E1A1NBM8	74	XS9E11RMBL01U20	79		40
XS7C2A1NAM12	50	XS7J1A1NAL2	46	XS8E1A1PAL01M12	74	XS9E11RPBL01M12	79		44
XS7C2A1NBM12	50	XS7J1A1NBL01M8	46	XS8E1A1PAL2	74	XS9F111A1L01M8	85		54
XS7C2A1PAM12	50	XS7J1A1NBL2	46	XS8E1A1PAM8	74	XS9F111A1L2	85	XSZB130	62
XS7C2A1PBM12	50	XS7J1A1PAL01M8	46	XS8E1A1PBL01M12	74	XS9F111A2L01M8	87		66
XS7C4A1DPP20	52	XS7J1A1PAL2	46	XS8E1A1PBL2	74	XS9F111A2L2	87		72
XS7C4A1MPP20	52	XS7J1A1PBL01M8	46	XS8E1A1PBM8	74	XSAV11373	77	XSZB165	22
XS7D1A1CAM12	48	XS7J1A1PBL2	46	XS8G12MA230	104	XSAV11801	77		23
XS7D1A1DAL2	48	XS8C1A1MAL01U20	74	XS8G12MB230	104	XSAV12373	77		26
XS7D1A1DAM12	48	XS8C1A1MAL2	74	XS8G12NA140	102	XSAV12801	77		33
XS7D1A1DBL2	48	XS8C1A1MBL01U20	74	XS8G12NA140S	102	XSCZ01	118	XSZB165	36
XS7D1A1DBM12	48	XS8C1A1MBL2	74	XS8G12NC440	102	XSZA020	118	XSZBC00	118
XS7D1A1NAL2	48	XS8C1A1NAL01M12	74	XS8G12PA140	102	XSZA034	118	XSZBC10	118
XS7D1A1NAM12	48	XS8C1A1NAL2	74	XS8G12PA140S	102	XSZB104	118	XSZBC90	118
XS7D1A1NBL2	48	XS8C1A1NAM8	74	XS8G12PC440	102	XSZB105	118	XSZBD10	118
XS7D1A1NBM12	48	XS8C1A1NBL01M12	74	XS908R1PAM12	100	XSZB108	22	XSZBE00	118
XS7D1A1PAL2	48	XS8C1A1NBL2	74		101		23	XSZBE10	118
XS7D1A1PAM12	48	XS8C1A1NBM8	74	XS908R4PAM12	100		26	XSZBE90	118
XS7D1A1PBL2	48	XS8C1A1PAL01M12	74		101		27	XSZBF00	118
XS7D1A1PBM12	48	XS8C1A1PAL2	74	XS912R1PAM12	100		33	XSZBF90	118
XS7D1A3CAM12DIN	106	XS8C1A1PAM8	74		101		34	XSZBJ00	118
XS7E1A1CAL01M12	48	XS8C1A1PBL01M12	74	XS912R4PAM12	100		36	XSZBJ90	118
XS7E1A1CAL08M12	48	XS8C1A1PBL2	74		101		40		118
XS7E1A1DAL01M12	48	XS8C1A1PBM8	74	XS912RWPAM12	108		57	XSZBPM12	72
XS7E1A1DAL2	48	XS8C2A1DAM12	50		109		66		79
XS7E1A1DAM8	48	XS8C2A1DAM12	50	XS912S1PAM12	90	XSZB108	118	XSZBPM12	118
XS7E1A1DBL01M12	48	XS8C2A1DBM12	50		91	XSZB112	22	XSZBS12	90
XS7E1A1DBL2	48	XS8C2A1MAU20	50	XS912S4PAM12	90		23		92
XS7E1A1DBM8	48	XS8C2A1MBU20	50		91		26	XSZBS30	90
XS7E1A1DAL01M12	48	XS8C2A1NCM12	50	XS918R1PAM12	100		27		92
XS7E1A1DAL2	48	XS8C2A1PCM12	50		101		30		94
XS7E1A1NAL01M12	48	XS8C2A1PCP20	50	XS918R4PAM12	100		33	XSZE105	118
XS7E1A1NAL2	48	XS8C2A4DAM12	50		101		34	XSZE108	118
XS7E1A1NAM8	48	XS8C2A4DBM12	50	XS918RWPAM12	108		36	XSZE112	118
XS7E1A1NBL01M12	48	XS8C2A4MAU20	50		109		38	XSZE118	118
XS7E1A1NBL2	48	XS8C2A4MBU20	50	XS918S1PAM12	90		40	XSZE118	118
XS7E1A1NBM8	48	XS8C2A4NCM12	50		91		42	XSZE130	118
XS7E1A1PAL01M12	48	XS8C2A4PCM12	50	XS918S4PAM12	90		54	XSZE208	118
XS7E1A1PAL2	48	XS8C4A1DPP20	52		91		57	XSZE212	118
XS7E1A1PAM8	48	XS8C4A1MPP20	52	XS930R1PAM12	100		60	XSZE218	118
XS7E1A1PBL01M12	48	XS8C4A1NCP20	52		101		66	XSZE230	118
XS7E1A1PBL2	48	XS8C4A1PCP20	52	XS930R4PAM12	100	XSZB112	96	XSZE308	118
XS7E1A1PBM8	48	XS8C4A4DPP20	52		101		118	XSZE312	118
XS7F1A1DAL01M8	46	XS8C4A4MPP20	52	XS930S1PAM12	90	XSZB118	22	XSZE318	118
XS7F1A1DAL2	46	XS8C4A4NCP20	52		91		23	XSZE330	118
XS7F1A1DBL01M8	46	XS8C4A4PCP20	52	XS930S4PAM12	90		26	XSZF10	118
XS7F1A1DBL2	46	XS8D1A1MAL2	74		91		27	XSZP112	118
XS7F1A1NAL01M8	46	XS8D1A1MAU20	74	XS9C111A1L01M12	85		30	XSZP118	118
XS7F1A1NAL2	46	XS8D1A1MBL2	74	XS9C111A1L2	85		33	XSZP130	118
XS7F1A1NBL01M8	46	XS8D1A1MBU20	74	XS9C111A2L01M12	87		34	XSZPE13	118
XS7F1A1NBL2	46	XS8D1A1MBU20	74	XS9C111A2L2	87		36	XSZPKC2	115
XS7F1A1PAL01M8	46	XS8D1A1NAL2	74	XS9C11RMBL01U20	79		38	XSZPSC2	115
XS7F1A1PAL2	46	XS8D1A1NAM12	74	XS9C11RPBL01M12	79		40	XTAZ30	118
XS7F1A1PBL01M8	46	XS8D1A1NBL2	74	XS9C2A1NCM12	114		42	XUZA118	90
XS7F1A1PBL2	46	XS8D1A1NBL2	74	XS9C2A1PCM12	114		44		92
		XS8D1A1NBM12	74	XS9C2A2A1M12	88		54		94
		XS8D1A1PAL2	74	XS9C2A2A2M12	88		57		
							60		
							62		
							66		
							72		

XUZH2005	92
XUZH32	118
XUZE04	118
XUZE06	118
XUZE08	118
XZCP1141L10	51 100 108
XZCP1141L2	51 100 108
XZCP1141L5	51 100 108
XZCP1241L10	100 108
XZCP1241L2	100 108
XZCP1241L5	100 108
XZCP1865L10	51
XZCP1865L5	51
XZCP1965L10	51
XZCP1965L5	51
XZCPA1141L10	90 92 96
XZCPA1141L2	90 92 96
XZCPA1141L5	90 92 96
XZCPA1241L10	92 96
XZCPA1241L2	92 96
XZCPA1241L5	92 96
XZCPA1865L10	94 98
XZCPA1865L5	94 98
XZCPA1965L10	94 98
XZCPA1965L5	94 98
XZCRA151140A2	92 96
XZCRA151140A5	92 96

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier
F-92500 Rueil-Malmaison
France

www.tesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric