



WL170-P430

SICK
Sensor Intelligence.

Ordering information



Other models and accessories → www.sick.com/

Illustration may differ



Detailed technical data

Features

Functional principle	Photoelectric retro-reflective sensor
Dimensions (W x H x D)	12 mm x 37 mm x 28.6 mm
Housing design (light emission)	Rectangular
Sensing range max.	0.01 m ... 4 m ¹⁾
Sensing range	0.01 m ... 3 m ²⁾
Type of light	Visible red light
Light source	LED

¹⁾ Reflector PL80A.

²⁾ Reflector P250.

Mechanics/electronics

Supply voltage	10 V DC ... 30 V DC
Ripple	± 10 %
Current consumption	30 mA ¹⁾
Switching output	PNP
Switching mode	Light/dark switching
Switching mode selector	Selectable via L/D control cable
Response time	≤ 0.7 ms ²⁾
Connection type	Male connector M8, 4-pin
Optics material	Plastic, PMMA
Enclosure rating	IP67
Ambient operating temperature	-25 °C ... +55 °C
Ambient temperature, storage	-40 °C ... +70 °C
UL File No.	NRNT2.E128350 & NRNT8.E128350

¹⁾ Without load.

²⁾ Signal transit time with resistive load.


Safety-related parameters

MTTF_D	1,524 years
DC_{avg}	0 %


Classifications

eCl@ss 5.0	27270902
eCl@ss 5.1.4	27270902
eCl@ss 6.0	27270902
eCl@ss 6.2	27270902
eCl@ss 7.0	27270902
eCl@ss 8.0	27270902
eCl@ss 8.1	27270902
eCl@ss 9.0	27270902
eCl@ss 10.0	27270902
eCl@ss 11.0	27270902
ETIM 5.0	EC002717
ETIM 6.0	EC002717
ETIM 7.0	EC002717
UNSPSC 16.0901	39121528


Connection type




Connection diagram



Characteristic curve




Sensing range diagram




Reflector type		Operating range
1	PL 80 A	0.01 - 3.5 m
2	PL 50 A	0.01 - 3.0 m
	PL 40 A	0.01 - 3.0 m
3	P 250	0.01 - 2.5 m
	PL 30 A	0.01 - 2.5 m
	PL 31	0.01 - 2.5 m
4	PL 20	0.01 - 1.8 m
5	Reflective tape «Diamond Grade» 90x90 mm	0.01 - 1.3 m


Adjustments



Dimensional drawing (Dimensions in mm (inch))



- ① Mounting hole, Ø 3 mm with integrated M3 thread
- ② LED signal strength indicator, red: Light received >= switching threshold
- ③ Optical axis, receiver
- ④ Optical axis, sender



SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations www.sick.com